













Hawa Junior 100 Z











→ Upper Tracks and Accessories

Description		Material	Finish	Length	Version	Item No.
Upper track, pre-drilled 34 x 40 mm (1 11/32" x 1 9/16")		Aluminum	clear anodized	1.4 m (4' 7 1/8")	–	940.80.140
				1.6 m (5' 3")	–	940.80.160
				1.8 m (5' 10 7/8")	–	940.80.180
				2 m (6' 6 3/4")	–	940.80.200
				2.2 m (7' 2 5/8")	–	940.80.220
				2.5 m (8' 2 7/16")	–	940.80.250
				3 m (9' 10 1/8")	–	940.80.300
				4 m (13' 1 1/2")	–	940.80.400
				6 m (19' 8 1/4")	–	940.80.600
Upper track, wall mounted, pre-drilled, for wood and aluminum fascia		Aluminum	clear anodized	2 m (6' 6 3/4")	–	941.04.600
				2.5 m (8' 2 7/16")	–	941.04.601
				3 m (9' 10 1/8")	–	941.04.602
				4 m (13' 1 1/2")	–	941.04.603
Upper track, top mounted, pre-drilled, for wood and aluminum fascia		Aluminum	clear anodized	6 m (19' 8 1/4")	–	941.04.604
				2 m (6' 6 3/4")	–	941.04.605
				2.5 m (8' 2 7/16")	–	941.04.606
				3 m (9' 10 1/8")	–	941.04.607
Clip-on fascia, Height: 77 mm (3 1/32")		Aluminum	clear anodized	4 m (13' 1 1/2")	–	941.04.608
				6 m (19' 8 1/4")	–	941.04.609
				2 m (6' 6 3/4")	–	941.04.700
				2.5 m (8' 2 7/16")	–	941.04.701
				3 m (9' 10 1/8")	–	941.04.702
				4 m (13' 1 1/2")	–	941.04.703
				6 m (19' 8 1/4")	–	941.04.704
Spacer profile for wall mounted tracks		Plastic	gray	2 m (6' 6 3/4")	–	941.13.220
End cap for clip-on fascia, Height: 77 mm (3 1/32")		Aluminum	clear anodized	59 mm (2 5/16")	Left	941.04.400
				59 mm (2 5/16")	Right	941.04.401
				66 mm (2 19/32")	Left	941.04.402
				66 mm (2 19/32")	Right	941.04.403
Clip for wood and aluminum fascia, Mount every 400–600 mm (15 3/4"–23 5/8")		Aluminum	mill	97 mm (3 13/16")	–	940.60.065
Guide rail, glue-in type		Plastic	black	1.3 m (4' 3 3/16")	–	940.41.130
End cap for upper track, 940.80.series		Steel	chrome matt	–	–	940.80.021
Track stopper with adjustable retaining spring		–	–	–	–	941.04.300
SoftStop Junior 80/100 with adjustable retaining spring		–	–	–	–	941.04.301
SoftMove 100 soft close mechanism, maximum capacity 100 kg (220 lbs.); includes running gear and stopper		–	–	–	–	941.04.302
SoftMove 100 cover cap		Plastic	black	–	–	941.04.303

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.

Hawa Junior 80 Z

→ Upper Tracks and Accessories

Description		Material	Finish	Length	Version	Item No.
Upper track, pre-drilled		Aluminum	clear anodized	1.4 m (4' 7 1/8")	–	940.80.140
				1.6 m (5' 3")	–	940.80.160
				1.8 m (5' 10 7/8")	–	940.80.180
				2 m (6' 6 3/4")	–	940.80.200
				2.2 m (7' 2 5/8")	–	940.80.220
				2.5 m (8' 2 7/16")	–	940.80.250
				3 m (9' 10 1/8")	–	940.80.300
				4 m (13' 1 1/2")	–	940.80.400
Upper track, wall mounted, pre-drilled, for wood and aluminum fascia		Aluminum	clear anodized	6 m (19' 8 1/4")	–	940.80.600
				2 m (6' 6 3/4")	–	941.04.600
				2.5 m (8' 2 7/16")	–	941.04.601
				3 m (9' 10 1/8")	–	941.04.602
Upper track, top mounted, pre-drilled, for wood and aluminum fascia		Aluminum	clear anodized	4 m (13' 1 1/2")	–	941.04.603
				6 m (19' 8 1/4")	–	941.04.604
				2 m (6' 6 3/4")	–	941.04.605
				2.5 m (8' 2 7/16")	–	941.04.606
Clip-on fascia, Height: 77 mm (3 1/32")		Aluminum	clear anodized	3 m (9' 10 1/8")	–	941.04.607
				4 m (13' 1 1/2")	–	941.04.608
				6 m (19' 8 1/4")	–	941.04.609
				2 m (6' 6 3/4")	–	941.04.700
Clip-on fascia, Height: 77 mm (3 1/32")		Aluminum	clear anodized	2.5 m (8' 2 7/16")	–	941.04.701
				3 m (9' 10 1/8")	–	941.04.702
				4 m (13' 1 1/2")	–	941.04.703
				6 m (19' 8 1/4")	–	941.04.704
Spacer profile for wall mounted tracks		Plastic	gray	2 m (6' 6 3/4")	–	941.13.220
End cap for clip-on fascia, Height: 77 mm (3 1/32")		Aluminum	clear anodized	59 mm (2 5/16")	Left	941.04.400
				59 mm (2 5/16")	Right	941.04.401
				66 mm (2 19/32")	Left	941.04.402
				66 mm (2 19/32")	Right	941.04.403
Clip for wood and aluminum fascia, mount every 400–600 mm (15 3/4"–23 5/8")		Aluminum	mill	97 mm (3 13/16")	–	940.60.065
Guide rail, glue-in type		Plastic	black	1.3 m (4' 3 3/16")	–	940.41.130
End cap for upper track, 940.80.series		Steel	chrome matt	–	–	940.80.021
Track stopper with adjustable retaining spring		–	–	–	–	941.04.300
SoftStop track stopper with adjustable retaining spring		–	–	–	–	941.04.301
SoftMove 80 soft close mechanism, maximum capacity 80 kg (176 lbs.)		–	–	–	–	940.80.046

Note

Each Hawa SoftMove 80 requires a track stopper. For applications that require a SoftMove in both directions either order the fitting set that includes two track stoppers or one additional track stopper. For additional information on SoftMove 80, see page **1.229**.

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.