










Hawa Junior 100 B







→ Tracks and Accessories

Description		Material	Finish	Length	Version	Item No.
Upper track, pre-drilled		Aluminum	clear anodized	1.4 m (4' 7 1/8")	–	940.80.140
				1.6 m (5' 3")	–	940.80.160
				1.8 m (5' 10 7/8")	–	940.80.180
				2 m (6' 6 3/4")	–	940.80.200
				2.2 m (7' 2 5/8")	–	940.80.220
				2.5 m (8' 2 7/16")	–	940.80.250
				3 m (9' 10 1/8")	–	940.80.300
				4 m (13' 1 1/2")	–	940.80.400
Upper track, wall mounted, pre-drilled, for wood and aluminum fascia		Aluminum	clear anodized	6 m (19' 8 1/4")	–	940.80.600
				2 m (6' 6 3/4")	–	941.04.600
				2.5 m (8' 2 7/16")	–	941.04.601
				3 m (9' 10 1/8")	–	941.04.602
Upper track, top mounted, pre-drilled, for wood and aluminum fascia		Aluminum	clear anodized	4 m (13' 1 1/2")	–	941.04.603
				6 m (19' 8 1/4")	–	941.04.604
				2 m (6' 6 3/4")	–	941.04.605
				2.5 m (8' 2 7/16")	–	941.04.606
Upper track, top mounted, pre-drilled, for suspended ceilings		Aluminum	clear anodized	3 m (9' 10 1/8")	–	941.04.607
				4 m (13' 1 1/2")	–	941.04.608
				6 m (19' 8 1/4")	–	941.04.609
				2.5 m (8' 2 7/16")	–	941.04.610
Clip-on fascia Height: 40 mm (1 9/16")		–	–	4 m (13' 1 1/2")	–	941.04.611
				6 m (19' 8 1/4")	–	941.04.612
				2 m (6' 6 3/4")	–	941.04.705
				2.5 m (8' 2 7/16")	–	941.04.706
Spacer profile, for wall mounted tracks		Plastic	gray	3 m (9' 10 1/8")	–	941.04.707
				4 m (13' 1 1/2")	–	941.04.708
				6 m (19' 8 1/4")	–	941.04.709
				2 m (6' 6 3/4")	–	941.13.220
End cap for clip-on fascia Height: 40 mm (1 9/16")		Aluminum	clear anodized	53 mm (2 3/32")	Left	941.04.404
				53 mm (2 3/32")	Right	941.04.405
				60 mm (2 3/8")	Left	941.04.406
				60 mm (2 3/8")	Right	941.04.407
Guide rail, glue-in type		Plastic	black	1.3 m (4' 3 3/16")	–	940.41.130
End cap for upper track		Steel	chrome matt	–	–	940.80.021
Track stopper with adjustable retaining spring		–	–	–	–	941.04.300
SoftStop track stopper with adjustable retaining spring		–	–	–	–	941.04.301
SoftMove 100 soft close mechanism, maximum capacity 100 kg (220 lbs.)		–	–	–	–	941.04.302
SoftMove 100 cover cap		Plastic	black	–	–	941.04.303

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.

Hawa Junior 100 B Acoustics Set

→ Upper Tracks and Accessories












Description		Material	Finish	Length	Version	Item No.
Upper track, wall mounted, pre-drilled, for wood and aluminum fascia		Aluminum	clear anodized	2 m (6' 6 3/4")	–	941.04.600
				2.5 m (8' 2 7/16")	–	941.04.601
				3.0 m (9' 10 1/8")	–	941.04.602
				4.0 m (13' 1 1/2")	–	941.04.603
				6 m (19' 8 1/4")	–	941.04.604
Clip-on fascia Height: 40 mm (1 9/16")				2 m (6' 6 3/4")	–	941.04.705
				2.5 m (8' 2 7/16")	–	941.04.706
				3.0 m (9' 10 1/8")	–	941.04.707
				4.0 m (13' 1 1/2")	–	941.04.708
End cap for clip-on fascia Height: 40 mm (3 1/32"), cut-table		Aluminum	clear anodized	95 mm (3 3/4")	Left	941.04.408
				95 mm (3 3/4")	Right	941.04.409
SoftStop track stopper with adjustable retaining spring and ramp		–	–	–	–	941.04.304
SoftStop track stopper with adjustable retaining spring		–	–	–	–	941.04.301
Vertical seal		Silicone	black	7.7 m (25' 3 1/8")	–	940.00.500

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.

Soundproofing matrix	page
Sliding door locks	pages 1.384–1.394
Door pulls	pages 2.3–2.29
Flush pulls	pages 1.395–1.396

Hawa Junior 80 B (mod.)

→ Upper Tracks and Accessories

Description		Material	Finish	Length	Version	Item No.
Upper track, pre-drilled		Aluminum	clear anodized	1.4 m (4' 7 1/8")	–	940.80.140
				1.6 m (5' 3")	–	940.80.160
				1.8 m (5' 10 7/8")	–	940.80.180
				2 m (6' 6 3/4")	–	940.80.200
				2.2 m (7' 2 5/8")	–	940.80.220
				2.5 m (8' 2 7/16")	–	940.80.250
				3 m (9' 10 1/8")	–	940.80.300
				4 m (13' 1 1/2")	–	940.80.400
Upper track, wall mounted, pre-drilled, for wood and aluminum fascia		Aluminum	clear anodized	6 m (19' 8 1/4")	–	940.80.600
				2 m (6' 6 3/4")	–	941.04.600
				2.5 m (8' 2 7/16")	–	941.04.601
				3 m (9' 10 1/8")	–	941.04.602
Upper track, top mounted, pre-drilled, for wood and aluminum fascia		Aluminum	clear anodized	4 m (13' 1 1/2")	–	941.04.603
				6 m (19' 8 1/4")	–	941.04.604
				2 m (6' 6 3/4")	–	941.04.605
				2.5 m (8' 2 7/16")	–	941.04.606
Upper track, top mounted, pre-drilled, for suspended ceilings		Aluminum	clear anodized	3 m (9' 10 1/8")	–	941.04.607
				4 m (13' 1 1/2")	–	941.04.608
				6 m (19' 8 1/4")	–	941.04.609
				2.5 m (8' 2 7/16")	–	941.04.610
Clip-on fascia Height: 40 mm (1 9/16")				4 m (13' 1 1/2")	–	941.04.611
				6 m (19' 8 1/4")	–	941.04.612
				2 m (6' 6 3/4")	–	941.04.705
				2.5 m (8' 2 7/16")	–	941.04.706
Spacer profile for wall mounted tracks		Plastic	gray	3 m (9' 10 1/8")	–	941.04.707
				4 m (13' 1 1/2")	–	941.04.708
				6 m (19' 8 1/4")	–	941.04.709
				2 m (6' 6 3/4")	–	941.04.705
End cap for clip-on fascia, Height: 40 mm (3 1/32")		Aluminum	clear anodized	53 mm (2 3/32")	Left	941.04.404
				53 mm (2 3/32")	Right	941.04.405
				60 mm (2 3/8")	Left	941.04.406
				60 mm (2 3/8")	Right	941.04.407
Guide rail, glue-in type		Plastic	black	1.3 m (4' 3 3/16")	–	940.41.130
End cap for upper track, 940.80.series		Steel	chrome matt	–	–	940.80.021
Track stopper with adjustable retaining spring		–	–	–	–	941.04.300
SoftStop track stopper with adjustable retaining spring		–	–	–	–	941.04.301
SoftMove 80 soft close mechanism, maximum capacity 80 kg (176 lbs.)		–	–	–	–	940.80.046

Note

Each Hawa SoftMove 80 requires a track stopper. For applications that require a SoftMove in both directions either order the fitting set that includes two track stoppers or one additional track stopper. For additional information on SoftMove 80, see page 1.229.