

EKU Divido 80 H Set

- For 1 sliding door without upper guide channel and lower running track

Item No.
940.92.001

Set Components

	Description	Material	Finish	Qty.
	Running gear with anti-derail device, single wheel	–	–	2 pcs.
	Upper guide with plastic guide wheels, mounted on a zinc-plated steel base	–	–	2 pcs.
	Adapter for running gear, includes mounting screws	Plastic	gray	2 pcs.
	Door stopper set for lower track	Plastic	gray	2 pcs.
	Door stopper for upper guide channel	Plastic	gray	2 pcs.
	End piece to lower guide track	Plastic	gray	1 pc.

Individual Components

	Description	Material	Finish	Length	Item No.
	Single upper guide channel, 40 x 40 mm (1 9/16" x 1 9/16")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.13.525
				3.5 m (11' 5 13/16")	941.13.535
				6 m (19' 8 1/4")	941.13.560
	Dual upper guide channel, 78 x 40 mm (3 1/16" x 1 9/16")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.13.925
				3.5 m (11' 5 13/16")	941.13.935
				6 m (19' 8 1/4")	941.13.960
	Single lower track, recessed, 13 x 8 mm (1/2" x 5/16")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.13.825
				3.5 m (11' 5 13/16")	941.13.835
				6 m (19' 8 1/4")	941.13.860
	Mounting profile for 2 single lower tracks, recessed, 51 x 10 mm (2" x 3/8")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.13.125
				3.5 m (11' 5 13/16")	941.13.135
				6 m (19' 8 1/4")	941.13.160
	Single lower track, surface mounted, 38 x 8 mm (1 1/2" x 5/16")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.13.725
				3.5 m (11' 5 13/16")	941.13.735
				6 m (19' 8 1/4")	941.13.760
	Dual lower track, surface mounted, 68 x 8 mm (2 11/16" x 5/16")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.13.625
				3.5 m (11' 5 13/16")	941.13.635
				6 m (19' 8 1/4")	941.13.660
	Clip profile to mounting profile and dual lower track, 25 x 6 mm (1" x 1/4")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.12.825
				3.5 m (11' 5 13/16")	941.12.835
				6 m (19' 8 1/4")	941.12.860
	Center door stop, installed into upper guide channels, 33 x 90 mm (1 5/16" x 3 9/16")	Plastic	gray	–	941.12.040
	Soft close 61–80 kg (135–220 lbs.)	–	–	–	940.92.010

Dimensional data not binding. We reserve the right to alter specifications without notice.

Dimensions in mm
Inches are approximate

EKU Divido 80 GR Set

- For 1 sliding door without lower running track and upper guide channel

1

Item No.
940.92.000

Set Components

	Description	Material	Finish	Qty.
	Running gear with anti-derail device, single wheel	–	–	2 pcs.
	Upper guide with guide wheels	Plastic	–	2 pcs.
	Door stopper set for lower running track	Plastic	gray	2 pcs.
	Door stopper for upper guide channel	Plastic	gray	2 pcs.
	End piece to lower guide track	Plastic	gray	1 pc.
	Fixing screws	–	–	1 set

Individual Components

	Description	Material	Finish	Length	Item No.
	Single upper guide channel, 40 x 40 mm (1 9/16" x 1 9/16")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.13.525
				3.5 m (11' 5 25/32")	941.13.535
				6 m (19' 8 1/4")	941.13.560
	Dual upper guide channel, 78 x 40 mm (3 1/16" x 1 9/16")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.13.925
				3.5 m (11' 5 25/32")	941.13.935
				6 m (19' 8 1/4")	941.13.960
	Single lower running track, recessed, 13 x 8 mm (1/2" x 5/16")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.13.825
				3.5 m (11' 5 25/32")	941.13.835
				6 m (19' 8 1/4")	941.13.860
	Mounting profile for single lower running track, recessed, 51 x 10 mm (2" x 13/32")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.13.125
				3.5 m (11' 5 25/32")	941.13.135
				6 m (19' 8 1/4")	941.13.160
	Single lower running track, surface mounted, 38 x 8 mm (1 1/2" x 5/16")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.13.725
				3.5 m (11' 5 25/32")	941.13.735
				6 m (19' 8 1/4")	941.13.760
	Dual lower running track, surface mounted, 68 x 8 mm (2 11/16" x 5/16")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.13.625
				3.5 m (11' 5 25/32")	941.13.635
				6 m (19' 8 1/4")	941.13.660
	Clip profile to mounting profile and dual lower running track, 25 x 6 mm (1" x 1/4")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.12.825
				3.5 m (11' 5 25/32")	941.12.835
				6 m (19' 8 1/4")	941.12.860
	Center door stop, installed into upper guide channels, 33 x 90 mm (1 5/16" x 3 9/16")	Plastic	gray	–	941.12.040
	Soft close 61 – 80 kg (135 – 220 lbs.)	–	–	–	940.92.010

Installation Plan

(included in fitting set), mounting instructions for planning and execution available upon request.

Aluminum frame profiles pages 1.226-1.227

Dimensions in mm
Inches are approximate