




HAWA Super 250/M

Individual Components

Order Specifications:

- Number of running gears
- Number of suspension plates
- Number of track stoppers
- Upper track length
- Lower guide channel length
- Door height and width
- Door weight
- Type of lower guide

	Description	Material	Finish	Length	Item No.
	Running gear with ball bearing wheels	Steel	–	–	942.44.012
	Suspension plate with bolt, M12	Steel	galvanized	–	942.44.026
	Upper track stopper to be drilled into upper track	–	–	–	942.42.041
	Lower guide with M10 threaded bolt	–	–	–	942.07.030
	Lower guide, floor mounted	Plastic	gray	–	942.44.030
	Buffer, screw-mounted	Rubber	black	–	941.60.051
	Lower guide channel, 20 x 20 x 3 mm (13/16" x 13/16" x 1/8")	Aluminum	anodized	6 m (19' 8 1/4")	941.00.960
				2.5 m (8' 2 7/16")	941.00.925
	Lower guide channel, pre-drilled	Aluminum	anodized	6 m (19' 8 1/4")	946.03.600
	Connecting pin, notched	Steel	galvanized	–	946.12.090
	Upper track, side-drilled	Stainless Steel	–	6 m (19' 8 1/4")	942.42.601
	Upper track, with mounting flanges	Stainless Steel	–	6 m (19' 8 1/4")	942.43.601

Note





Installation plan for planning and execution available upon request.

Dimensional data not binding. We reserve the right to alter specifications without notice.

Dimensions in mm
Inches are approximate

HAWA Super 500/M

Individual Components

	Description	Material	Finish	Length	Item No.
	Running gear with ball bearing wheels	Steel	–	–	942.42.013
	Suspension plate with bolt, M12	Steel	galvanized	–	942.54.020
	Upper track stopper to be drilled into upper track	Steel	galvanized	–	942.42.041
	Lower guide with M10 threaded bolt	–	–	–	942.07.030
	Lower guide, floor mounted	Plastic	gray	–	942.44.030
	Buffer, screw-mounted	Rubber	black	–	941.60.051
	Spring-loaded door stop	–	–	–	942.30.051
	Lower guide channel, 20 x 20 x 3 mm (13/16" x 13/16" x 1/8")	Aluminum	anodized	6 m (19' 8 1/4")	941.00.960
				2.5 m (8' 2 7/16")	941.00.925
	Lower guide channel, pre-drilled	Aluminum	anodized	6 m (19' 8 1/4")	946.03.600
	Connecting pin, notched	Steel	galvanized	–	946.12.090
	Upper track, side-drilled	Stainless Steel	–	6 m (19' 8 1/4")	942.42.601
	Upper track, with mounting flanges	Stainless Steel	–	6 m (19' 8 1/4")	942.43.601

Note

Installation plan for planning and execution available upon request.

Dimensional data not binding. We reserve the right to alter specifications without notice.