




HAWA Super 250/M

Individual Components

Order Specifications:

- Number of running gears
- Number of suspension plates
- Number of track stoppers
- Upper track length
- Lower guide channel length
- Door height and width
- Door weight
- Type of lower guide

	Description	Material	Finish	Length	Item No.
	Running gear with ball bearing wheels	Steel	–	–	942.44.012
	Suspension plate with bolt, M12	Steel	galvanized	–	942.44.026
	Upper track stopper to be drilled into upper track	–	–	–	942.42.041
	Lower guide with M10 threaded bolt	–	–	–	942.07.030
	Lower guide, floor mounted	Plastic	gray	–	942.44.030
	Buffer, screw-mounted	Rubber	black	–	941.60.051
	Lower guide channel, 20 x 20 x 3 mm (13/16" x 13/16" x 1/8")	Aluminum	anodized	6 m (19' 8 1/4")	941.00.960
				2.5 m (8' 2 7/16")	941.00.925
	Lower guide channel, pre-drilled	Aluminum	anodized	6 m (19' 8 1/4")	946.03.600
	Connecting pin, notched	Steel	galvanized	–	946.12.090
	Upper track, side-drilled	Stainless Steel	–	6 m (19' 8 1/4")	942.42.601
	Upper track, with mounting flanges	Stainless Steel	–	6 m (19' 8 1/4")	942.43.601

Note

Installation plan for planning and execution available upon request.

Dimensional data not binding. We reserve the right to alter specifications without notice.

Dimensions in mm
Inches are approximate