

HAWA Super 500/M

Individual Components

Description	Material	Finish	Length	Item No.
 Running gear with ball bearing wheels	Steel	–	–	942.42.013
 Suspension plate with bolt, M12	Steel	galvanized	–	942.54.020
 Upper track stopper to be drilled into upper track	Steel	galvanized	–	942.42.041
 Lower guide with M10 threaded bolt	–	–	–	942.07.030
 Lower guide, floor mounted	Plastic	gray	–	942.44.030
 Buffer, screw-mounted	Rubber	black	–	941.60.051
 Spring-loaded door stop	–	–	–	942.30.051
 Lower guide channel, 20 x 20 x 3 mm (13/16" x 13/16" x 1/8")	Aluminum	anodized	6 m (19' 8 1/4") 2.5 m (8' 2 7/16")	941.00.960 941.00.925
 Lower guide channel, pre-drilled	Aluminum	anodized	6 m (19' 8 1/4")	946.03.600
 Connecting pin, notched	Steel	galvanized	–	946.12.090
 Upper track, side-drilled	Stainless Steel	–	6 m (19' 8 1/4")	942.42.601
 Upper track, with mounting flanges	Stainless Steel	–	6 m (19' 8 1/4")	942.43.601

Note

Installation plan for planning and execution available upon request.