


HAWA Junior 250/A Set

- For 1 sliding door without upper track and lower guide channel

	Item No.
	942.56.001



Set Components

	Description	Material	Finish	Qty.	Item No.
	Double roller running gear	–	–	2 pcs.	942.56.012
	One-way suspension plate, M12 bolt and mounting screws	–	–	2 pcs.	942.56.022
	Floor mounted guide, rattle-free	Plastic	black	1 pc.	941.60.031
	Track stopper with adjustable retention spring	–	–	1 pc.	942.56.041
	Wall buffer	Rubber	black	1 pc.	941.60.051
	Locking wrench	Steel	–	1 pc.	941.20.091

Note

Item numbers are valid only for 1 piece, when ordering individual components, please state the desired amount.
Depending on application an additional track stopper has to be ordered with set. For 2 bi-parting sliding doors, please order 2 sets.

Individual Components

	Description	Material	Finish	Length	Item No.
	Upper track, pre-drilled	Aluminum	clear anodized	4 m (13' 1 1/2")	942.56.940
				6 m (19' 8 1/4")	942.56.960
	Guide rail, glue-in type	Plastic	black	3 m (9' 10 1/8")	941.61.130
	Connecting bolts, for upper tracks	Steel	galvanized	–	942.56.090

Installation Plan

(Included in fitting set), mounting instructions for planning and execution available upon request.

Confort guides	page 1.198
Other lower guide options	page 1.199




Dimensions in mm
Inches are approximate

HAWA Junior 250/B Set

- For 1 sliding door without upper track and lower guide channel

	Item No.
	942.56.002




Set Components

	Description	Material	Finish	Qty.	Item No.
	Double roller running gear	–	–	2 pcs.	942.56.012
	Carrier profile with suspension plates and M12 hanger bolt	–	–	2 pcs.	942.56.024
	End caps for carrier profile	Plastic	anthracite gray	2 pc.	942.56.029
	Floor mounted guide, rattle-free	Plastic	black	1 pc.	941.60.031
	Track stopper with adjustable retention spring	–	–	1 pc.	942.56.041
	Wall buffer	Rubber	black	1 pc.	941.60.051
	Locking wrench	Steel	–	1 pc.	941.20.091

Note

Item numbers are valid only for 1 piece, when ordering individual components, please state the desired amount.
Depending on application an additional track stopper has to be ordered with set. For 2 bi-parting sliding doors, please order 2 sets.

Individual Components

	Description	Material	Finish	Length	Item No.
	Upper track, pre-drilled	Aluminum	clear anodized	4 m (13' 1 1/2")	942.56.940
				6 m (19' 8 1/4")	942.56.960
	Suspension profiles	Aluminum	clear anodized	2.5 m (8' 2 7/16")	946.14.925
				6.5 m (21' 3 15/16")	946.08.651
	Guide rail, glue-in type	Plastic	black	3 m (9' 10 1/8")	941.61.130
	Connecting bolts, for upper tracks	Steel	galvanized	–	942.56.090

Installation Plan

(Included in fitting set), mounting instructions for planning and execution available upon request.

Confort guides	page 1.198
Other lower guide options	page 1.199

Dimensions in mm
Inches are approximate

HAWA Junior 250/G

Set

- For 1 sliding door without upper track and lower guide

Item No.
942.56.003

Supplied With

Mounting instructions

Set Components

	Description	Material	Finish	Qty.	Item No.
	Double roller running gear	Aluminum	–	2 pcs.	942.56.012
	Suspension block including M12 and clamping screw	Zinc alloy	–	2 pcs.	942.56.023
	Track stopper with adjustable retention spring	–	–	2 pcs.	942.56.041
	Cover cap, for glass suspension profile	Plastic	anthracite	2 pcs.	942.56.029
	Wall buffer	Rubber	black	1 pc.	941.60.051
	Wrench, for suspension block	Aluminum	clear anodized	1 pc.	940.40.092

Note

Item numbers are valid for only 1 piece, when ordering individual components please state the desired amount. For 2 bi-parting sliding glass doors, please order 2 sets.

Individual Components

	Description	Area of application	Material	Finish	Length/Qty	Item No.
	Upper track, pre-drilled		Aluminum	anodized	4 m (13' 1 1/2") 6 m (19' 8 1/4")	942.56.940 942.56.960
	Connecting pin set for upper track		–	–	–	942.56.091
	Support and glass suspension profile, glass thickness 8 – 10 mm (3/16" – 13/32")		Aluminum	anodized	6 m (19' 8 1/4")	942.56.765
	Cover for glass suspension, profile glass thickness of 8 – 10 mm (3/16" – 13/32")		Plastic	anthracite	–	942.44.060
	Support and glass suspension profile, glass thickness 12 – 16 mm (15/32" – 5/8")		Aluminum	anodized	6 m (19' 8 1/4")	942.56.865
	Cover for glass suspension, profile glass thickness of 12 – 16 mm (15/32" – 5/8")		Plastic	anthracite	–	942.44.061
	Glass holder, for glass thickness 8, 10, 12, 12.7, 14 and 16 mm (5/16", 13/32", 15/32", 1/2", 9/16", 5/8") (4 pcs. required for each support and glass suspension profile)		Plastic	–	–	940.84.024
	Lower guide, rattle-free for glass thickness 8, 10 and 12.7 mm (3/16", 13/32", 1/2")	Floor guide version 1	Steel	chrome plated matt	–	940.40.032
	Floor guide, for bottom support and glass suspension profile	– Floor guide version 2	–	–	1 pc.	940.84.037
	Guide track, 31 x 28 mm (1 1/4" x 1 1/8"), pre-drilled	Floor guide version 3	Aluminum	anodized	6 m (19' 8 1/4")	946.03.600
	Guide piece, with zero clearance, 14 mm (9/16"), with suspension block	Floor guide version 3	Aluminum	anodized	–	946.12.060
	Connecting pin, for guide channel (Order 2 pcs. for each guide track connection)	Floor guide version 3	Steel	galvanized	–	946.12.090

Pull handles	pages 2.10-2.32
Door seals and accessories	page 1.290
Sliding door locks	pages 1.357, 1.364-1.367

Dimensions in mm
Inches are approximate