





Hawa Varifold 80 H

→ Individual Components

Description		Material	Finish	Length	Item No.
Upper track, pre-drilled		Aluminum	clear anodized	6 m (19' 8 1/4")	943.27.960
Lower guide channel, pre-drilled, 24 x 24 mm (15/16" x 15/16")		Aluminum	clear anodized	6 m (19' 8 1/4")	940.81.600
Heavy duty ball bearing hinge - ≤ 2.5 m (8' 2 7/16") 2 pcs. required - ≤ 3.5 m (11' 5 13/16") 3 pcs. required		Stainless Steel 316	mat	–	926.21.003
Door seal		Rubber	black	10 m (32' 9 11/16")	950.07.423










Order Specifications

Length of upper track (opening)
Select appropriate set types and number of sets
Length of lower guide channel
Number of hinges
Door seals if desired
Locks if desired

Installation Plan










(Included in fitting set), mounting instructions for planning and execution available upon request.

→ Locking Components

Description		Material	Finish	Item No.
Bar bolt Lock		Steel	galvanized	943.04.084
Deadbolt lock		Steel	galvanized	943.04.080
Thumbturn for door thickness of 35–40 mm (1 3/8"–1 9/16")		–	chrome-plated	946.22.950
Thumbturn for door thickness of 41–57 mm (1 5/8"–2 1/4")		–	chrome-plated	946.22.951
Key for deadbolt lock		Steel	galvanized	943.04.090
Slip-fit rosette		Brass	dull nickel-plated	943.04.091
Dust proof strike with spring-loaded cover		–	chromium-plated	946.23.920
Rosette for dust proof strike above		–	chromium-plated	946.23.921
Strike plate with oblong hole		Steel	chromium-plated	946.23.910

Hawa Centerfold 80 H









→ **Locking Components**

Description		Material	Finish	Item No.
Bar bolt Lock		Steel	galvanized	943.04.084
Deadbolt lock		Steel	galvanized	943.04.080
Thumbturn for door thickness of 35–40 mm (1 3/8"–1 9/16")		–	chrome-plated	946.22.950
Thumbturn for door thickness of 41–57 mm (1 5/8"–2 1/4")		–	chrome-plated	946.22.951
Key for deadbolt lock		Steel	galvanized	943.04.090
Slip-fit rosette		Brass	dull nickel-plated	943.04.091
Dust proof strike with spring-loaded cover		–	chromium-plated	946.23.920
Rosette for dust proof strike above		–	chromium-plated	946.23.921
Strike plate with oblong hole		Steel	chromium-plated	946.23.910

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.

[illegible]

- > Backset: 42.5 mm (1 11/16")
- > Throw: 18 mm (3/4")
- > Operation height: 960 mm (37 13/16")
- > Locks and secures partition walls
- > Operation with square or hexagonal key from the face of the door or with a thumbturn

Description		Material	Finish	Item No.
Bar bolt Lock		Steel	galvanized	943.04.084
Thumb turn for door thickness of 35–40 mm (1 3/8"–1 9/16")		–	chrome-plated	946.22.950
Thumb turn for door thickness of 41–57 mm (1 5/8"–2 1/4")		–	chrome-plated	946.22.951
Key for deadbolt lock		Steel	galvanized	943.04.090
Slip-fit rosette		Brass	dull nickel-plated	943.04.091
Dust proof strike with spring-loaded cover		–	chromium-plated	946.23.920
Rosette for dust proof strike above		–	chromium-plated	946.23.921
Strike plate with oblong hole		Steel	chromium-plated	946.23.910