HAFELE

HAWA Aperto 60/H Sliding Door

Individual Components

	omponents .	Item No.
	Suspension carriage with integrated mounting block and M8 screw	943.30.020
	Running gear with 2 rollers and M8 screw	943.30.012
	Suspension profile 250 x 20 x 25 mm (9 27/32" x 28/32" x 1")	943.31.125
	Cover cap for suspension profile 20 x 25 mm (25/32" x 1") Plastic, anthracite gray	943.30.029
	Floor guide with mounting block	943.30.030
	Single bolt lock with square/hexagonal socket, clip-on escutcheon and Ø9 mm (11/32") bolt/guide plan	943.31.083
	Single bolt lock for 17 mm (11/16") profile cylinder, with Ø9 mm (11/32") bolt/guide pin	943.31.082
6	Single bolt lock with square/hexagonal socket, clip-on escutcheon and Ø9 mm (11/32") bolt	943.31.080
	Single bolt lock for 17 mm (21/32") profile cylinder, with Ø9 mm (11/32") bolt	943.31.081
	Strike plate for 9 mm (11/32") bolt	943.31.090
	Socket key for bolt lock	943.04.090

Pivot Door Individual Components

		Item No.
	Suspension profile 250 x 20 x 25 mm (9 27/32" x 28/32" x 1")	943.31.125
	Cover cap for suspension profile 20 x 25 mm (25/32" x 1") Plastic, gray	943.30.029
	Top pivot bearing for parallel parking area	943.30.022
	Pivot bearing for 90 mm (3 1/2") parking area	943.30.023
	Bottom pivot bearing for guide channel	943.30.032
	Bottom pivot bearing with thrust 2 bearing sleeve 20 mm (25/32")	943.30.033
	Adapter piece for inner running track Length: 300 mm (11 13/16")	943.30.090
	Adapter piece for outer running track Length: 300 mm (11 13/16")	943.30.091
0000	Mounting plate for 2 x single running track	943.30.024
The second secon	Wrench SW13	943.30.095

Note

Item numbers refer to only 1 pc. or 1 set. Please specify required quanitiy when ordering individual parts.

Dimensions in mm Inches are approximate

10/19