

HAWA 20-c Set

Order Specifications:

- Length of upper track/opening
- Set type and number of sets
- Length of lower guide channel
- Number of hinges

	Item No.
	943.02.001
	943.02.002
	943.02.003
	943.02.004
	943.02.005

Set Components

	Description:	943.02.001	943.02.002	943.02.003	943.02.004	943.02.005	Item No.
	Running gear	1 pc.	1 pc.	2 pcs.	2 pcs.	3 pcs.	942.41.014
	Suspension bracket	1 pc.	1 pc.	2 pcs.	2 pcs.	3 pcs.	943.02.022
	Lower guide bracket	1 pc.	1 pc.	2 pcs.	2 pcs.	3 pcs.	943.02.030
	Deadbolt lock	1 pc.	1 pc.	2 pcs.	2 pcs.	3 pcs.	943.04.080
	Slip-fit rose	1 pc.	1 pc.	2 pcs.	2 pcs.	3 pcs.	943.04.091
	Key to deadbolt lock	1 pc.	1 pc.	1 pc.	1 pc.	1 pc.	943.04.090

Note

Item numbers are valid only for 1 piece, when ordering individual components please state the desired amount.

Individual Components

	Description	Material	Finish	Length/Door Height	Qty./Door	Item No.
	Dual upper tracks, with mounting flanges	Stainless Steel 304	–	6 m (19' 8 1/4")	–	942.43.611
	Lower guide channel, pre-drilled 20 x 20 x 3 mm (25/32" x 25/32" x 1/8")	Aluminum	anodized	6 m (19' 8 1/4")	–	941.00.960
		Brass	–	2.5 m (8' 2 7/16")	–	941.00.925
	Lower guide channel, pre-drilled 20 x 28 x 3 mm (25/32" x 1 1/8" x 1/8")	Brass	–	6 m (19' 8 1/4")	–	943.05.600
	Ball bearing hinges, 102 x 76 mm (4" x 3")	Stainless Steel	matt	up to 2.5 m (8' 2 7/16")	3 pcs.	926.98.040
				up to 3.2 m (10' 6")	4 pcs.	–
				up to 4 m (13' 1 1/2")	5 pcs.	–
	HAWA bar bolt lock, Doorfix	Steel	galvanized	–	–	946.21.100
	Strike plate	Steel	chromium-plated, polished	–	–	946.23.910
	Dust proof strike	Steel	chromium-plated, polished	–	–	946.23.920

Installation Plan

Mounting instructions for planning and execution available upon request.

Dimensional data not binding. We reserve the right to alter specifications without notice.