

→ HAWA Clipo 26 GR IF Set






	Supplied With	Item No.
For 2 doors	4 running gears 2 floor guides 8 corner brackets (4 each left/right) 1 door follower 4 door stoppers with clip-in door stopper	405.00.007

Supplied With
1 set

Note

Please order one soft closing mechanism for each door for soft opening and soft closing action separately with pitch lengths of running gears from 460 mm (18 1/8") and above.

→ Tracks and Accessories

	Description	Material	Finish	Length	Item No.
	Single upper track, pre-drilled, for screw mounting	Aluminum	anodized, silver	2.5 m (8' 2 7/16")	405.00.622
				3.5 m (11' 5 13/16")	405.00.623
	Door frame profile, top/vertical	Aluminum	anodized, silver	2.5 m (8' 2 7/16")	401.64.902
	Door frame profile, bottom	Aluminum	anodized, silver	2.5 m (8' 2 7/16")	401.66.902
	Gasket, for aluminum frame profile	Plastic	gray	2.5 m (8' 2 7/16")	401.65.526
	Track end piece	Plastic	gray	—	405.00.072
	Soft closing mechanism for door weights up to 15 kg (33 lbs.)	Plastic and Aluminum	—	—	405.10.073
	Soft closing mechanism for door weights up to 26 kg (57.2 lbs.)				405.10.074
	Routing jig for top and vertical door frame profile	—	—	—	401.80.001

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.

→ HAWA Clipo 36 G IF Set






	Supplied With	Item No.
For 1 door	2 running gears 1 bottom guide 2 clamp shoes for glass 2 door stoppers with clip-in door stopper Mounting material	405.02.409

Supplied With
1 set

Note

Only use tempered safety glass. Please order running and guide tracks separately. Soft closing mechanism on one side is possible from pitch length of min. 260 mm (10 1/4"), both sides from 460 mm (18 1/8"). Please order soft closing mechanism set separately.

→ Tracks and Accessories

	Description	Material	Finish	Length/Door weight	Item No.
	Upper track, pre-drilled, for screw mounting	Aluminum	anodized	2.5 m (8' 2 7/16")	405.00.622
				3.5 m (11' 5 13/16")	405.00.623
	Upper track, pre-drilled, surface mounted	Aluminum	anodized	2.5 m (8' 2 7/16")	405.00.632
	Soft closing mechanism, optional One set includes two mechanisms. Two sets are required for dual soft closing of two doors.	Plastic and Aluminum	-	15.4–26 kg (34–57 lbs.)	405.10.074
				26–36 kg (57–79 lbs.)	940.48.045
	Service port for upper track (To access running gear after installation)	Plastic	gray	–	405.00.072
	Clip-on fascia	Aluminum	anodized silver	2.5 m (8' 2 7/16")	405.23.902
	End cap set	Plastic	–	–	405.02.050

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.

→ HAWA Clipo 36 GPK/GPPK IF Set



	Version	Supplied With	Item No.
For 1 door	Clipo 36 GPK	2 running gears 1 clear threshold floor guide 2 door stoppers with clip-in door stopper Mounting material	405.02.410
	Clipo 36 GPPK	2 running gears 1 bottom guide 3 covers 2 door stoppers with clip-in door stopper Mounting material	405.02.411

Supplied With
1 set

Order Reference

Please order running and guide tracks and glass fixing profiles (GPK: top, GPPK: top and bottom) separately. Soft closing mechanism on one side is possible from pitch length of min. 260 mm (10 1/4"), both sides from 460 mm (18 1/8"). Please order soft closing mechanism set separately.

→ Tracks and Accessories

	Description	Material	Finish	Length/Door weight	Item No.
	Glass fixing profile, for top and bottom of door, for glue mounting	Aluminum	anodized, silver	2.5 m (8' 2 7/16")	405.03.202
				3.5 m (11' 5 13/16")	405.03.203
	Upper track, pre-drilled, for screw mounting	Aluminum	anodized, silver	2.5 m (8' 2 7/16")	405.00.622
				3.5 m (11' 5 13/16")	405.00.623
	Double upper track, pre-drilled, for screw mounting	Aluminum	anodized, silver	2.5 m (8' 2 7/16")	405.02.622
				3.5 m (11' 5 13/16")	405.02.623
	Soft closing mechanism, optional for screw mounting to housing. One set includes two mechanisms. Two sets are required for dual soft closing of two doors.	Plastic	gray	up to 15 kg (33 lbs.)	405.10.073
				15–27 kg (34–57 lbs.)	405.10.074
				26–36 kg (57–79 lbs.)	940.48.045
	Service port for upper track (to access running gear after installation)	Plastic	gray	–	405.00.072
	Service port for double upper track (to access running gear after installation)	Plastic	gray	–	405.00.074

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.

→ HAWA Clipo 36 HM IF Set

	Version	Supplied with	Item No.
For 1 door	With clip-in door stopper	2 running gears with housings 2 door stoppers 1 floor guide	405.02.408




Supplied With

1 set

Note

Please order running and guide tracks separately. Soft closing mechanism on one side is possible from pitch length of min. 260 mm (10 1/4"), both sides from 460 mm (18 1/8"). Please order soft closing mechanism set for soft closing on both sides separately.

→ Tracks and Accessories

Description		Material	Finish	Length/Door weight	Item No.
Upper track, pre-drilled, for screw mounting		Aluminum	anodized silver	2.5 m (8' 2 7/16")	405.00.622
				3.5 m (11' 5 13/16")	405.00.623
Lower guide channel		Plastic	gray	2.5 m (8' 2 7/16")	406.73.803
				3.5 m (11' 5 13/16")	406.73.804
Soft closing mechanism, optional for screw mounting to housing		Plastic	-	up to 15 kg (33 lbs.)	405.10.073
One set includes two mechanisms Two sets are required for dual soft closing of two doors				15.4–26 kg (34–57 lbs.)	405.10.074
Service port for upper track (to access running gear after installation)		Plastic	gray	-	405.00.072
Soft stop, for screw mounting to the back of the front door Optional for a two door application		-	-	-	405.93.012

→ HAWA Clipo 36 H IF Set

	Supplied with	Item No.
For 2 doors	4 running gears with housings 1 door follower 2 guides 4 door stoppers with clip-in door stopper Mounting material	405.02.404
For 3 doors	6 running gears with housings 3 guides 4 door stoppers with clip-in door stopper 2 buffers Mounting material	405.02.405




Supplied With

1 set

Note

Please order running and guide tracks separately. Soft closing mechanism on one side is possible from pitch length of min. 260 mm (10 1/4"), both sides from 460 mm (18 1/8"). Please order soft closing mechanism set for soft closing on both sides separately.

→ Tracks and Accessories

Description		Material	Finish	Length/Door weight	Item No.
Upper track, pre-drilled, for screw mounting		Aluminum	anodized silver	2.5 m (8' 2 7/16")	405.00.622
				3.5 m (11' 5 13/16")	405.00.623
Lower guide channel		Plastic	gray	2.5 m (8' 2 7/16")	406.73.803
				3.5 m (11' 5 13/16")	406.73.804
Soft closing mechanism, optional for screw mounting to housing		Plastic	gray	up to 26 kg (57 lbs.)	405.10.074
One set includes two mechanisms. Two sets are required for dual soft closing of two doors.				26–36 kg (57–79 lbs.)	940.48.045
Service port for upper track (access running gear after installation)		Plastic	gray	–	405.00.072

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.




→ HAWA Clipo 26 H IF Set

	Supplied with	Item No.
For 2 doors	4 running gears with housings 1 door follower 2 guides 4 door stoppers with clip-in door stopper Mounting material	405.00.004

Supplied With
1 set

Note
Please order running and guide tracks separately. Soft closing mechanism on one side is possible from pitch length of min. 260 mm (10 1/4"), both sides from 460 mm (18 1/8"). Please order soft closing mechanism set for soft closing on both sides separately.

→ Tracks and Accessories

Description		Material	Finish	Length/Door weight	Item No.
Upper track, pre-drilled, for screw mounting		Aluminum	anodized silver	2.5 m (8' 2 7/16")	405.00.622
				3.5 m (11' 5 13/16")	405.00.623
Lower guide channel, for glue mounting		Plastic	gray	2.5 m (8' 2 7/16")	406.73.803
				3.5 m (11' 5 13/16")	406.73.804
Soft closing mechanism, optional, for screw mounting to housing One set includes two mechanisms. Two sets are required for dual soft closing of two doors.		Plastic	gray	up to 15 kg (33 lbs.)	405.10.073
				15.4–26 kg (34–57 lbs.)	405.10.074
Service port for upper track (access running gear after installation)		Plastic	gray	–	405.00.072

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.