

## Rebate seal colours and nature of material

### Standard colours

- Black
- Dark brown
- Brown
- Beige
- white
- Transparent

Other colours available on request.

### paint compatibility

Sealing profiles which are painted over or used for renovation purposes must always be tested for their compatibility with the lacquer.

**Irrespective of the specifications for paint compatibility, testing should always be carried out.**

When complying with the stipulated drying cycles, the compatibility is given for following coating systems:

Sealing profiles made from modified elastic polymer (PVC)	Sealing profiles made from thermoplastic elastomer (TPE) or cross-linked silicon
Alkyd resin varnishes and lacquers	Alkyd resin varnishes and lacquers
Polyurethane lacquers (DD lacquers)	Polyurethane lacquers (DD lacquers)
2-component epoxy resin lacquers	2-component epoxy resin lacquers
Acid hardening lacquers, where the PVC resistance is specified by the manufacturer	Acid hardening lacquers
Chemically cross-linked enamel	Chemically cross-linked enamel
	Nitrocellulose lacquers
	Solvent-based or water-based acrylic varnishes and lacquers
<b>Not suitable for coating are following:</b>	
Nitrocellulose lacquers	—
Solvent-based or water	
thinnable acrylic varnishes and lacquers	
PVC lacquers	

## Quality

Modified elastic polymer (PVC)	Thermoplastic elastomer (TPE)	cross-linked silicon
<b>Features</b>		
Good physical properties	Good physical and thermal properties	Very good physical and thermal properties
Temperature range from -20 to +60 °C	Excellent resilience	Excellent resilience
Resistant to aging, weathering and ozone	Comfortable closing pressure High tolerance compensation Temperature range from -40 to +180 °C Resistant to aging, weathering and ozone	Soft and smooth closing properties High tolerance compensation with warped door panel Temperature range from -60 to +250 °C Resistant to aging, weathering and ozone
<b>Areas of application</b>		
For interior doors	For interior and front doors For soundproof and smoke control doors	For interior and front doors For soundproof and smoke control doors For sauna doors