

Trim & Auxiliary




To complement our extensive European offering, Hager Companies delivers a wide array of trim & auxiliary products for international markets. This includes door stops, bolts, dust proof strikes, coat hooks, and signage.





TRIM & AUXILIARY


DOOR STOPS



248E

Pedestal Door Stop

Base Diameter: 22 mm
Height: 30.5 mm
Materials: Stainless steel with rubber bumper
Finish: US32D
Fasteners: One (1) 5 mm x 30 mm FPHWS with anchor



248U

Pedestal Door Stop - Tall

Base Diameter: 28 mm
Height: 37.5 mm
Materials: Stainless steel with rubber bumper
Finish: US32D
Fasteners: One (1) 5 mm x 30 mm FPHWS with anchor

SURFACE BOLTS



277E

Surface Bolt

Bolt Length: 125 mm
Bolt Height: 18 mm
Bolt Depth: 6 mm
Bolt Throw: 35 mm
Base Width: 100 mm
Knob Diameter: 25 mm
Projection: 32 mm
Material: Zinc
Finish: US15
Fasteners: Seven (7) 3.5 mm x 25 mm FPHMS



277T

Indicator Thumbturn Bolt

Bolt Length: 87 mm
Bolt Height: 11.5 mm
Bolt Width: 6 mm
Bolt Throw: 19 mm
Projection: 29 mm
Material: Stainless steel
Finish: US32D
Fasteners: Eight (8) 3.5 mm x 25 mm FPHSMS
Notes: 57 mm maximum door thickness





TRIM & AUXILIARY

FLUSH BOLTS & STRIKES



280E

Dust Proof Strike

Barrel Diameter:	19 mm
Barrel/Plunger Diameter:	13.5 mm
Depth:	36.5 mm
Material:	Stainless steel
Finish:	US32D



1420

Manual Flush Bolt

Length:	200 mm
Width:	20.3 mm
Depth:	16.5 mm
Bolt Diameter:	9.9 mm
Bolt Throw:	15.8 mm
Material:	Stainless steel
Finish:	US32D
Strike Fasteners:	Two (2) 3.5 mm x 19 mm FPHWS
Flush Bolt Fasteners:	Two (2) 3.5 mm x 25 mm FPHWS

MISCELLANEOUS



299D

Concealed Door Chain

Materials:	Strike - Stainless steel Latch body - Plastic Latch faceplate - Stainless steel
Door Thickness:	35 mm - 55 mm
Finish:	US32D
Fasteners:	Five (5) 3.5 mm x 25 mm FPHWS




1757

Door Viewer

Viewing Range:	145 Degrees
Material:	Brass
Finish:	US26D
Notes:	• PVC lens, with back cover • For doors 35 mm - 55 mm thick, adjustable • Requires 16 mm hole

TRIM & AUXILIARY

COAT HOOKS



6630

Double Coat Hook - Angled

Height: 72 mm
 Upper Projection: 75.5 mm
 Lower Projection: 30 mm
 Material: Stainless steel
 Finish: US32D
 Fasteners: Two (2) 4 mm x 25 mm FPHWS



6640

Double Coat Hook - Straight

Height: 78 mm
 Upper Projection: 72 mm
 Lower Projection: 25 mm
 Material: Stainless steel
 Finish: US32D
 Fasteners: Two (2) 4 mm x 25 mm FPHWS

SIGNAGE



371F

Female

Size: 75 mm diameter
 Material: 1.6 mm thick 304 stainless steel
 Finish: US32D
 Fasteners: Two (2) 4 mm x 25 mm FPHWS



371H

Handicap

Size: 75 mm diameter
 Material: 1.6 mm thick 304 stainless steel
 Finish: US32D
 Fasteners: Two (2) 4 mm x 25 mm FPHWS



TRIM & AUXILIARY



371M

Male

Size:

Material:

Finish:

Fasteners:

75 mm diameter

1.6 mm thick 304 stainless steel

US32D

Two (2) 4 mm x 25 mm FPHWS



371S

No Smoking

Size:

Material:

Finish:

Fasteners:

75 mm diameter

1.6 mm thick 304 stainless steel

US32D

Two (2) 4 mm x 25 mm FPHWS



371U

Unisex

Size:

Material:

Finish:

Fasteners:

75 mm

1.6 mm thick 304 stainless steel

US32D

Two (2) 4 mm x 25 mm FPHWS