



FULL MORTISE - SPRING

SINGLE ACTING

The following single acting spring hinges are for automatic closing of doors, please note:

- 1150 is not available in 3-1/2" x 3-1/2" (89 mm x 89 mm) and 4" x 4" (102 mm x 102 mm) sizes.
- 1250 is available with raised barrel for square edge or beveled doors.
- 1250 UL approved for use on 4' 0" x 8' 0" (1219 mm x 2438 mm) doors. 3 springs/one BB for 8' door.
- For maximum versatility, use all spring hinges or a combination of spring and ball bearing hinges. Do not use plain bearing hinges.
- Full spring tension may not be required on all hinges.
- Strong wind conditions, drafts, carpeting drag, twisted/misaligned frames, or weatherstripping on doors may require additional spring hinges. Available with HT - voids UL. Available with RBB/RBS - UL approved.



1150

Square Corner

Stainless steel with stainless steel components (ANSI K51071F)

1151

1/4" Radius

Stainless steel with stainless steel components (ANSI K51071F)



1152

5/8" Radius

Stainless steel with stainless steel components (ANSI K51071F)

1250

Square Corner

Steel with steel components (ANSI K81071F)

1251

1/4" Radius

Steel with steel components (ANSI K81071F)

1252

5/8" Radius

Steel with steel components (ANSI K81071F)

1255

Square Corner Set

Steel with steel components (ANSI K81071F)
Two (2) each 1250 and one (1) each AB700

1256

Square Corner Set

Steel with steel components (ANSI K81071F)
Two (2) each 1250 and one (1) each BB1279

Hinge Size		Gauge of Metal	Hole Count	Screw Size	
Inches	mm			Machine	Wood
3-1/2 x 3-1/2	89 x 89	0.134	6	1/2 x 10-24	1 x 9
4 x 4	102 x 102	0.134	8	1/2 x 12-24	1-1/4 x 12
4-1/2 x 4	114 x 102	0.134	8	1/2 x 12-24	1-1/4 x 12
4-1/2 x 4-1/2	114 x 114	0.134	8	1/2 x 12-24	1-1/4 x 12

Series	Size	Recommended Max Door Weight (lbs)	Spring Hinge	Ball Bearing Hinge
For use on 1-3/8" (35 mm) door				
1250	3-1/2 x 3-1/2	40	1	2
1250	3-1/2 x 3-1/2	70	2	1
1250	3-1/2 x 4-1/2	90	3	-
For use on 1-3/4" (45 mm) door				
1250	4 x 4	60	1	2
1250	4 x 4	85	2	1
1250	4 x 4	110	3	-
1150	4-1/2 x 4, 4-1/2 x 4-1/2	70	1	2
1150	4-1/2 x 4, 4-1/2 x 4-1/2	115	2	1
1150	4-1/2 x 4, 4-1/2 x 4-1/2	150	3	-
1250	4-1/2 x 4, 4-1/2 x 4-1/2	70	1	2
1250	4-1/2 x 4, 4-1/2 x 4-1/2	115	2	1
1250	4-1/2 x 4, 4-1/2 x 4-1/2	150	3	-
1255	4-1/2 x 4-1/2	115	2	1
1256	4-1/2 x 4-1/2	115	2	1





FULL MORTISE - SPRING

REVERSE ACTION - SINGLE ACTING

The following reverse action, single acting spring hinges are for automatic opening of door, please note:

- For maximum versatility, use all spring hinges or a combination of spring and ball bearing hinges. Do not use plain bearing hinges.
- Full spring tension may not be required on all hinges.
- Strong wind conditions, drafts, carpeting drag, twisted/misaligned frames, or weatherstripping on doors may require additional spring hinges.



1257
Square Corner
Steel (ANSI K81071)

1258
1/4" Radius
Steel (ANSI K81071)

1259
5/8" Radius
Steel (ANSI K81071)

Hinge Size		Gauge of Metal	Hole Count	Screw Size	
Inches	mm			Machine	Wood
3-1/2 x 3-1/2	89 x 89	0.134	6	1/2 x 10-24	1 x 9
4 x 4	102 x 102	0.134	8	1/2 x 12-24	1-1/4 x 12
4-1/2 x 4	114 x 102	0.134	8	1/2 x 12-24	1-1/4 x 12
4-1/2 x 4-1/2	114 x 114	0.134	8	1/2 x 12-24	1-1/4 x 12

Size	Recommended Max Door Weight (lbs)	Spring Hinge	Ball Bearing Hinge
For use on 1-3/8" (35 mm) door			
3-1/2 x 3-1/2	40	1	2
3-1/2 x 3-1/2	70	2	1
3-1/2 x 3-1/2	90	3	-
For use on 1-3/4" (45 mm) door			
4 x 4	60	1	2
4 x 4	85	2	1
4 x 4	110	3	-
4-1/2 x 4, 4-1/2 x 4-1/2	70	1	2
4-1/2 x 4, 4-1/2 x 4-1/2	115	2	1
4-1/2 x 4, 4-1/2 x 4-1/2	150	3	-

SWING CLEAR

The following swing clear spring hinge is for automatic closing of door. It provides the features of both a swing clear hinge and a spring hinge. It meets codes for hotels, motels, institutions, and commercial buildings. Please note:

- For maximum versatility, use all spring hinges or a combination of spring and ball bearing hinges. Do not use plain bearing hinges.
- Full spring tension may not be required on all hinges.
- Strong wind conditions, drafts, carpeting drag, twisted/misaligned frames, or weatherstripping on doors may require additional spring hinges.



1267
Square Corner

- Steel with steel components (ANSI K81071F)
- For square edge door. Use in conjunction with AB7001 or BB1260



Hinge Size		Gauge of Metal	Hole Count	Screw Size	
Inches	mm			Machine	Wood
4-1/2 x 4-1/2	114 x 114	0.134	8	1/2 x 12-24	1-1/4 x 12