

BY-PASS - 9611 & 9612 PACKAGED SETS

FEATURES


- Heavy duty aluminum box double track and hardware
- Conforms to ANSI A156.14
- Type: D8731, D8751

SPECIFICATIONS

- For doors 1-3/8" (35 mm) thick doors (top figure)
 - no spacer kit required
- For doors 1-3/4" (45 mm) thick with tracks spaced 3/8" (10 mm) apart using 9573 (bottom figure)
- 9611 Packaged Sets for doors weighing up to 150 lbs (68 kg) per door
- 9612 Packaged Sets for doors weighing up to 250 lbs (113 kg) per door
- Quick release hangers allow easy door hanging and removal
- Hangers have 1" (25 mm) diameter wheels
- Universal extruded aluminum track interchanges with Stanley and Johnson hangers and track


| Part Number | Description | |
|---|---|--|
| 9611 Packaged Set Includes two (2) 9821 tracks and one (1) 9892 parts bag: four (4) 9824 hangers, or guide, and one (1) 9573 spacer For doors up to 150 lbs (68 kg) per door | | |
| 9611-60 | By-Pass Set - For two 30" (762 mm) doors | |
| 9611-72 | By-Pass Set - For two 36" (914 mm) doors | |
| 9611-96 | By-Pass Set - For two 48" (1219 mm) doors | |
| 9612 Series Set Includes two (2) 9821 tracks and one (1) 9893 parts bag: four (4) 9825 hangers, one (1) 9 guide, and one (1) 9573 spacer For doors up to 250 lbs (113 kg) per door | | |
| 9612-60 | By-Pass Set - For two 30" (762 mm) door | |
| 9612-72 | By-Pass Set - For two 36" (914 mm) door | |
| 9612-96 | By-Pass Set - For two 48" (1219 mm) door | |


Installation note: Clearance between door bottom and top of 9122 track must be 7/8" (22 mm) minimum to 1-3/4" (44 mm) maximum.



Optional Bottom Track







Interchanges with Stanley 125/250 Series and Johnson 100 Series







BY-PASS - 9611 & 9612 TRACK COMPONENTS



9821 **Aluminum Box Track**

Extruded aluminum Materials: 0.06" (2 mm) thick Gauge: Track: 1-5/8" x 1-1/16" (41 mm x 27 mm) Lengths:

59" (1499 mm) to 144" (3658 mm)

 Jump proof twin channel Notes:

design

• Two-piece required for

by-pass



9573

Celcon Plastic Spacer Kit

Celcon plastic Materials: • Includes screws Notes:

> • Properly spaces two single tracks for 1-3/4" (44 mm)

doors



9892 Parts Bag

Includes four (4) 9824 4-wheel hangers with quick release top mount plate, one (1) 9909 guide, and one (1) 9573 spacer kit Note: Up to 150 lbs (68 kg) per door



9893 Parts Bag

Includes four (4) 9825 4-wheel ball bearing hangers with quick release top mount plate, one (1) 9909 guide, and one (1) 9573 spacer kit

Note: Up to 250 lbs per door



9824

4 Wheel Hanger with Quick Release **Top Mount Plate**

Materials: Zinc plated steel Self aligning to allow Wheels:

consistent contact with

track

Wheel: 1" (25 mm) diameter Notes:

• Pre-lubricated Celcon

wheels

• Up to 150 lbs (68kg)

per door

• For use with 9821 track

• Ouick release feature allows easy door hanging

and removal



9825

9709

4 Wheel Ball Bearing Hanger with **Quick Release Top Mount Plate**

Materials: Zinc plated steel Self aligning to allow Wheels:

consistent contact with track with steel ball bearings

Wheel: 1" (25 mm) diameter

Notes: • Pre-lubricated Celcon

wheels

• Up to 250 lbs (113 kg)

per door

• For use with 9821 track

• Quick release feature allows easy door hanging

and removal



9909

Notes:

Adjustable Guide

Steel with bright zinc finish Materials: Posts: Molded Celcon/Nylon 0.060" (1.5 mm) Gauge: Guide: 4-7/8" x 1-5/8" x 1-3/16"

(124 mm x 41 mm x 30 mm)

For doors 3/4" to 1-3/4"

(19 mm to 44 mm) thick and

up to 275 lbs (125 kg)

Optional Components

Fascia

| 5,05 | . 400.4 |
|------|----------------------|
| 2610 | Pull |
| 2630 | Pull |
| 9865 | Pull |
| 9121 | Bottom Door Guide |
| 9122 | Bottom Guide Channel |
| 9351 | Adjustable Guide |
| 9353 | Adjustable Guide |
| 9354 | 3/4" Riser |
| 9815 | Bumper Stop |
| 9880 | Door Stop |
| | |

For optional components see pages 59-63