



WALL STOPS & HOLDERS



230W Convex Wall Stop

Certification: Meets ANSI A156.16 for L02101
 Diameter: 2-15/32" (63 mm)
 Projection: 1-3/32" (28 mm)
 Materials: Cast brass, bronze with grey rubber bumper
 Finishes: US3, US4, US10, US10B, US15, US15A, US19, US26, US26D
 Fasteners: One (1) #10 x 1-1/2" PPHWS with plastic and toggle anchor.
 Notes:

- Concealed tamper proof mounting
- Easy installation by inserting screwdriver through small hole in bumper
- Specify 230T for machine screw and toggle nut screwpack (10 pk)



232W | BL232W Convex Wall Stop

Certification: Meets ANSI A156.16 for L02101
 Diameter: 2-7/16" (62 mm)
 Projection: 1" (25 mm)
 Materials: Wrought brass, bronze, stainless steel with grey rubber bumper
 Finishes: US3, US4, US5, US9, US10, US10B, US15, US15A, US19, US26, US26D, US32, US32D
 Fasteners: One (1) #10 x 1-1/2" PPHWS with plastic and toggle anchor
 Notes:

- Concealed tamper proof mounting
- Easy installation by inserting screwdriver through small hole in bumper
- Specify 230T for machine screw and toggle nut screwpack (10 pk)
- BL232W is 232W case quantity 50



234W Concave Wall Stop

Certification: Meets ANSI A156.16 for L02251
 Diameter: 2-15/32" (63 mm)
 Projection: 1-3/32" (28 mm)
 Materials: Cast brass, bronze with grey rubber bumper
 Finishes: US3, US4, US10, US10B, US15, US15A, US19, US26, US26D
 Fasteners: One (1) #10 x 1-1/2" PPHWS w/ plastic and toggle anchor
 Notes:

- Easy installation by inserting screwdriver through small hole in rubber bumper
- Concealed tamper proof mounting
- Concave rubber bumper prevents damage to locksets with projecting buttons
- Specify 230T for machine screw and toggle nut screwpack (10 pk)



236W | BL236W Concave Wall Stop

Certification: Meets ANSI A156.16 for L02251
 Diameter: 2-7/16" (75 mm)
 Projection: 1" (25 mm)
 Materials: Wrought brass, bronze, stainless steel with grey rubber bumper
 Finishes: US3, US4, US5, US9, US10, US10B, US15, US15A, US19, US26, US26D, US32, US32D
 Fasteners: One (1) #10 x 1-1/2" PPHWS w/ plastic and toggle anchor
 Notes:

- Easy installation by inserting screwdriver through small hole in rubber bumper
- Concealed tamper proof mounting
- Concave rubber bumper prevents damage to locksets with projecting buttons
- Specify 230T for machine screw and toggle nut screwpack (10 Pk)
- BL236W is 236W case quantity 50

WALL STOPS & HOLDERS



250W

Convex Wall Stop

- Diameter: 1" (25 mm)
 Projection: 9/16" (14 mm)
 Materials: Cast brass
 Finishes: US3, US4, US10, US10B, US15, US15A, US19, US26, US26D
 Fasteners: One (1) #6 x 3/4" screw with plastic anchor and one (1) 0.052 diameter nail
 Notes:
 - Concealed mounting screw prevents vandalism
 - For use on drywall
 - Compact design



251W

Concave Wall Stop

- Diameter: 1-7/8" (48 mm)
 Projection: 25/32" (20 mm)
 Materials: Adhesive backed rubber bumper
 Finish: Grey only
 Notes:
 - Concave bumper prevents damage to locksets with projecting buttons
 - For areas where concealed mounting is not required
 - Adhesive backing for use on clean smooth flat surfaces only



254S

Wall Stop & Holder

- Certification: Meets ANSI A156.16 for L01341
 Base Diameter: 2-11/32" (60 mm)
 Base Projection: 3-1/2" (89 mm)
 Engaged Projection: 5-19/32" (142 mm)
 Keeper: 1" x 2" (25 mm x 51 mm)
 Materials: Cast brass with black rubber bumper
 Finishes: US3, US4, US10, US10B, US15, US26, US26D
 Fasteners: Five (5) #10 x 1" FPHWS, and three (3) plastic anchors
 Notes:
 - For use on drywall
 - Manual holder ideal for interior and exterior applications
 - Unit functions as a stop, but can serve as a "Hold Open" when hook is manually engaged
 - Ideal for use with locksets with a projection of 3-5/16" (84 mm) or less



254W

Wall Stop & Holder

- Certification: Meets ANSI A156.16 for L01351
 Base Diameter: 2-11/32" (60 mm)
 Base Projection: 3-1/2" (89 mm)
 Engaged Projection: 5-19/32" (142 mm)
 Keeper: 1" x 2" (25 mm x 51 mm)
 Materials: Cast brass with black rubber bumper
 Finishes: US3, US4, US10, US10B, US15, US26, US26D
 Fasteners: Three (3) #10 x 1" FPH tapping screw, one (1) plastic anchor, one (1) 5/16-18 x 2-1/2" threaded stud, and one (1) 5/16-18 lead anchor
 Notes:
 - For use on concrete walls
 - Manual holder ideal for interior and exterior applications
 - Unit functions as a stop, but can serve as a "Hold Open" when hook is manually engaged
 - Ideal for use with locksets with a projection of 3-5/16" (84 mm) or less



WALL STOPS & HOLDERS



255S

Wall Stop

- Certification: Meets ANSI A156.16 for L02011
 Base Diameter: 2-11/32" (60 mm)
 Projection: 3-11/16" (94 mm)
 Materials: Cast brass with black rubber bumper
 Finishes: US3, US4, US10, US10B, US15, US26, US26D
 Fasteners: Three (3) #10 x 1" OPHWS and three (3) plastic anchors
 Notes:
- For use on drywall
 - Ideal for interior and exterior applications
 - Heavy duty - for use in high traffic areas
 - Ideal for use with locksets with a projection of 3" (76 mm) or less



255W

Wall Stop

- Certification: Meets ANSI A156.16 for L02021
 Base Diameter: 2-11/32" (60 mm)
 Projection: 3-11/16" (94 mm)
 Materials: Cast brass with black rubber bumper
 Finishes: US3, US4, US10, US10B, US15, US26, US26D
 Fasteners: One (1) #10 x 1" OPHWS, one (1) plastic anchor, one (1) 5/16-18 lead anchor, one (1) 5/16-18 x 2-1/2" threaded stud, one (1) 5/16-18 x 2-1/2" combo threaded stud
 Notes:
- For use on concrete walls
 - Ideal for interior and exterior applications
 - Heavy duty - for use in high traffic areas
 - Ideal for use with locksets with a projection of 3" (76 mm) or less



256S

Manual Wall Stop & Holder

- Certification: Meets ANSI A156.16 for L01341
 Base Diameter: 2-1/4" (57 mm)
 Base Projection: 3-3/4" (95 mm)
 Engaged Projection: 5-11/16" (145 mm)
 Keeper: 25/32" x 1-1/2" (20 mm x 38 mm)
 Materials: Cast brass with black rubber bumper
 Finishes: US3, US10, US10B, US15, US26, US26D
 Fasteners: Three (3) #10 x 1" OPHWS and three (3) plastic anchors
 Notes:
- For use on drywall
 - Ideal for interior and exterior applications
 - Heavy duty - for use in high traffic areas
 - Unit functions as a stop, but can serve as a "Hold Open" when hook is manually engaged
 - Ideal for use with locksets with a projection of 3" (76 mm) or less

WALL STOPS & HOLDERS



256W

Manual Wall Stop & Holder

Certification: Meets ANSI A156.16 for L01351
 Base Diameter: 2-1/4" (57 mm)
 Base Projection: 3-3/4" (95 mm)
 Engaged Projection: 5-11/16" (145 mm)
 Keeper: 25/32" x 1-1/2" (20 mm x 38 mm)
 Materials: Cast brass with black rubber bumper
 Finishes: US3, US10, US10B, US15, US26, US26D
 Fasteners: One (1) #10 x 1" OPHWS, one (1) plastic anchor, one (1) 5/16-18 lead anchor, one (1) 5/16-18 x 2-1/2" threaded stud, and one (1) 5/16-18 x 2-1/2" combo threaded stud

Notes:

- For use on concrete walls
- Ideal for interior and exterior applications
- Heavy duty - for use in high traffic areas
- Unit functions as a stop, but can serve as a "Hold Open" when hook is manually engaged
- Ideal for use with locksets with a projection of 3" (76 mm) or less



260W

Angled Wall Stop

Certification: Meets ANSI A156.16 for L02201
 Base: 2-3/16" x 2-15/16" (56 mm x 75 mm)
 Projection: 3-21/32" (93 mm)
 Materials: Cast brass with black rubber bumper
 Finishes: US26D
 Fasteners: Three (3) #14 x 1-1/2" FPHWS, three (3) 1/4-20 x 3/4" FPHMS, three (3) plastic anchors, and three (3) 1/4-20 lead anchors

Notes:

- For use with drywall or concrete walls
- Sloping design resists vandalism
- Ideal for use with locksets with a projection of 3" (76 mm) or less



324W

Light Duty Wall Bumper

Certification: Meets ANSI A156.16 for L02031
 Base Diameter: 1-1/4" (32 mm)
 Projection: 3-1/4" (83 mm)
 Tip Diameter: 5/8" (16 mm)
 Materials: Cast brass, bronze with white rubber tip
 Finishes: US3, US4, US5, US10, US10B, US15, US15A, US19, US26, US26D
 Fastener: #10 x 7/8" wood thread

Notes:

- Replaceable rubber tip available
- Hex shape near the tip allows usage of a wrench for easier installation



WALL STOPS & HOLDERS



326W

Automatic Wall Stop & Holder

- Certification: Meets ANSI A156.16 for L01293
 Holder Base: 2-13/32" x 2-25/32" (61 mm x 71 mm)
 Holder Projection: 2-5/16" (59 mm)
 Engaged Projection: 3-5/8" (92 mm)
 Strike Base: 1" x 2-1/16" (25 mm x 52 mm)
 Strike Projection: 2" (51 mm)
 Keeper: 1" x 2" (25 mm x 51 mm)
 Materials: Cast brass
 Finishes: US3, US10, US10B, US26, US26D
 Fasteners: Five (5) #10 x 1" OPHWS, three (3) 10-24 x 1-1/4" FPHMS, and three (3) plastic anchors
- Notes:
- For use with wood or metal doors
 - Holder is mounted on the door
 - Roller is spring loaded to seat on strike - heavy duty rubber pad dampens sound and shock
 - Ideal for use with locksets with a projection of 3" (76 mm) or less



327W

Automatic Wall Stop & Holder

- Certification: Meets ANSI A156.16 for L11291
 Holder Base: 3-1/16" x 3-1/2" (78 mm x 89 mm)
 Holder Projection: 1-15/16" (49 mm)
 Engaged Projection: 3-1/2" (89 mm)
 Strike Diameter: 2-3/8" (60 mm)
 Strike Projection: 3-1/16" (78 mm)
 Materials: Cast brass
 Finishes: US3, US4, US10, US10B, US26, US26D
 Fasteners: Three (3) #14 x 1-1/2" FPHWS, three (3) 1/4-20 x 3/4" FPHMS, four (4) 12-24 x 1" TPHMS, four (4) #12 x 1" TPHWS, and three (3) 1/4-20 lead anchors
- Notes:
- For use with wood or metal doors
 - For use with drywall or concrete walls
 - Roller is spring loaded to seat on strike - heavy duty rubber pad dampens sound and shock
 - Strike is adjustable 45° left or right
 - Holder has vertical adjustment once mounted on the door
 - Ideal for use with locksets with a projection of 3" (76 mm) or less
 - For doors up to 500 lbs

ROLLER STOPS



271W

Roller Bumper

Certification:

Base Diameter:

Projection:

Materials:

Finishes:

Fasteners:

Notes:

Meets ANSI A156.16 for L02193

2" (51 mm)


4-1/2" (114 mm)

Cast brass with grey rubber roller

US3, US10, US10B, US26, US26D

Three (3) #10 x 1" FPHWS and three (3) plastic anchors

- For use when two doors swing into each other at right angles (back to back)
- Prevents damage to the door and door hardware



272W

Roller Bumper

Certification:

Base Diameter:

Projection:

Materials:

Finishes:

Fasteners:

Notes:

Meets ANSI A156.16 for L02193

2" (51 mm)


6-1/4" (159 mm)

Cast brass with grey rubber roller

US3, US10, US10B, US26, US26D

Three (3) #10 x 1" FPHWS, and three (3) plastic anchors

- For use when two doors swing into each other at right angles (back to back)
- Prevents damage to the door and door hardware



273W

Curved Roller Bumper

Certification:

Projection:

Materials:

Finishes:

Fasteners:

Notes:

Meets ANSI A156.16 for L12213


2-21/32" (67 mm)

Cast brass with grey rubber roller

US3, US4, US10, US10B, US26, US26D

Three (3) #10 x 1" FPHWS and three (3) plastic anchors

- Used when two doors swing into each other at odd angles
- Prevents damage to the door and door hardware





FLOOR STOPS & HOLDERS



241F | BL241F

Dome Stop - Low

- Certification: Meets ANSI A156.16 for L02142
 Base Diameter: 1-11/16" (43 mm)
 Base Thickness: 1/8" (3.2 mm)
 Overall Height: 1" (25 mm)
 Materials: Cast brass with grey rubber bumper
 Finishes: US3, US4, US5, US9, US10, US10B, US15, US15A, US19, US26, US26D
 Fasteners: One (1) #14 x 1-1/2" FPHWS, one (1) 1/4-20 x 3/4" FPHMS, one (1) 1/4-20 lead anchor, and one (1) plastic anchor
- Notes:
- To be used independently or in conjunction with 246B
 - For use when no threshold is used (door not undercut)
 - For use with wood or concrete floors
 - BL241F is 241F case quantity 50



242F

Dome Stop - Universal

- Certification: Meets ANSI A156.16 for L02162
 Base Diameter: 1-11/16" (43 mm)
 Base Thickness: 7/32" (5.5 mm)
 Overall Height: 1-5/8 (41 mm)
 Materials: Brass with grey rubber bumper
 Finishes: US3, US4, US10B, US15, US26, US26D
 Fasteners: One (1) #14 x 1-1/2" FPHWS, one (1) 1/4-20 x 3/4" FPHMS, one (1) 1/4-20 lead anchor, and one (1) plastic anchor
- Notes:
- For use with wood or concrete floors



243F | BL243F

Dome Stop - High

- Certification: Meets ANSI A156.16 for L02162
 Base Diameter: 1-11/16" (43 mm)
 Base Thickness: 7/16" (11 mm)
 Overall Height: 1-9/32" (33 mm)
 Materials: Cast brass with grey rubber bumper
 Finishes: US3, US4, US5, US9, US10, US10B, US15, US15A, US19, US26, US26D
 Fasteners: One (1) #14 x 1-1/2" FPHWS, one (1) 1/4-20 x 1-1/4" FPHMS, one (1) 1/4-20 lead anchor, and one (1) plastic anchor
- Notes:
- For use with thresholds or undercut doors
 - For use with wood or concrete floors
 - BL243F is 243F case quantity 50



244F

Cast Floor Stop

- Certification: Meets ANSI A156.16 for L02141
 Base: 1-3/4" x 4" (45 mm x 102 mm)
 Base Thickness: 5/32" (4 mm)
 Overall Height: 1" (25 mm)
 Materials: Cast brass with grey rubber bumper
 Finishes: US3, US4, US10, US10B, US26, US26D
 Fasteners: Two (2) #14 x 1-1/2" FPHWS, two (2) 1/4-20 x 3/4" FPHMS, two (2) 1/4-20 lead anchor, and two (2) plastic anchor
- Notes:
- Heavy duty - for use in high traffic areas
 - For use when no thresholds are used (door not undercut)
 - For use with wood or concrete floors

FLOOR STOPS & HOLDERS



245F

Cast Floor Stop

Certification: Meets ANSI A156.16 for L02161
 Base: 1-3/4" x 4" (45 mm x 102 mm)
 Base Thickness: 1/2" (13 mm)
 Overall Height: 1-5/16" (33 mm)
 Materials: Cast brass with grey rubber bumper
 Finishes: US3, US4, US10, US10B, US26, US26D
 Fasteners: Two (2) #14 x 1-1/2" FPHWS, two (2) 1/4-20 x 1-1/4" FPHMS, two (2) 1/4-20 lead anchor, and two (2) plastic anchor
 Notes:

- Heavy duty - for use in high traffic areas
- For use with thresholds and undercut doors
- For use on wood or concrete floors



246B

Dome Stop Riser Plate

Diameter: 1-3/4" (45 mm)
 Thickness: 3/8" (10 mm)
 Fasteners: One (1) 1/4-20 x 1" FPHMS
 Materials: Cast brass
 Finishes: US3, US4, US10, US10B, US15, US15A, US19, US26, US26D
 Notes: For use with 241F on undercut doors, doors with thresholds, and carpeted flooring



248F

Modern Style Universal Stop

Base Diameter: 1-7/16" (37 mm)
 Height: 1-1/2" (38 mm)
 Materials: Brass with black rubber bumper
 Finishes: US26D
 Fasteners: One (1) #12 x 1-1/4" FPHWS, one (1) plastic anchor, one (1) 1/4-20 x 1" FPHMS, and one (1) 1/4-20 lead anchor



248G

Modern Style Universal Stop

Base Diameter: 1-7/16" (37 mm)
 Height: 1-1/2" (38 mm)
 Materials: Brass with grey rubber bumper
 Finishes: US26D
 Fasteners: One (1) #12 x 1-1/4" FPHWS with plastic anchor and one (1) 1/4-20 x 1" FPHMS with lead anchor



249F

L-Shaped Floor Stop

Base: 1" x 2-1/2" x 7/32" thick (25 mm x 64 mm x 6 mm)
 Base Thickness: 1/4" (6 mm)
 Overall Height: 2-5/8" (67 mm)
 Stop face: Resilient black rubber
 Materials: Steel
 Fasteners: Two (2) #14 x 1-1/2" FPHWS and two (2) plastic anchors
 Notes: 1-1/2" (38 mm) max door to floor clearance



FLOOR STOPS & HOLDERS



252F

Floor Stop

Certification:

Meets ANSI A156.16 for L02131

Base:

1-9/16" x 2-1/2" (40 mm x 64 mm)

Overall Height:

2-11/16" (68 mm)

Materials:

Cast brass with black rubber bumper

Finishes:

US3, US10, US10B, US15, US15A, US19, US26, US26D

Fasteners:

One (1) #14 x 1-1/2" FPHWS, one (1) 1/4-20 x 3/4" FPHMS, one (1) 5/16-18 lead anchor, one (1) 1/4-20 lead anchor, one (1) plastic anchor, one (1) 5/16-18 x 2-1/2" threaded stud, and one (1) 5/16-18 x 2-1/2" combo threaded stud

Notes:

- Heavy duty - for use in high traffic areas
- For use on wood or concrete floors
- 2" (51 mm) max door to floor clearance



257F

Floor Stop

Certification:

Meets ANSI A156.16 for L02131

Base:

1-9/16" x 2-15/32" (40 mm x 63 mm)

Overall Height:

2" (51 mm)

Materials:

Cast brass with black rubber bumper

Finishes:

US3, US10, US10B, US15, US15A, US19, US26, US26D

Fasteners:

One (1) #14 x 1-1/2" FPHWS, one (1) 1/4-20 x 3/4" FPHMS, one (1) 5/16-18 lead anchor, one (1) 1/4-20 lead anchors, one (1) plastic anchor, one (1) 5/16-18 x 2-1/2" threaded stud, and one (1) 5/16-18 x 2-1/2" combo threaded stud

Notes:

- 1-3/8" (35 mm) max door to floor clearance
- Heavy duty - for use in high traffic areas
- For use on wood or concrete floors



258F

Floor Stop and Holder

Certification:

Meets ANSI A156.16 for L01371

Base:

1-9/16" x 2-15/32" (40 mm x 63 mm)

Height:

3" (76 mm)

Keeper:

1" x 2" (25 mm x 51 mm)

Materials:

Cast brass with black rubber bumper

Finishes:

US3, US10, US10B, US15, US26, US26D

Fasteners:

Two (2) #10 x 1" FPHWS, one (1) 1/4-20 x 3/4" FPHMS, one (1) 5/16-18 lead anchor, one (1) 1/4-20 lead anchors, and one (1) 5/16-18 x 2-1/2" threaded stud

Notes:

- 1-3/8" (35 mm) max door to floor clearance
- Heavy duty - for use in high traffic areas
- For use on concrete floors
- Manual holder ideal for interior and exterior applications
- Unit functions as a stop, but can serve as a "Hold Open" when hook is manually engaged

FLOOR STOPS & HOLDERS



259F

Tri Base Floor Stop

- Certification: Meets ANSI A156.16 for L02121
 Base: 2-1/2" wide x 1-9/16" deep (64 mm x 40 mm)
 Overall Height: 1-11/16" (43 mm)
 Material: Cast brass with grey rubber bumper
 Finishes: US3, US4, US10, US10B, US26, US26D
 Fasteners: Three (3) #10 x 1-1/4" FPHWS, three (3) plastic anchors, three (3) 10-32 x 3/4" FPHMS, and three (3) 10-32 lead anchor
 Notes:
 - 1/2" (13 mm) max door to floor clearance
 - Heavy duty - for use in high traffic areas
 - For use on wood or concrete floors



259H

Tri Base Floor Stop - Tall

- Certification: Meets ANSI A156.16 for L02121
 Base: 2-1/2" wide x 1-9/16" deep (64 mm x 40 mm)
 Overall Height: 2-1/4" (57 mm)
 Materials: Cast brass with grey rubber bumper
 Finishes: US3, US4, US10, US10B, US26, US26D
 Fasteners: Three (3) #10 x 1-1/4" FPHWS, three (3) plastic anchor, three (3) 10-32 x 3/4" FPHMS, and three (3) 10-32 lead anchors
 Notes:
 - 1" (25 mm) max door to floor clearance
 - Heavy duty - for use in high traffic areas
 - For use on wood or concrete floors



267F

Cast Floor Stop

- Certification: Meets ANSI A156.16 for L02131
 Base Diameter: 2-1/4" (57 mm)
 Overall Height: 3-1/8" (80 mm)
 Materials: Cast brass with black rubber bumper
 Finishes: US3, US10, US10B, US15, US15A, US19, US26, US26D
 Fasteners: One (1) #10 x 1" OPHWS, one (1) plastic anchor, one (1) 5/16-18 lead anchor, one (1) 5/16-18 x 2-1/2" threaded stud, and one (1) 5/16-18 x 2-1/2" combo threaded stud
 Notes:
 - 2-3/8" (60 mm) max door to floor clearance
 - Heavy duty - for use in high traffic areas
 - For use on concrete floors



267S

Cast Floor Stop

- Certification: Meets ANSI A156.16 for L02121
 Base Diameter: 2-1/4" (57 mm)
 Overall Height: 3-1/8" (80 mm)
 Materials: Cast brass with black rubber bumper
 Finishes: US3, US10, US10B, US15, US15A, US19, US26, US26D
 Fasteners: Three (3) #10 x 1" OPHWS and three (3) plastic anchors
 Notes:
 - 2-3/8" (60 mm) max door to floor clearance
 - Heavy duty - for use in high traffic areas
 - For use on wood floors



FLOOR STOPS & HOLDERS



268F

Cast Floor Stop and Holder

- Certification: Meets ANSI A156.16 for L01371
- Base Diameter: 2-1/4" (57 mm)
- Height: 3-19/32" (91 mm)
- Keeper: 25/32" x 1-1/2" (20 mm x 38 mm)
- Materials: Cast brass with black rubber bumper
- Finishes: US3, US10, US10B, US15, US15A, US19, US26, US26D
- Fasteners: Three (3) #10 x 1" OPHWS, one (1) plastic anchor, one (1) 5/16-18 lead anchor, and one (1) 5/16-18 x 2-1/2" threaded stud
- Notes:
- 2-1/2" (64 mm) max door to floor clearance
 - Heavy duty - for use in high traffic areas
 - For use on concrete floors
 - Manual holder ideal for interior and exterior applications
 - Unit functions as a stop, but can serve as a "Hold Open" when hook is manually engaged



268S

Cast Floor Stop and Holder

- Certification: Meets ANSI A156.16 for L01361
- Base Diameter: 2-1/4" (57 mm)
- Height: 3-19/32" (91 mm)
- Keeper: 25/32" x 1-1/2" (20 mm x 38 mm)
- Materials: Cast brass with black rubber bumper
- Finishes: US3, US10, US10B, US15, US15A, US19, US26, US26D
- Fasteners: Five (5) #10 x 1" OPHWS and three (3) plastic anchors
- Notes:
- 2-1/2" (64 mm) max door to floor clearance
 - Heavy duty - for use in high traffic areas
 - For use on wood floors
 - Manual holder ideal for interior and exterior applications
 - Unit functions as a stop, but can serve as a "Hold Open" when hook is manually engaged



269F

Heavy Duty Floor Stop

- Certification: Exceeds the criteria set forth for a 300-pound impact test (Report #91-04-01646)
- Bumper Diameter: 2" (51 mm)
- Bumper Height: 1-1/2" (38 mm)
- Steel Bolt: 5/8 - 11 x 2-1/2" thread
- Materials: Black rubber (fire-resistant)
- Notes:
- Designed for high vandalism areas
 - Ideal for prisons where floor stops are required
 - Grouted in concrete to eliminate exposed screws

FLOOR STOPS & HOLDERS



269T

Heavy Duty Floor Stop

Certification:

Exceeds the criteria set forth for a 300-pound impact test
(Report #91-04-01646)

Bumper Diameter:

2" (51 mm)

Bumper Height:

3-1/2" (89 mm)

Steel Bolt:

5/8 – 11 x 2-1/2" thread

Materials:

Black rubber (fire-resistant)

Notes:

- Designed for high vandalism areas
- Ideal for prisons where floor stops are required
- Grouted in concrete to eliminate exposed screws



326F

Automatic Floor Stop and Holder

Certification:

Meets ANSI A156.16 for L01301

Holder Projection:

1-15/16" (49 mm)

Holder Base:

3-1/16" x 3-1/2" (78 mm x 89 mm)

Floor Strike:

2" x 4-3/32" (51 mm x 104 mm)

Strike Height:

1-1/4" (32 mm)

Max Door to Floor Clearance:

1/2" (13 mm) or less

Materials:

Cast brass

Finishes:

US3, US10, US10B, US26, US26D

Fasteners:

Three (3) #14 x 1-1/2" FPHWS, three (3) 1/4-20 x 3/4" FPHMS, three (3) 1/4-20 lead anchors, four (4) 12-24 x 1" TPHMS, and four (4) #12 x 1" TPHWS

Notes:

- For use on wood or metal doors and wood or concrete floors
- Ideal for heavy traffic situations that require frequent hold open
- Firm pull releases holding mechanism
- Holder has vertical adjustment once mounted on the door



327F

Automatic Floor Stop and Holder

Certification:

Meets ANSI A156.16 for L01301

Holder Projection:

1-15/16" (49 mm)

Holder Base:

3-1/16" x 3-1/2" (78 mm x 89 mm)

Floor Strike:

2-3/16" x 4-1/8" (56 mm x 105 mm)

Strike Height:

1-3/4" (44 mm)

Max Door to Floor Clearance:

9/16" to 1-1/16" (14 mm to 27 mm)

Materials:

Cast brass

Finishes:

US3, US10, US10B, US26, US26D

Fasteners:

Three (3) #14 x 1-1/2" FPHWS, three (3) 1/4-20 x 3/4" FPHMS, three (3) 1/4-20 lead anchors, four (4) 12-24 x 1" TPHMS, and four (4) #12 x 1" TPHWS

Notes:

- For use on wood or metal doors and wood or concrete floors
- Ideal for heavy traffic situations that require frequent hold open
- Firm pull releases holding mechanism
- Holder has vertical adjustment once mounted on the door



FLOOR STOPS & HOLDERS



328F

Automatic Floor Stop and Holder

Certification: Meets ANSI A156.16 for L01301
 Holder Projection: 1-15/16" (49 mm)
 Holder Base: 3-1/16" x 3-1/2" (78 mm x 89 mm)
 Floor Strike: 2-3/16" x 4-1/8" (56 mm x 105 mm)
 Strike Height: 2-1/4" (57 mm)
 Max Door to Floor Clearance: 1-1/8" to 1-9/16" (29 mm to 40 mm)
 Materials: Cast brass
 Finishes: US3, US10, US10B, US26, US26D
 Fasteners: Three (3) #14 x 1-1/2" FPHWS, three (3) 1/4-20 x 3/4" FPHMS, three (3) 1/4-20 lead anchors, four (4) 12-24 x 1" TPHMS, and four (4) #12 x 1" TPHWS

- Notes:
- For use on wood or metal doors and wood or concrete floors
 - Ideal for heavy traffic situations that require frequent hold open
 - Firm pull releases holding mechanism
 - Holder has vertical adjustment once mounted on the door



329F

Automatic Floor Stop and Holder

Certification: Meets ANSI A156.16 for L01301
 Holder Projection: 1-15/16" (49 mm)
 Holder Base: 3-1/16" x 3-1/2" (78 mm x 89 mm)
 Floor Strike: 2-3/16" x 4-1/8" (56 mm x 105 mm)
 Strike Height: 2-3/4" (70 mm)
 Max Door to Floor Clearance: 1-5/8" to 2-1/16" (41 mm to 52 mm)
 Materials: Cast brass
 Finishes: US3, US10, US10B, US26, US26D
 Fasteners: Three (3) #14 x 1-1/2" FPHWS, three (3) 1/4-20 x 3/4" FPHMS, three (3) 1/4-20 lead anchors, four (4) 12-24 x 1" TPHMS, and four (4) #12 x 1" TPHWS

- Notes:
- For use on wood or metal doors and wood or concrete floors
 - Ideal for heavy traffic situations that require frequent hold open
 - Firm pull releases holding mechanism
 - Holder has vertical adjustment once mounted on the door

KICK DOWN DOOR STOPS



270C

Kick Down Door Holder

- Certification: Meets ANSI A156.16 for L71382
 Base: 1-7/16" x 2-1/8" (37 mm x 54 mm)
 Arm: 3-13/16" (97 mm)
 Materials: Cast iron with rubber tip
 Finishes: S1 - Sprayed Aluminum, S2 - Sprayed Brass, S3 - Sprayed Bronze
 Fasteners: Four (4) #6 x 3/4" OPH tapping screws
 Notes:
 - Provides simple hold and release with a touch of the foot
 - 2-1/4" (57 mm) max door to floor clearance



270D

Kick Down Door Holder

- Certification: Meets ANSI A156.16 for L01381
 Base: 1-19/32" x 1-25/32" (41 mm x 45 mm)
 Arm: 3-1/2" (89 mm)
 Materials: Cast brass with rubber tip
 Finishes: US3, US10, US10B, US15, US15A, US19, US26, US26D
 Fasteners: Three (3) #6 x 3/4" OPHWS
 Notes:
 - Provides simple hold and release with a touch of the foot
 - 2-1/4" (57 mm) max door to floor clearance



270R

Replacement Rubber Tip

- Materials: Rubber
 Notes:
 - For use with 270D and 271D
 - Sold in packs of 10



270CR

Replacement Rubber Tip

- Materials: Rubber
 Notes:
 - For use with 270C
 - Sold in packs of 6



271D

Kick Down Door Holder

- Certification: Meets ANSI A156.16 for L01381
 Base: 1-19/32" x 1-25/32" (41 mm x 45 mm)
 Arm: 4-7/16" (87 mm)
 Materials: Cast brass with rubber tip
 Finishes: US3, US10, US10B, US26, US26D
 Fasteners: Three (3) #6 x 3/4" OPHWS
 Notes:
 - Provides simple hold and release with a touch of the foot
 - 3-1/4" (83 mm) max door to floor clearance