

OPTIONAL COMPONENTS



9113

Stop

Materials: Zinc plated steel and rubber
 Stop: 1-5/8" x 1-1/2" x 5/8" x
 1-3/4" (41 mm x 38 mm x
 16 mm x 45 mm)

Notes: Use with 9105 hanger



9114

Bottom Guide Rail

Materials: Aluminum
 Guide: 7/8" x 1/2" (22 mm x 13 mm)
 Lengths: 72" (1829 mm)
 96" (2438 mm)
 144" (3658 mm)

Notes:

- Door bottom prep requires 1/4" (6 mm) wide kerf and 9/16" (14 mm) depth
- Pre-punched for use with flat head screws



9121

Adjustable Bottom Door Guide

Materials: Zinc plated steel with bronze roller
 Guide: 1" x 3-1/2" x 3/16"
 (25 mm x 89 mm x 5 mm)

Post: 2-1/2" x 5/16" (64 mm x 8 mm)

Notes: Use with 9122 guide channel



9122

Bottom Guide Channel

Materials: Extruded aluminum
 Gauge: 0.093 (2.4 mm)
 Lengths: 48" (1219 mm) to 192"
 (4877 mm)
 Channel: 5/8" x 3/4"
 (16 mm x 19 mm)

Notes:

- Screws not provided
- Mortised into floor or surface mounted



9169

Top Pivot Assembly

Materials: Zinc plated steel
 Top Pivot: 1" x 3-1/2" x 1-7/16"
 (25 mm x 89 mm x 37 mm)

Notes: Inserts into 9155 top pivot clamp assembly



9200* | 9201**

Single Wheel Hanger

Materials: Zinc plated steel with molded Celcon wheels
 Gauge: 0.075" (2 mm)

Wheel: 7/8" (22 mm) diameter

Notes:

- For use on doors weighing up to 60 lbs (27 kg)
- For use with 9810, 9820, and 9840 track
- Side mounted with slot adjust offset
- Hanger is stamped "A" or "B" for easy identification

 * 9200 is A offset of 3/8" (9.5 mm)
 ** 9201 is B offset of 11/16" (17.5 mm)



9202* | 9203**

Two Wheel Hanger

Materials: Zinc plated steel with molded Celcon wheels

Gauge: 0.075" (2 mm)

Wheel: 7/8" (22 mm) diameter

Notes:

- For use on doors weighing up to 75 lbs (34 kg)
- For use with 9810, 9820, and 9840 track
- Side mounted with slot adjust offset
- Hanger is stamped "A" or "B" for easy identification

 * 9202 is B offset of 11/16" (17.5 mm)
 ** 9203 is A offset of 3/8" (9.5 mm)



9220

Bi-Fold Door Hinge

Materials: Steel with bright zinc finish
 Hinge: 3" x 1" (76 mm x 25 mm) hole

Hole Locations: 1/2" (13 mm) from the center lines of holes to center of barrel

Notes: Non-mortise and easy to install

