



LOCKS

CONVENTIONAL/FIXED CYLINDERS

Keying Options

Keyed function locks are supplied standard with Schlage 'C' keyway cylinder, drilled 6-pin, keyed 5-pin and will be keyed different with two operating keys unless otherwise specified.

- Keyed Alike, 0 Bitted, 1 Bitted
- Master Keyed, Grand Master Keyed [must specify quantity of Master keys where applicable, 3961 (5-pin) or 3962 (6-pin)]
- Construction Master Keyed (C keyway only)
- Keyed to Specific or Existing Number
- Submit master keying form; pages 72-73 or online
- Extra Cut Keys (3961 - Cut 5-pin, 3962 - Cut 6-pin)
- Key Markings: 1AA, 2AA etc. (per key)
- Key Markings other than Key Set (per key)
- Cylinder markings
- Bitting Lists are available, ordered separately from Master Keyed order, specify 3998

Optional Keyways (Conventional Cylinders)



Arrow AR1



Corbin 60



Corbin 67



Corbin 77



**Corbin/
Russwin L4**



Kwikset KW1



Weiser E



Russwin D1



Sargent LA



Schlage E



Schlage F



**Yale E1R
(PARA)**



Yale GA

Keys



3955
Key Blank
5-pin, C keyway



3961
Cut Key
5-pin, keyed to specific or existing number



3956
Key Blank
6-pin, C keyway



3962
Cut Key
6-pin, keyed to specific or existing number





CONVENTIONAL/FIXED CYLINDERS (CONTINUED)

Cylinders



3960

Fixed Cylinder Kit

Includes two operating keys
Specify keyway, tailpiece, and how keyed
Note: Cylinder instructions and ordering guide available online

Tailpieces



2-639-7000

Tailpiece 1

Pack of 10 tailpieces for use with 3453L, 3450L, 3480L, 2580L



2-639-7001

Tailpiece 2

Pack of 10 tailpieces for use with 3470L, 3495L (Exterior Lever)



2-639-7002

Tailpiece 3

Pack of 10 tailpieces for use with 3453K, 3480K, 3550L, 3553L, 3553K, 3579L, 3580L, 3580K, 3753L, 2550L, 2553L



2-639-7003

Tailpiece 4

Pack of 10 tailpieces for use with 3470K, 3570K



2-639-7005

Tailpiece 6

Pack of 10 tailpieces for use with 3114DB and 3214DB exterior cylinders



2-639-7006

Tailpiece 7

Pack of 10 tailpieces for use with 3114DB and 3214DB interior cylinders



2-639-7007

Tailpiece 8

Pack of 10 tailpieces for use with 3115DB, 3118DB, 3215DB, 3710DB, 3753DB



2-639-7008

Tailpiece 9

Pack of 10 tailpieces for use with 3653L, 3670L, 3680L



2-639-7087

Tailpiece Z

Pack of 10 tailpieces for use with 3473L, 3570L, 3573L



2-639-7094

Tailpiece X

Pack of 10 tailpieces for use with 3495L (Interior Lever)



2-639-7192

Tailpiece K

Pack of 10 tailpieces for use with 4700 key-in-lever trim (KE, KN)



2-639-7322

Tailpiece V

Pack of 10 tailpieces for use with 2570L

Rim Cylinders



3901

Rim Cylinder

- Conventional cylinder supplied drilled 6-pin, keyed 5-pin standard
- Furnished with trim ring, mounting plate, and break off screws
- Long tail piece included (shipped loose in box)
- Supplied with two operating keys



3903

Rim Dummy Cylinder

Rim Cylinder Accessories



2-639-7045

Standard Breakoff Tailpiece

1-3/4" (45 mm)



2-639-7058

Long Breakoff Tailpiece

2-3/8" (60 mm)





LOCKS

CONVENTIONAL/FIXED CYLINDERS (CONTINUED)

Rim Cylinder Accessories (Continued)



2-300-0118

Extra Long Breakoff Screws
2-3/8" (60 mm)



2-649-0137

Retaining Cup
Can be used with 45PN, 47PN, and 47RN

Mortise Cylinders



3902

Mortise Cylinder

- Conventional cylinder supplied drilled 6-pin, keyed 5-pin standard
- 3975 standard cam attached and 3972 Adams Rite cam shipped loose in the box
- Thread size is 1.150" x 32 UNS
- Cylinder face diameter is 1.360"
- Supplied with two operating keys
- 1-1/8" (29 mm) standard length, 1-1/4" (31 mm) available
- **Must specify length, cam, keyway, and keying instructions**



3904

Mortise Dummy

1-1/8" (29 mm) length



3905

Mortise ADA Turn Knob

1-1/8" (29 mm) length

Mortise Cylinder Cams



3971

Yale Cam

Radius .722" (18 mm)



3972

Adams Right Cam

Radius .560 (14 mm)



3973

Standard Cloverleaf

Radius .741" (19 mm)



3974

Marks Cam

Radius .755" (19 mm)



3975

Standard Cam

Radius .723" (18 mm)

For use with Hager exit devices and trim



3976

Schlage L Cam

Radius .637" (16 mm)

For use with Hager mortise locks (all functions)



3977

Sargent/Yale Cam

Radius .733" (18.6 mm)



3978

Corbin/Russwin/Best Cloverleaf

Radius .725" (18.5 mm)





SMALL FORMAT INTERCHANGEABLE CORE

Keying Options

Cores are furnished keyed different unless otherwise specified. Other keying options include:

- Keyed Alike
- Construction Cores
- Master keyed, Grand Master Keyed (Must specify quantity of master keys, control keys, or additional change keys, 3984.)
- Keyed to specific or existing number
- Key Markings: 1AA, 2AA etc. (per key) - VKC
- Key markings other than key set
- Core markings
- Bitting Lists are available, ordered separately from Master Keyed order, specify 3998

* Construction master keyed not available.

Keyways (Best) - A, B, C, D, E, F, G, H, J, K, L, M, Q

SFIC Cores



3981-C

Combined Core 6-Pin

Includes two change keys
Finishes include US4 or US26D

3981-U

Uncombined Core 6-Pin

Includes two key blanks
Finishes include US4 or US26D



3982-C

Combined Core 7-Pin

Includes two change keys
Finishes include US4 or US26D

3982-U

Uncombined Core 7-Pin

Includes two key blanks
Finishes include US4 or US26D

SFIC Construction Cores

Construction Small Format Interchangeable Cores are available in blue or red and are keyed alike. Will receive full credit, less shipping, of original cost upon return of construction cores with keys.



3981-Blue or 3981-Red

Construction Core

Combined, 6-pin
Includes two operating keys



3982-Blue or 3982-Red

Construction Core

Combined, 7-pin
Includes two operating keys

SFIC Keys



3983

SFIC Key Blank

Best Keyways, used with 6-pin and 7-pin cores



3984

SFIC Cut Key

Best Keyways, used with 6-pin and 7-pin cores

SFIC Construction Core Keys



2-639-7168

3984 Control Key (BA IC 6 Blue)

2-639-7169

3984 Control Key (BA IC 7 Blue)

2-639-7170

3984 Control Key (BA IC 7 Red)

2-639-7171

3984 Control Key (BA IC 6 Red)

Note: Two (2) each will be shipped unless otherwise specified.





LOCKS

SMALL FORMAT INTERCHANGEABLE CORE (CONTINUED)

SFIC Tailpieces



2-639-7060

Pack of 10 tailpieces for use with
2500/3500 Series SFIC lever
(6-pin/7-pin combo)



2-639-7061

Pack of 10 tailpieces for use with
3400/3500 Series SFIC knob
(6-pin/7-pin combo)



2-639-7090

Pack of 10 tailpieces for use with
3753 Interconnected Lock SFIC lever
(6-pin/7-pin combo)



2-639-7091

Pack of 10 tailpieces for use with
3114/3214 SFIC deadbolt
(6-pin/7-pin combo)



2-639-7095

Pack of 10 tailpieces for use with
3115/3118/3215 and 3710/3753
SFIC deadbolt (6-pin/7-pin combo)

SFIC Rim Cylinder Housing



3901

Rim Cylinder

- Furnished with trim ring, mounting plate, and break off screws
- Long tail piece standard
- Small Format Interchangeable Core housing supplied less core.
- Specify 6- or 7-pin.

SFIC Rim Cylinder Accessories



2-639-7045

Standard Breakoff Tailpiece
1-3/4" (45 mm)



2-639-7058

Long Breakoff Tailpiece
2-3/8" (60 mm)



2-300-0118

Extra Long Breakoff Screws
2-3/8" (60 mm)



2-649-0137

Retaining Cup

Can be used with 45PN, 47PN, and 47RN

Mortise Cylinder Housing



3902

Mortise Cylinder

- 2-639-7082 standard cam; 2-639-7083 shipped loose in the box
- Thread size is 1.150" x 32 UNS. Cylinder face diameter is 1.360"
- Small Format Interchangeable Core housing supplied less core
- **Must specify length and cam, 6-pin 1-1/4", 7-pin 1-3/8"**

Mortise Cylinder SFIC Cams



2-639-7082

Standard Yale Cam



2-639-7083

Adams Right Cam



2-639-7084

Standard Cloverleaf Cam



2-639-7085

Schlage "L" Cam

For use with Hager mortise locks (all functions)



2-639-7086

Sargent/Yale Cam

