

## 29KS

### Key Switches



#### Description:

- Provides an economical method of providing authorized control for a variety of applications
- Choice of several contact configurations ensures compatibility with virtually any system
- Compatible with U.S. standard 1.125" and 1.25" mortise key cylinders and interchangeable core cylinders (not included)
- Compatibility with a new or exiting facility mechanical key system is maintained
- Standard switch assemblies are single gang box mounted

#### Applications:

- Access control
- Automatic gate operation
- Alarm shunt
- Alarm reset
- Machine operation

## PRODUCT SPECIFICATIONS

#### FUNCTIONS:

- ASD - Alternate Action (on/off) SPDT
- MSD - Momentary SPDT
- ADD - Alternate Action (on/off) DPDT
- MDD - Momentary DPDT

#### FEATURES:

- Single gang, wall mounted, recessed key cylinder
- Tamper resistant, recessed cylinder
- Tamper resistant spanner screws
- Heavy duty all steel assembly
- 20 gauge stainless steel faceplate
- Large actuator for positive and consistent activation
- Compatible with 1.125" or 1.25" mortise cylinder (non included)

#### FINISHES:

- US32D dull stainless steel (standard)

#### OPTIONS:

- LEDG - One green LED
- LEDR - One red LED
- 2LED - One green and one red LED

#### DIMENSIONS:

- 2.875" x 4-1/2" x 20 gauge
- 73 x 114 x 0.912 mm

#### SPECIFICATIONS:

- 6 amp @ 30 VDC
- 7", 22 gauge wire leads

#### CYLINDER:

- 3902 - 1-1/8" recommended (order separately)
- 3978 cam required (order separately)