

4500 Series Rim

Grade 1 Rim Device

Applications:

- Heavy Duty Commercial

Certifications:

- BHMA Certified ANSI A156.3 Grade 1
- UL305 Listed for Panic Hardware
- UL/cUL Listed for up to 3 hours for "A" label single doors
- UL10C Positive Pressure Rated
- UL10B Neutral Pressure Rated
- Warnock Hersey listed for up to 3 hours with fire rated removable mullion
- Complies with ANSI A117.1 for accessible buildings and facilities
- Miami Dade NOA #11-1219.14 compliant. Must specify. Also complies with ANSI A 250.13 Severe Windstorm Resistant.



PRODUCT SPECIFICATIONS

TRIM:

- Archer, August, William or Withnell lever with escutcheon
- Pull plate trim
- Rim cylinder x optional pull

COVERS:

- Stainless steel, zinc

CHASSIS:

- Aluminum

END CAPS:

- Zinc

DOOR WIDTH:

- 36" (914 mm) field sizeable to 30" (762 mm) door
- 48" (1219 mm) field sizeable to 36" (914 mm) door
- 36" (762 mm) minimum w/electric latch retraction, electric dogging, or alarm kit

DOOR THICKNESS:

- 1-3/4" (44 mm) - Standard

STILE WIDTH:

- 5-3/8" (137 mm) - Minimum stile width required for single doors and standard 5/8" (16 mm) stop
- 4-7/8" (124 mm) - Minimum stile width required for double door x surface vertical rod with double door strike
- 5-3/4" (137 mm) - Minimum stile width required for double door and 2" (51 mm) mullion
- All stile widths are measured from the door edge

FASTENERS:

- Wood and machine screws
- Thru-bolts

LATCHBOLT:

- 3/4" (19 mm) throw, pullman type with automatic dead-latching, stainless steel

STRIKES:

- Stainless steel with plated rollers - Included standard with panic devices
- Solid stainless steel - Included standard with fire rated devices
- Surface applied to frame with slotted holes for easy adjustment
- Double door strike for use with surface vertical rod and rim device available

FINISHES:

- US3, US4, US10, US10B, US26, US26D, US32D

DOGGING:

- Hex key dogging standard on panic rated devices
- Cylinder dogging available on panic rated devices, specify CD (3902 1-1/8" (29 mm) mortise cylinder sold separately)

PROJECTION:

- 3" (76 mm) in undogged position
- 2-5/8" (67 mm) in dogged position

NOTE:

- Recommended to be used on appropriately reinforced doors