



CYLINDER, CORE & KEYING - SMALL FORMAT INTERCHANGEABLE CORE

SFIC Tailpieces



2-639-7060

Pack of 10 tailpieces for use with 2500/3500 Series SFIC lever (6-pin/7-pin combo)



2-639-7061

Pack of 10 tailpieces for use with 3400/3500 Series SFIC knob (6-pin/7-pin combo)



2-639-7090

Pack of 10 tailpieces for use with 3753 Interconnected Lock SFIC lever (6-pin/7-pin combo)



2-639-7091

Pack of 10 tailpieces for use with 3114/3214 SFIC deadbolt (6-pin/7-pin combo)



2-639-7095

Pack of 10 tailpieces for use with 3115/3118/3215 and 3710/3753 SFIC deadbolt (6-pin/7-pin combo)

SFIC Rim Cylinder Housing



3901

Rim Cylinder

- Furnished with trim ring, mounting plate, and break off screws
- Long tail piece standard
- Small Format Interchangeable Core housing supplied less core
- Specify 6- or 7-pin

SFIC Rim Cylinder Accessories



2-639-7058

Long Breakoff Tailpiece

2-3/8" (60 mm)



2-300-0118

Extra Long Breakoff Screws

2-3/8" (60 mm)



2-649-0137

Retaining Cup

Can be used with 45PN, 47PN, and 47RN

SFIC Mortise Cylinder Housing



3902

Mortise Cylinder

- 2-639-7082 standard cam; 2-639-7083 Adams Rite cam shipped loose in the box
- Thread size is 1.150" x 32 UNS. Cylinder face diameter is 1.360"
- Small Format Interchangeable Core housing supplied less core
- **Must specify length and cam, 6-pin 1-1/4", 7-pin 1-3/8", 7-pin 1-5/8" (for mortise exit device)**

SFIC Mortise Cylinder Cams



2-639-7082

Standard Yale Cam



2-639-7083

Adams Rite Cam



2-639-7084

Corbin/Best Cloverleaf Cam



2-639-7085

Schlage "L" Cam

For use with Hager mortise locks (all functions)



2-639-7086

Sargent/Yale Cam





CYLINDER, CORE & KEYING - LARGE FORMAT INTERCHANGEABLE CORE

Keying Options

Cores are furnished zero bitted - unless otherwise specified. Other keying options include:

- Keyed alike
- Keyed different
- Master keyed (must specify quantity of master keys, control keys or additional change keys)
- Temporary construction cores available upon request
- Keyed to specific or existing number
- Key Markings: 1AA, 2AA etc. (per key) - VKC
- Key markings other than key set
- Core markings (visual or concealed) - limited to 6 characters
- Bitting Lists are available, ordered separately from master keyed order, specify 3998

LFIC Cores (Available in Schlage C Only)


3919
Zero Bitted Core 6-Pin

Includes two key blanks

Finishes include US4 or US26D

LFIC Keys


3956
Key Blank

Schlage C Keyway, 6-pin only

Combinated Core 6-Pin

Includes two change keys

Finishes include US4 or US26D


3962
Cut Key

Schlage C Keyway, 6-pin only

LFIC Tailpieces


2-639-7645

50, 53 and 80 functions only


2-639-7646

70 function only


2-639-7647

73 and 95 functions only

3963
3919 Control Cut Key
2-639-7649
3919 Control Key Blank

LFIC Rim Cylinder Housing


3901
Rim Cylinder

- Furnished with trim ring, mounting plate, and break off screws
- Tail piece supplied standard
- Large Format Interchangeable
- Core housing supplied less core.
- 6-pin only

LFIC Rim Cylinder Accessories


2-639-7578
Breakoff Tailpiece Assy

2-3/8" (60 mm)


2-300-0175
Breakoff Screws

2-1/8" (54 mm)



CYLINDER, CORE & KEYING - LARGE FORMAT INTERCHANGEABLE CORE

LFIC Mortise Cylinder Housing



3902

Mortise Cylinder

- 2-639-7570 standard cam;
2-639-7571 Adams Rite Cam shipped loose
in the box.
- Thread size is 1.150" x 32 UNS.
Cylinder face diameter is 1.360".
- Large Format Interchangeable
Core housing supplied less core
- **Must specify cam, 1-1/2" length**

LFIC Mortise Cylinder Cams



2-639-7570
Standard Yale Cam



2-639-7571
Adams Rite Cam



2-639-7572
Schlage "L" Cam
For use with Hager mortise locks
(all functions)



2-639-7573
Corbin/Best Cloverleaf Cam



2-639-7574
Sargent/Yale Cam

CYLINDER, CORE & KEYING - CONVENTIONAL CYLINDERS - HAGER KEYWAY - (7-PIN ONLY)

Keying Options

Keyed function locks are supplied keyed different unless otherwise specified.

- Keyed alike, 0 bitted, 1 bitted
- Master keyed (must specify quantity of Master keys where applicable)
- Construction master keyed
- Keyed to specific or existing number
- Submit master keying form (page 86)
- Extra cut keys (3908 - Cut 7-pin)
- Key markings: 1AA, 2AA etc. (per key)
- Key markings other than key set (per key)
- Cylinder markings (visual or concealed) - limited to 6 characters
- Do not duplicate standard
- Bitting lists are available, ordered separately from Master keyed order, specify 3998

Notes:

- Keys are cut bow to tip
- Must purchase capping block/press and key punch due to 140 pin spacing

ALL - SECTION KEY



MULTI - SECTION KEYS



Hager Keyway (Conventional Cylinders)



Hager H1



Hager H2



Hager H3

Cylinders



Rim Cylinders



3901

Rim Cylinder

- 140 Pin spacing
- Conventional cylinder supplied 7-pin only
- Furnished with trim ring, mounting plate, and break off screws
- Long tail piece standard
- Supplied with two operating keys

Mortise Cylinders



3902

Mortise Cylinder

- 140 Pin spacing
- Conventional cylinder supplied 7-pin only
- 3975 standard cam attached and 3972 Adams Rite cam shipped loose in the box
- Thread size is 1.150" x 32 UNS
- Cylinder face diameter is 1.360"
- Supplied with two operating keys
- 1-1/8" (29 mm) standard length, 1-1/4" (31 mm) available, 1-5/8" (41 mm) for mortise exit devices
- **Must specify length, cam, keyway, and keying requirements**

Keys



3907

Key Blank

Hager keyways (H1, H2, H3, H12, H23, H123)



3908

Cut Key

- Hager keyways (H1, H2, H3, H12, H23, H123)
- Specify keying required (masterkey, construction masterkey, control key)