

Optional Components



330D

Pocket Door Latch

Certification: Meets ANSI A156.14 for D0821.1
 Size: 2-3/4" x 2-1/2"
 (70 mm x 64 mm)
 Finger Piece: 1-3/8" (35 mm)
 extension
 Materials: Brass
 Finishes: US3, US5, US10B,
 US15, US15A, US19,
 US26, US26D
 Fasteners: Two (2) #6 x 5/8"
 OPHWS; (2) #6 x 3/4"
 FPHWS
 Notes: For use with 1-3/8" to
 1-3/4" (35 mm to
 45 mm) door



1741

Full Mortise, Five Knuckle, Plain Bearing Hinge

- Steel with steel pin (ANSI A5134)
- Reversible
- Square corners
- Removable pin
- 3.5" x 3.5"
- US2D



2610

Flush Cup Finger Pull

Overall Diameter: 31/32" (25 mm)
 Finger Pull Diameter: 3/4" (19 mm)
 Depth: 5/16" (8 mm)
 Projection: 1/32" (.8 mm)
 Materials: Solid brass
 Finishes: US3, US4, US5,
 US10A, US15,
 US15A, US26,
 US26D, ABA

Notes:

Built-in prong design eliminates the need for screws or brads



330L

Pocket Door Privacy Latch

Size: 2-3/4" x 2-1/2"
 (70 mm x 64 mm)
 Finger Piece: 1-3/8" (35 mm)
 extension
 Strike Size: 1" x 2-1/4" (25 mm x
 57 mm)
 Materials: Brass
 Finishes: US3, US5, US10B,
 US15, US15A, US19,
 US26, US26D
 Fasteners: Two (2) #6 x 5/8"
 OPHWS; (2) #6 x 3/4"
 FPHWS
 Notes: For use with 1-3/8" door



2630

Flush Cup Pull

Overall Diameter: 2-7/16" (62 mm)
 Finger Pull: 2-1/16" (52 mm)
 diameter
 Depth: 11/32" (9 mm)
 Projection: 3/32" (2 mm)
 Materials: Solid brass
 Finishes: US3, US4, US5, US10A,
 US15, US15A, US26,
 US26D, ABA

Notes:

Built-in prong design eliminates the need for screws or brads.



330M

Pocket Door Privacy Latch

Certifications: Meets ANSI A156.14 for D0831
 Size: 2-3/4" x 2-1/2"
 (70 mm x 64 mm)
 Finger Piece: 1-3/8" (35 mm)
 extension
 Strike Size: 1" x 2-1/4" (25 mm x
 57 mm)
 Materials: Brass
 Finishes: US3, US5, US10B,
 US15, US15A, US19,
 US26, US26D
 Fasteners: Two (2) #6 x 5/8"
 OPHWS; (2) #6 x 3/4"
 FPHWS
 Notes: For use with 1-3/4" door



9111

Fixed Bottom Door Guide

Materials: Zinc plated steel with
 bronze roller
 Guide: 2" x 3/4" x 3/32"
 (51 mm x 19 mm x 2.4 mm)
 Roller: 1-7/32" x 1/2"
 (14 mm x 13 mm)
 Notes:

- Door mortising is not required
- Use with 9122 guide channel





OPTIONAL COMPONENTS



9113

Stop

Materials: Zinc plated steel and rubber
 Stop: 1-5/8" x 1-1/2" x 5/8" x
 1-3/4" (41 mm x 38 mm x
 16 mm x 45 mm)

Notes: Use with 9105 hanger



9169

Top Pivot Assembly

Materials: Zinc plated steel
 Top Pivot: 1" x 3-1/2" x 1-7/16"
 (25 mm x 89 mm x 37 mm)

Notes: Inserts into 9155 top pivot
 clamp assembly



9114

Bottom Guide Rail

Materials: Aluminum
 Guide: 7/8" x 1/2" (22 mm x 13 mm)
 Lengths: 72" (1829 mm)
 96" (2438 mm)
 144" (3658 mm)

Notes:

- Door bottom prep requires 1/4" (6 mm) wide kerf and 9/16" (14 mm) depth
- Pre-punched for use with flat head screws



9200* | 9201**

Single Wheel Hanger

Materials: Zinc plated steel with
 molded Celcon wheels
 Gauge: 0.075" (2 mm)
 Wheel: 7/8" (22 mm) diameter

Notes:

- For use on doors weighing up to 60 lbs (27 kg)
- For use with 9810, 9820, and 9840 track
- Side mounted with slot adjust offset
- Hanger is stamped "A" or "B" for easy identification

 * 9200 is A offset of 3/8" (9.5 mm)
 ** 9201 is B offset of 11/16" (17.5 mm)



9121

Adjustable Bottom Door Guide

Materials: Zinc plated steel with bronze roller
 Guide: 1" x 3-1/2" x 3/16"
 (25 mm x 89 mm x 5 mm)

Post: 2-1/2" x 5/16" (64 mm x 8 mm)
 Notes: Use with 9122 guide channel



9202* | 9203**

Two Wheel Hanger

Materials: Zinc plated steel with
 molded Celcon wheels
 Gauge: 0.075" (2 mm)
 Wheel: 7/8" (22 mm) diameter

Notes:

- For use on doors weighing up to 75 lbs (34 kg)
- For use with 9810, 9820, and 9840 track
- Side mounted with slot adjust offset
- Hanger is stamped "A" or "B" for easy identification

 * 9202 is B offset of 11/16" (17.5 mm)
 ** 9203 is A offset of 3/8" (9.5 mm)



9122

Bottom Guide Channel

Materials: Extruded aluminum
 Gauge: 0.093 (2.4 mm)
 Lengths: 48" (1219 mm) to 192"
 (4877 mm)
 Channel: 5/8" x 3/4"
 (16 mm x 19 mm)

Notes:

- Screws not provided
- Mortised into floor or surface mounted



9220

Bi-Fold Door Hinge

Materials: Steel with bright zinc finish
 Hinge: 3" x 1" (76 mm x 25 mm)
 hole

Hole Locations: 1/2" (13 mm) from the
 center lines of holes to
 center of barrel

Notes: Non-mortise and easy
 to install





OPTIONAL COMPONENTS



9262

Pocket Door Keyed Lock

Materials: Steel

Notes:

- For doors 1-3/8" (35 mm) to 1-3/4" (44 mm) thick
- Lock cylinder fits in one 1" (25 mm) hole
- Available keyed alike



9264

Keyed Lock

Materials: Steel

Notes:

- Lock cylinder fits 1" (25 mm) hole
- Available keyed alike



9351

Guide

Materials: High density polyethylene

Guide: 4-9/16" x 1" x 11-3/16" (116 mm x 25 mm x 46 mm)

Notes:

- One piece fixed guide for 1-3/8" (35 mm) doors



9353

Adjustable Door Guide

Materials: High density polyethylene

Notes: Adjustable guide from 3/4" (19 mm) to 1-3/8" (35 mm)



9354

3/4" (19 mm) Riser

Materials: Steel with bright zinc finish

Rise: 3/4" (19 mm)

Notes:

- For mounting 9351 and 9353 floor guides over carpeting



9558

Wood Knob

Diameter: 1-1/2" (38 mm)

Materials: Solid wood

Notes:

- Will accept paint or stain



9559

Aligner

Materials: Steel with brass-tone dichromate finish

Notes:

- Keeps lead doors aligned when closed
- Use one on each lead door



9572

4-Wheel Hanger and Door Bracket

For 100 lbs (45 kg) doors

Materials: Steel with bright zinc

Wheel: 7/8" (22 mm) diameter

Notes:

- Wheels are self aligning to allow consistent contact with track
- Pre-lubricated Celcon wheels
- Includes wrench
- For use on doors weighing up to 100 lbs (45 kg) per door
- For use with 9601, 9602, and 9603 track



9575

Parts Bag

Includes four (4) 9572 hangers with quick release top mount plate, one (1) 9909 guide

Note: Up to 125 lbs (57 kg) per door



9605

4-Wheel Hanger with Top Mount Plate

Materials: Steel with brass-tone dichromate finish

Wheels: 7/8" (22 mm) diameter

Notes:

- Self aligning to allow consistent contact with track
- Pre-lubricated Celcon wheels mounted on steel ball bearing shafts
- Can be used on pivot set
- Up to 125 lbs (57 kg) per door
- Use in conjunction with 9601, 9602, or 9603 track



9606

4-Wheel Ball Bearing Hanger with Top Mount Plate

Materials: Steel with brass-tone dichromate finish

Wheels: 7/8" (22 mm) diameter

Notes:

- Self aligning to allow consistent contact with track
- Pre-lubricated Celcon wheels mounted on steel ball bearing shafts
- Up to 150 lbs (68 kg) per door
- Use with 9601, 9602, or 9603 track



OPTIONAL COMPONENTS



9610

Replacement Top Mount Plate

Materials: Bright zinc plated steel
 Gauge: 1/8" (3 mm)
 Size: 1-3/8" (35 mm) x 2-13/16" (72 mm)
 Notes:

- Replacement for four wheel hangers 9605, 9606, 9575, 9824, 9825 and 9827



9634

Pocket Door Adapter Kit

Materials: Galvanized steel and wood shims
 Clearance: 1/8" (3 mm) on each side of a 1-3/4" (44 mm) door
 Notes:

- Used with 1-3/4" (44 mm) doors by allowing additional clearance between door and jamb
- Includes wider floor plates and shims for spacing split studs for an additional 3/16" (4.8 mm) on each side of a 1-3/4" (44 mm) door



9639

Double Pocket Door Adapter Kit

Materials: Zinc plated steel and rubber bumper stops
 Notes:

- Joins two frames in the middle of the doorway
- For joining 9629, 9630, 9631 or 9850 pocket door kits
- Fits both KD and Built Up frames
- Lag bolt for attaching to rough header
- Bumpers included to stop doors in center of doorway



9680

Parts Bag

Includes four (4) 9606 ball bearing hangers and one (1) 9909 guide
 Note: Up to 150 lbs (68 kg) per door



9709

Aluminum Fascia

Materials: Extruded aluminum
 Gauge: 0.062" (1.6 mm)
 Lip: 5/8" (16 mm)
 Fascia: 2-3/4" (70 mm)
 Lengths: 48" (1219 mm) to 144" (3658 mm)
 Notes:

- **Grooved fascia for painting**
- Pre-punched holes for easy installation



9815

Bumper Stop

Materials: Zinc plated steel and rubber
 Notes:

- Fits all Hager track styles except 9101
- Screws onto track
- Included in bi-fold sets 9570 and 9890



9865

Flush Cup Pull

Overall Diameter: 1-31/32" (50 mm)
 Finger Pull Diameter: 1-19/32" (41 mm)
 Depth: 11/32" (9 mm)
 Projection: 5/64" (2 mm)
 Materials: Tan color ABS plastic
 Notes:

- Built-in prong design eliminates the need for screws or brads



9877

Door Guide

Materials: Plastic
 Notes:

- For doors 1-3/8" (35 mm) to 1-3/4" (44 mm) thick
- Two pieces required per door



9880

Door Stop

Materials: Zinc plated steel and rubber
 Gauge: 0.090" (2.3 mm)
 Stop: 1-1/4" x 1-1/4" x 7/8" (32 mm x 32 mm x 22 mm)
 Notes:

- For doors up to 175 lbs (79 kg)
- Keeps rear door pull exposed
- Mounts on door
- Not included in sets





OPTIONAL COMPONENTS



9881 Bumper

Materials: Rubber
Stop: 1/2" diameter x 3/8" deep
(13 mm x 10 mm)
Notes: With screws



9883 Two Piece Pocket Door Guide

Materials: Polyethylene
Guide: 1-3/16" x 3/4" x 1-1/8"
(21 mm x 19 mm x 29 mm)
Notes: • Two pieces per door required
• Screws to jamb to guide door and prevent rubbing



9884 Pocket Door Edge Pull

Finger Pull Extends: 1-1/16" (27 mm)
Faceplate: 21/32" x 3-1/2"
(17 mm x 89 mm)
Materials: Die cast zinc
Finishes: US3
Fasteners: Two (2) #6 x 5/8" FPHWS
Notes: Ideal for narrow and standard door thicknesses.



9889 Non-Adjustable Floor Guide

Materials: Polyethylene
Guide: 2-3/8" x 2-1/2" x 7/8"
(60 mm x 64 mm x 22 mm)
Notes: For 1-3/8" (35 mm) doors



9909 Adjustable Guide

Materials: Steel with bright zinc
Posts: Molded Celcon/Nylon
Gauge: 0.060" (2 mm)
Guide: 4-7/8" x 1-5/8" x 1-3/16"
(124 mm x 41 mm x 30 mm)
Notes: For doors 3/4" to 1-3/4" (19 mm to 44 mm) thick with steel base, celcon, and nylon posts



9928 Reversible Side Mount Bracket

Materials: Steel with bright zinc
Posts: Molded Celcon/Nylon
Gauge: 0.060" (1.5 mm)
Guide: 4-7/8" x 1-5/8" x 1-3/16"
(124 mm x 41 mm x 30 mm)
Size: For 3/4" to 1-3/4" (19 mm to 44 mm) doors
Notes: • Mounts at ends of track and every foot



3835 Small Case Deadlock

Thumbturn: Meet ADA Requirements, "No pinch," No grasp."
Lock Case: Heavy wrought steel with zinc dichromate finish - 4-5/16" x 3-9/16" x 1" (110 mm x 90 mm x 25 mm)
Armor Front: 1-1/4" x 5-5/8" x 7/32" (32 mm x 143 mm x 5 mm)
Keys: Two operating keys supplied per lock
Cylinder: • Brass - keyed different - C keyway - Standard
• Other keying options, including keyed 6-pin, available from factory
• SFIC uncombined or combined, brass 6- or 7-pin sold separately
• Drilled 6-pin, keyed 5-pin - Standard
• Small Format Interchangeable Core housing available
• Schlage "L" cam - Standard
Door Thickness: • 1-3/8" - 2-1/2" (35 mm-64 mm) - steel door
• 1-3/4" - 2-1/2" (45 mm-64 mm)- wood door
• Must specify door thickness if greater than 1-3/4" (45 mm)
Backset: • 2-3/4" (70 mm) only
Deadbolt: • 1" (25 mm) throw - stainless steel
Strike: • 1 1/8" wide x 3 1/2" (29 mm x 89 mm) NO LIP
Finishes: US26D
Functions: 35-Cylinder x Thumbturn, 36-Single Cylinder, 37-Double Cylinder, 38-Thumbturn Only, 39-Thumbturn w/ Emergency Key