



ACCESSORIES



100

Set Screw Set

- 1/8" x 10-32 set screws (quantity 300)
- 3/16" x 10-32 set screws (quantity 300)
- 3/32" hex key
- Hand tap "T" wrench
- 10-32 tap
- #21 drill bit
- This set converts removable pin hinges to non-removable pin (set screw in barrel) hinges as required



263

Sleeve Bolt

- Aluminum
- 9/16" (14 mm) head sex nut with 1/4" - 20 internal thread
- Knurled shoulder prevents bolt from turning
- Drill a 3/8" (9.5 mm) hole and insert the sex bolt
- Available in US2C finish only (compatible with US26D, US28, or US32D)
- For use in securing push bars, exposed door closers and other fixtures to doors 1-3/4" (45 mm) thick or greater



265

Molly Jack Nut (8S JN)

- Aluminum
- For use with the Hager reinforcing pivot hinges (250 Series)
- Easily installed by drilling a 7/16" (11.1 mm) pilot hole and following the instructions provided with each product
- For use in properly anchoring various products to hollow metal frames 3/16" - 3/8" (4.8 mm - 9.5 mm) thick



305

Hinge Reinforcement Plate

- Steel
- For metal frames
- Four (4) holes

Hinge Size		Width		Total Length	
Inches	mm	Inches	mm	Inches	mm
4-1/2	114	1.5	38	10	254
Offset		Gauge of Metal		Tapped for Screw	
0.074		0.154		12-24	



417

Back Plate

- Steel
- For wood doors
- For full or half surface hinges

Length		Width		Gauge of Metal
Inches	mm	Inches	mm	
4-5/8	117	1-13/16	46	0.074
5	127	2-1/8	54	0.097
Number of Holes		Machine Screw Size		
3		1/4 x 20		
4		1/4 x 20		



ACCESSORIES

DECORATOR TIP KITS



1712
Ball Standard Weight

1713
Ball Heavy Weight



1716
Acorn Standard Weight

1717
Acorn Heavy Weight



1722
Steeple Standard Weight

1723
Steeple Heavy Weight



1728
Urn Standard Weight

1729
Urn Heavy Weight

- Standard weight hinge size - 3-1/2" (89 mm), 4" (102 mm), 4-1/2" (114 mm), 5" (127 mm), 6" (152 mm)
- Heavy weight hinge size - 4-1/2" (114 mm), 5" (127 mm), 6" (152 mm), 8" (203 mm)
- Solid brass with stainless steel pin
- Conversion tips and pins for architectural grade hinges

