



DOOR PROTECTION PLATES



Door Protection Plates

The metal door protection plates below meet ANSI A156.6 for J101 Metal Armor Plate, J102 Metal Kickplate, and J103 Metal Mop Plate. The plastic door protection plates below meet ANSI A156.6 for J105 Plastic Armor Plate, J106 Plastic Kickplate, and J107 Plastic Mop Plate. Options for all plates include countersunk holes, UL armor plate stamped, self-adhesive tape, spanner head screws, torx head screws, round corners, wrap around side and bottom return, and 0.125" (3.2 mm) material. All plates below are supplied standard with #6 x 5/8" truss head screws (unless specified otherwise). They are available in mop plate, kick plate, stretcher plate, and armor plate sizes.

Mop Plate:	Protects the bottom of the pull side of doors subject to cleaning and mopping procedures.
Kick Plate:	Protects the bottom of the push side of doors subject to scuffing from foot traffic.
Stretcher Plate:	Protects doors in specific areas where constant contact is made by stretchers, service carts, or other equipment.
Armor Plate:	Protects lower half of doors from abuse by carts, trucks, and rough usage.

NFPA 80 STANDARD 6.4.5.1/6.4.5.2 /6.4.5.3 Protection Plates

- Factory installed protection plates shall be installed in accordance with the listing of the door.
- Field installed protection plate shall be labeled and installed in accordance with their listing.
- Labeling is not required where the top of the protection plate is not more than 16" (406 mm) above the bottom of the door.

190S

Thickness: 0.050" (1.3 mm)
 U.S. Gauge: 18
 Materials: Aluminum, brass, bronze, stainless steel
 Finishes: US3, US4, US10, US10B, US28, US32, US32D
 Bevel: None
 Options: UL Listed for US32 and US32D*

193S

Thickness: 0.050" (1.3 mm)
 U.S. Gauge: 18
 Materials: Aluminum, brass, bronze, stainless steel
 Finishes: US3, US4, US10, US10B, US28, US32, US32D
 Bevel: 3 edges
 Options: UL Listed for US32 and US32D*

194S

Thickness: 0.050" (1.3 mm)
 U.S. Gauge: 18
 Materials: Aluminum, brass, bronze, stainless steel
 Finishes: US3, US4, US10, US10B, US28, US32, US32D
 Bevel: 4 edges
 Options: UL Listed for US32 and US32D*

198S

Thickness: 0.038" (0.8 mm)
 U.S. Gauge: 20
 Materials: Stainless steel
 Finishes: US32D
 Options: UL Listed*

199B

Thickness: 0.038" (0.8 mm)
 U.S. Gauge: 20
 Materials: Aluminum
 Finishes: Bright gold anodized
 Fasteners: #6 x 5/8" TPH Tapping Screws

204S

Thickness: 0.125" (3.2 mm)
 Materials: Clear plastic
 Bevel: 4 edges

214S

Thickness: 0.125" (3.2 mm)
 Materials: Plastic laminate
 Bevel: 4 edges
 Colors: Black, Brown, Grey
 Notes: Other colors are available and will be subject to minimum order quantities; priced on application

220S

Thickness: 0.062" (1.6 mm)
 U.S. Gauge: 16
 Materials: Aluminum, brass, bronze, stainless steel
 Finishes: US3, US4, US10, US10B, US28, US32, US32D, (diamond tread available in US26 only)
 Bevel: None

223S

Thickness: 0.062" (1.6 mm)
 U.S. Gauge: 16
 Materials: Aluminum, brass, bronze, stainless steel
 Finishes: US3, US4, US10, US10B, US28, US32, US32D
 Bevel: 3 edges

224S

Thickness: 0.062" (1.6 mm)
 U.S. Gauge: 16
 Materials: Aluminum, brass, bronze, stainless steel
 Finishes: US3, US4, US10, US10B, US28, US32, US32D
 Bevel: 4 edges

225S

Thickness: 0.060" (1.9 mm)
 Materials: Kydex®
 Colors: CBO - Calcutta Black, KGO - Beige, KHO - Chocolate
 Notes: Other colors are available and will be subject to minimum order quantities; priced on application
 Options: UL Listed*

*Must specify UL stamp. UL labeling not required when top of plate is less than 16" above the bottom of the door.
 Screw fasteners only.

