



FLOOR STOPS & HOLDERS



241F | BL241F

Dome Stop - Low

- Certification: Meets ANSI A156.16 for L02142
 Base Diameter: 1-11/16" (43 mm)
 Base Thickness: 1/8" (3.2 mm)
 Overall Height: 1" (25 mm)
 Materials: Cast brass with grey rubber bumper
 Finishes: US3, US4, US5, US9, US10, US10B, US15, US15A, US19, US26, US26D
 Fasteners: One (1) #14 x 1-1/2" FPHWS, one (1) 1/4-20 x 3/4" FPHMS, one (1) 1/4-20 lead anchor, and one (1) plastic anchor
- Notes:
- To be used independently or in conjunction with 246B
 - For use when no threshold is used (door not undercut)
 - For use with wood or concrete floors
 - BL241F is 241F case quantity 50



242F

Dome Stop - Universal

- Certification: Meets ANSI A156.16 for L02162
 Base Diameter: 1-11/16" (43 mm)
 Base Thickness: 7/32" (5.5 mm)
 Overall Height: 1-5/8" (41 mm)
 Materials: Brass with grey rubber bumper
 Finishes: US3, US4, US10B, US15, US26, US26D
 Fasteners: One (1) #14 x 1-1/2" FPHWS, one (1) 1/4-20 x 3/4" FPHMS, one (1) 1/4-20 lead anchor, and one (1) plastic anchor
- Notes:
- For use with wood or concrete floors



243F | BL243F

Dome Stop - High

- Certification: Meets ANSI A156.16 for L02162
 Base Diameter: 1-11/16" (43 mm)
 Base Thickness: 7/16" (11 mm)
 Overall Height: 1-9/32" (33 mm)
 Materials: Cast brass with grey rubber bumper
 Finishes: US3, US4, US5, US9, US10, US10B, US15, US15A, US19, US26, US26D
 Fasteners: One (1) #14 x 1-1/2" FPHWS, one (1) 1/4-20 x 1-1/4" FPHMS, one (1) 1/4-20 lead anchor, and one (1) plastic anchor
- Notes:
- For use with thresholds or undercut doors
 - For use with wood or concrete floors
 - BL243F is 243F case quantity 50



244F

Cast Floor Stop

- Certification: Meets ANSI A156.16 for L02141
 Base: 1-3/4" x 4" (45 mm x 102 mm)
 Base Thickness: 5/32" (4 mm)
 Overall Height: 1" (25 mm)
 Materials: Cast brass with grey rubber bumper
 Finishes: US3, US4, US10, US10B, US26, US26D
 Fasteners: Two (2) #14 x 1-1/2" FPHWS, two (2) 1/4-20 x 3/4" FPHMS, two (2) 1/4-20 lead anchor, and two (2) plastic anchor
- Notes:
- Heavy duty - for use in high traffic areas
 - For use when no thresholds are used (door not undercut)
 - For use with wood or concrete floors



FLOOR STOPS & HOLDERS



245F

Cast Floor Stop

Certification: Meets ANSI A156.16 for L02161
Base: 1-3/4" x 4" (45 mm x 102 mm)
Base Thickness: 1/2" (13 mm)
Overall Height: 1-5/16" (33 mm)
Materials: Cast brass with grey rubber bumper
Finishes: US3, US4, US10, US10B, US26, US26D
Fasteners: Two (2) #14 x 1-1/2" FPHWS, two (2) 1/4-20 x 1-1/4" FPHMS, two (2) 1/4-20 lead anchor, and two (2) plastic anchor
Notes:

- Heavy duty - for use in high traffic areas
- For use with thresholds and undercut doors
- For use on wood or concrete floors



246B

Dome Stop Riser Plate

Diameter: 1-3/4" (45 mm)
Thickness: 3/8" (10 mm)
Fasteners: One (1) 1/4-20 x 1" FPHMS
Materials: Cast brass
Finishes: US3, US4, US10, US10B, US15, US15A, US19, US26, US26D
Notes: For use with 241F on undercut doors, doors with thresholds, and carpeted flooring



248F

Modern Style Universal Stop

Base Diameter: 1-7/16" (37 mm)
Height: 1-1/2" (38 mm)
Materials: Brass with black rubber bumper
Finishes: US26D
Fasteners: One (1) #12 x 1-1/4" FPHWS, one (1) plastic anchor, one (1) 1/4-20 x 1" FPHMS, and one (1) 1/4-20 lead anchor



248G

Modern Style Universal Stop

Base Diameter: 1-7/16" (37 mm)
Height: 1-1/2" (38 mm)
Materials: Brass with grey rubber bumper
Finishes: US26D
Fasteners: One (1) #12 x 1-1/4" FPHWS with plastic anchor and one (1) 1/4-20 x 1" FPHMS with lead anchor



249F

L-Shaped Floor Stop

Base: 1" x 2-1/2" x 7/32" thick (25 mm x 64 mm x 6 mm)
Base Thickness: 1/4" (6 mm)
Overall Height: 2-5/8" (67 mm)
Stop face: Resilient black rubber
Materials: Steel
Fasteners: Two (2) #14 x 1-1/2" FPHWS and two (2) plastic anchors
Notes: 1-1/2" (38 mm) max door to floor clearance





FLOOR STOPS & HOLDERS



252F

Floor Stop

Certification:

Meets ANSI A156.16 for L02131

Base:

1-9/16" x 2-1/2" (40 mm x 64 mm)

Overall Height:

2-11/16" (68 mm)

Materials:

Cast brass with black rubber bumper

Finishes:

US3, US10, US10B, US15, US15A, US19, US26, US26D

Fasteners:

One (1) #14 x 1-1/2" FPHWS, one (1) 1/4-20 x 3/4" FPHMS, one (1) 5/16-18 lead anchor, one (1) 1/4-20 lead anchor, one (1) plastic anchor, one (1) 5/16-18 x 2-1/2" threaded stud, and one (1) 5/16-18 x 2-1/2" combo threaded stud

Notes:

- Heavy duty - for use in high traffic areas
- For use on wood or concrete floors
- 2" (51 mm) max door to floor clearance



257F

Floor Stop

Certification:

Meets ANSI A156.16 for L02131

Base:

1-9/16" x 2-15/32" (40 mm x 63 mm)

Overall Height:

2" (51 mm)

Materials:

Cast brass with black rubber bumper

Finishes:

US3, US10, US10B, US15, US15A, US19, US26, US26D

Fasteners:

One (1) #14 x 1-1/2" FPHWS, one (1) 1/4-20 x 3/4" FPHMS, one (1) 5/16-18 lead anchor, one (1) 1/4-20 lead anchors, one (1) plastic anchor, one (1) 5/16-18 x 2-1/2" threaded stud, and one (1) 5/16-18 x 2-1/2" combo threaded stud

Notes:

- 1-3/8" (35 mm) max door to floor clearance
- Heavy duty - for use in high traffic areas
- For use on wood or concrete floors



258F

Floor Stop and Holder

Certification:

Meets ANSI A156.16 for L01371

Base:

1-9/16" x 2-15/32" (40 mm x 63 mm)

Height:

3" (76 mm)

Keeper:

1" x 2" (25 mm x 51 mm)

Materials:

Cast brass with black rubber bumper

Finishes:

US3, US10, US10B, US15, US26, US26D

Fasteners:

Two (2) #10 x 1" FPHWS, one (1) 1/4-20 x 3/4" FPHMS, one (1) 5/16-18 lead anchor, one (1) 1/4-20 lead anchors, and one (1) 5/16-18 x 2-1/2" threaded stud

Notes:

- 1-3/8" (35 mm) max door to floor clearance
- Heavy duty - for use in high traffic areas
- For use on concrete floors
- Manual holder ideal for interior and exterior applications
- Unit functions as a stop, but can serve as a "Hold Open" when hook is manually engaged



FLOOR STOPS & HOLDERS



259F

Tri Base Floor Stop

- Certification: Meets ANSI A156.16 for L02121
Base: 2-1/2" wide x 1-9/16" deep (64 mm x 40 mm)
Overall Height: 1-11/16" (43 mm)
Material: Cast brass with grey rubber bumper
Finishes: US3, US4, US10, US10B, US26, US26D
Fasteners: Three (3) #10 x 1-1/4" FPHWS, three (3) plastic anchors, three (3) 10-32 x 3/4" FPHMS, and three (3) 10-32 lead anchor
Notes:
 - 1/2" (13 mm) max door to floor clearance
 - Heavy duty - for use in high traffic areas
 - For use on wood or concrete floors



259H

Tri Base Floor Stop - Tall

- Certification: Meets ANSI A156.16 for L02121
Base: 2-1/2" wide x 1-9/16" deep (64 mm x 40 mm)
Overall Height: 2-1/4" (57 mm)
Materials: Cast brass with grey rubber bumper
Finishes: US3, US4, US10, US10B, US26, US26D
Fasteners: Three (3) #10 x 1-1/4" FPHWS, three (3) plastic anchor, three (3) 10-32 x 3/4" FPHMS, and three (3) 10-32 lead anchors
Notes:
 - 1" (25 mm) max door to floor clearance
 - Heavy duty - for use in high traffic areas
 - For use on wood or concrete floors



267F

Cast Floor Stop

- Certification: Meets ANSI A156.16 for L02131
Base Diameter: 2-1/4" (57 mm)
Overall Height: 3-1/8" (80 mm)
Materials: Cast brass with black rubber bumper
Finishes: US3, US10, US10B, US15, US15A, US19, US26, US26D
Fasteners: One (1) #10 x 1" OPHWS, one (1) plastic anchor, one (1) 5/16-18 lead anchor, one (1) 5/16-18 x 2-1/2" threaded stud, and one (1) 5/16-18 x 2-1/2" combo threaded stud
Notes:
 - 2-3/8" (60 mm) max door to floor clearance
 - Heavy duty - for use in high traffic areas
 - For use on concrete floors



267S

Cast Floor Stop

- Certification: Meets ANSI A156.16 for L02121
Base Diameter: 2-1/4" (57 mm)
Overall Height: 3-1/8" (80 mm)
Materials: Cast brass with black rubber bumper
Finishes: US3, US10, US10B, US15, US15A, US19, US26, US26D
Fasteners: Three (3) #10 x 1" OPHWS and three (3) plastic anchors
Notes:
 - 2-3/8" (60 mm) max door to floor clearance
 - Heavy duty - for use in high traffic areas
 - For use on wood floors





FLOOR STOPS & HOLDERS



268F

Cast Floor Stop and Holder

- Certification: Meets ANSI A156.16 for L01371
 Base Diameter: 2-1/4" (57 mm)
 Height: 3-19/32" (91 mm)
 Keeper: 25/32" x 1-1/2" (20 mm x 38 mm)
 Materials: Cast brass with black rubber bumper
 Finishes: US3, US10, US10B, US15, US15A, US19, US26, US26D
 Fasteners: Three (3) #10 x 1" OPHWS, one (1) plastic anchor, one (1) 5/16-18 lead anchor, and one (1) 5/16-18 x 2-1/2" threaded stud
- Notes:
- 2-1/2" (64 mm) max door to floor clearance
 - Heavy duty - for use in high traffic areas
 - For use on concrete floors
 - Manual holder ideal for interior and exterior applications
 - Unit functions as a stop, but can serve as a "Hold Open" when hook is manually engaged



268S

Cast Floor Stop and Holder

- Certification: Meets ANSI A156.16 for L01361
 Base Diameter: 2-1/4" (57 mm)
 Height: 3-19/32" (91 mm)
 Keeper: 25/32" x 1-1/2" (20 mm x 38 mm)
 Materials: Cast brass with black rubber bumper
 Finishes: US3, US10, US10B, US15, US15A, US19, US26, US26D
 Fasteners: Five (5) #10 x 1" OPHWS and three (3) plastic anchors
- Notes:
- 2-1/2" (64 mm) max door to floor clearance
 - Heavy duty - for use in high traffic areas
 - For use on wood floors
 - Manual holder ideal for interior and exterior applications
 - Unit functions as a stop, but can serve as a "Hold Open" when hook is manually engaged



269F

Heavy Duty Floor Stop

- Certification: Exceeds the criteria set forth for a 300-pound impact test (Report #91-04-01646)
 Bumper Diameter: 2" (51 mm)
 Bumper Height: 1-1/2" (38 mm)
 Steel Bolt: 5/8 - 11 x 2-1/2" thread
 Materials: Black rubber (fire-resistant)
- Notes:
- Designed for high vandalism areas
 - Ideal for prisons where floor stops are required
 - Grouted in concrete to eliminate exposed screws



FLOOR STOPS & HOLDERS



269T

Heavy Duty Floor Stop

Certification:

Exceeds the criteria set forth for a 300-pound impact test
(Report #91-04-01646)

Bumper Diameter:

2" (51 mm)

Bumper Height:

3-1/2" (89 mm)

Steel Bolt:

5/8 - 11 x 2-1/2" thread

Materials:

Black rubber (fire-resistant)

Notes:

- Designed for high vandalism areas
- Ideal for prisons where floor stops are required
- Grouted in concrete to eliminate exposed screws



326F

Automatic Floor Stop and Holder

Certification:

Meets ANSI A156.16 for L01301

Holder Projection:

1-15/16" (49 mm)

Holder Base:

3-1/16" x 3-1/2" (78 mm x 89 mm)

Floor Strike:

2" x 4-3/32" (51 mm x 104 mm)

Strike Height:

1-1/4" (32 mm)

Max Door to Floor Clearance:

1/2" (13 mm) or less

Materials:

Cast brass

Finishes:

US3, US10, US10B, US26, US26D

Fasteners:

Three (3) #14 x 1-1/2" FPHWS, three (3) 1/4-20 x 3/4" FPHMS, three (3) 1/4-20 lead anchors, four (4) 12-24 x 1" TPHMS, and four (4) #12 x 1" TPHWS

Notes:

- For use on wood or metal doors and wood or concrete floors
- Ideal for heavy traffic situations that require frequent hold open
- Firm pull releases holding mechanism
- Holder has vertical adjustment once mounted on the door



327F

Automatic Floor Stop and Holder

Certification:

Meets ANSI A156.16 for L01301

Holder Projection:

1-15/16" (49 mm)

Holder Base:

3-1/16" x 3-1/2" (78 mm x 89 mm)

Floor Strike:

2-3/16" x 4-1/8" (56 mm x 105 mm)

Strike Height:

1-3/4" (44 mm)

Max Door to Floor Clearance:

9/16" to 1-1/16" (14 mm to 27 mm)

Materials:

Cast brass

Finishes:

US3, US10, US10B, US26, US26D

Fasteners:

Three (3) #14 x 1-1/2" FPHWS, three (3) 1/4-20 x 3/4" FPHMS, three (3) 1/4-20 lead anchors, four (4) 12-24 x 1" TPHMS, and four (4) #12 x 1" TPHWS

Notes:

- For use on wood or metal doors and wood or concrete floors
- Ideal for heavy traffic situations that require frequent hold open
- Firm pull releases holding mechanism
- Holder has vertical adjustment once mounted on the door





FLOOR STOPS & HOLDERS



328F

Automatic Floor Stop and Holder

Certification:	Meets ANSI A156.16 for L01301
Holder Projection:	1-15/16" (49 mm)
Holder Base:	3-1/16" x 3-1/2" (78 mm x 89 mm)
Floor Strike:	2-3/16" x 4-1/8" (56 mm x 105 mm)
Strike Height:	2-1/4" (57 mm)
Max Door to Floor Clearance:	1-1/8" to 1-9/16" (29 mm to 40 mm)
Materials:	Cast brass
Finishes:	US3, US10, US10B, US26, US26D
Fasteners:	Three (3) #14 x 1-1/2" FPHWS, three (3) 1/4-20 x 3/4" FPHMS, three (3) 1/4-20 lead anchors, four (4) 12-24 x 1" TPHMS, and four (4) #12 x 1" TPHWS

- Notes:
- For use on wood or metal doors and wood or concrete floors
 - Ideal for heavy traffic situations that require frequent hold open
 - Firm pull releases holding mechanism
 - Holder has vertical adjustment once mounted on the door



329F

Automatic Floor Stop and Holder

Certification:	Meets ANSI A156.16 for L01301
Holder Projection:	1-15/16" (49 mm)
Holder Base:	3-1/16" x 3-1/2" (78 mm x 89 mm)
Floor Strike:	2-3/16" x 4-1/8" (56 mm x 105 mm)
Strike Height:	2-3/4" (70 mm)
Max Door to Floor Clearance:	1-5/8" to 2-1/16" (41 mm to 52 mm)
Materials:	Cast brass
Finishes:	US3, US10, US10B, US26, US26D
Fasteners:	Three (3) #14 x 1-1/2" FPHWS, three (3) 1/4-20 x 3/4" FPHMS, three (3) 1/4-20 lead anchors, four (4) 12-24 x 1" TPHMS, and four (4) #12 x 1" TPHWS

- Notes:
- For use on wood or metal doors and wood or concrete floors
 - Ideal for heavy traffic situations that require frequent hold open
 - Firm pull releases holding mechanism
 - Holder has vertical adjustment once mounted on the door