



FLUSH CUP PULLS



15C

Heavy Duty Flush Cup Pull


Certification: Meets ANSI A156.6 for J403 Pulls
 Description: Cup welded to face plate
 Face: 3-1/2" x 5" (89 mm x 127 mm)
 Projection: 1/8" (3.2 mm)
 Opening: 1-3/4" x 3-1/16" (44 mm x 78 mm)
 Cup Clearance: 3/4" (19 mm)
 Materials: Stainless steel
 Finishes: US32D
 Fasteners: Four (4) #6 x 5/8" OPHWS



15N

Flush Cup Pull

Certification: Meets ANSI A156.6 for J403 Pulls
 Description: Cup attached to face plate with adhesive
 Face: 3-1/2" x 5" (89 mm x 127 mm)
 Projection: 1/8" (3.2 mm)
 Opening: 1-3/4" x 3-1/16" (44 mm x 78 mm)
 Cup Clearance: 3/4" (19 mm)
 Materials: Aluminum, brass, bronze, stainless steel
 Finishes: US3, US4, US10, US10B, US26, US26D, US28, US32D
 Fasteners: Four (4) #6 x 5/8" OPHWS



15P

Heavy Duty Security Flush Cup Pull

Certification: Meets ANSI A156.6 for J403 Pulls
 Description: Cup welded to face plate and welded studs for security torx thru-bolt mounting
 Face: 3-1/2" x 5" (89 mm x 127 mm)
 Projection: 1/8" (3.2 mm)
 Opening: 1-3/4" x 3-1/16" (44 mm x 78 mm)
 Cup Clearance: 3/4" (19 mm)
 Materials: Stainless steel
 Finishes: US32D
 Fasteners: Two (2) 6-32 x 1-1/2" FPHMS (Security Torx)
 Notes: For use on 1-3/4" (44 mm) doors



15S

Light Duty Flush Cup Pull

Certification: Meets ANSI A156.6 for J403 Pulls
 Description: Concealed mounting by screws within the recessed cup (similar to 16N or 17N)
 Face: 3-1/2" x 5" (89 mm x 127 mm)
 Projection: 1/8" (3.2 mm)
 Opening: 1-3/4" x 3-1/16" (44 mm x 78 mm)
 Cup Clearance: 3/4" (19 mm)
 Materials: Aluminum, brass, bronze, stainless steel
 Finishes: US3, US4, US10, US10B, US26, US26D, US28, US32D
 Fasteners: Two (2) #6 x 5/8" PPHWS
 Notes: Fasteners concealed in cup



FLUSH CUP PULLS



16N

Light Duty Flush Cup Pull

Certification: Meets ANSI A156.6 for J403 Pulls
 Face: 1-15/16" x 3" (49 mm x 76 mm)
 Projection: 1/16" (1.5 mm)
 Opening: 27/32" x 2-3/8" (22 mm x 60 mm)
 Cup Clearance: 5/8" (16 mm)
 Materials: Brass
 Finishes: US3, US4, US10, US10B, US26, US26D
 Fasteners: Two (2) #8 x 3/4" OPHWS
 Notes: Fasteners concealed in cup



16R

Finger Pull Plate

Certification: Meets ANSI A156.6 for combination J301 Pull Plate and J403 Pulls
 Face: 4" x 16" (102 mm x 406 mm)
 Projection: .050" (1.3 mm)
 Opening: 1-3/4" x 3-1/16" (44 x 78 mm)
 Cup Clearance: 13/16" (21 mm)
 Materials: Aluminum, brass, bronze, stainless steel
 Finishes: US3, US4, US10, US10B, US26, US26D, US28, US32, US32D
 Fasteners: Ten (10) #6 x 5/8" OPHWS



17N

Light Duty Flush Cup Pull

Certification: Meets ANSI A156.6 for J403 Pulls
 Face: 2-1/2" x 3-31/32" (64 mm x 101 mm)
 Projection: 3/32" (2.4 mm)
 Opening: 1-11/32" x 3-13/32" (34 mm x 87 mm)
 Cup Clearance: 5/8" (16 mm)
 Materials: Brass
 Finishes: US3, US4, US10, US10B, US26, US26D
 Fasteners: Two (2) #8 x 13/16" OPHWS
 Notes: Fasteners concealed in cup



25B

Security Flush Pull Set

Certification: Meets ANSI A156.6 for J403 Pulls
 Face: 3-1/2" x 5" (89 mm x 127 mm)
 Opening: 1-3/4" x 3-1/16" (45 mm x 78 mm)
 Projection: 3/16" (5 mm)
 Cup Clearance: 3/4" (19 mm)
 Door Thickness: 1-3/4" (45 mm) - Standard
 Materials: Stainless steel
 Finishes: US32D
 Fasteners: Two (2) 6-32 x 1-1/2" FPHMS (Security Torx)
 Notes: Security pull thru-bolted to a 15P pull



FLUSH CUP PULLS



25C

Heavy Duty Flush Pull Set

Certification: Meets ANSI A156.6 for J403 Pulls
 Face: 3-1/2" x 5" (89 mm x 127 mm)
 Opening: 1-3/4" x 3-1/16" (45 mm x 78 mm)
 Projection: 1/8" (3 mm)
 Cup Clearance: 3/4" (19 mm)
 Door Thickness: 1-3/4" (45 mm) - Standard
 Materials: Stainless steel
 Finishes: US32D
 Fasteners: Two (2) 6-32 OPHMS sex nuts and bolts
 Notes: Consists of two (2) 15C pulls mounted back to back



25N

Flush Pull Set

Certification: Meets ANSI A156.6 for J403 Pulls
 Face: 3-1/2" x 5" (89 mm x 127 mm)
 Opening: 1-3/4" x 3-1/16" (45 mm x 78 mm)
 Projection: 1/8" (3 mm)
 Cup clearance: 3/4" (19 mm)
 Door Thickness: 1-3/4" (45 mm) - Standard
 Materials: Aluminum, brass, bronze, stainless steel
 Finishes: US3, US4, US10, US10B, US26, US26D, US28, US32D
 Fasteners: Two (2) 6-32 OPHMS sex nuts and bolts
 Notes: Consists of two (2) 15N pulls mounted back to back



25P

Security Finger Push/Pull Plate Set

Certification: Meets ANSI A156.6 for combination J301 Push Plate and J403 Flush Pull
 Face: 4" x 16" (102 mm x 406 mm)
 Projection: 1/8" (3.2 mm)
 Opening: 1-3/4" x 3-1/16" (44 mm x 78 mm)
 Cup Clearance: 13/16" (21 mm)
 Materials: Stainless steel
 Finishes: US32D
 Fasteners: Six (6) 8-32 x 3/4" FPHMS (Security Torx) with sex nuts and bolts
 Notes: Consists of a 15 pull cup welded to a 100T push plate (Mounted in back to back fashion)



26N

Security Finger Pull

Certification: Meets ANSI A156.6 for J403 Pulls
 Face: 4" x 5" (102 mm x 127 mm)
 Projection: 1/8" (3.2 mm)
 Opening: 1-5/8" x 3" (41 mm x 76 mm)
 Cup Clearance: 13/16" (21 mm)
 Materials: Brass, stainless steel
 Finishes: US4, US26D, US32D
 Fasteners: Four (4) 1/4-20 x 3/4" Undercut FPHMS (Security Torx)
 Notes: Cup welded to face



FLUSH CUP PULLS



27N

Security Flush Cup Pull

Certification: Meets ANSI A156.6 for J403 Pulls
 Face: 5" x 5" (127 mm x 127 mm)
 Projection: 3/8" (9.5 mm)
 Opening: 3" x 3-1/2" (76 mm x 89 mm)
 Cup Clearance: 7/8" (22 mm)
 Materials: Stainless steel
 Finishes: US32D
 Fasteners: Four (4) 10-24 FPHMS (Security Torx) sex nuts and bolts (compatible with 1-3/4" doors only)
 Notes:

- ADA Compliant
- Not available for back to back mounting



27P

Security Flush Cup Pull

Certification: Meets ANSI A156.6 for J403 Pulls
 Face: 5" x 5" (127 mm x 127 mm)
 Projection: 3/8" (9.5 mm)
 Opening: 3" x 3-1/2" (76 mm x 89 mm)
 Cup Clearance: 7/8" (22 mm)
 Materials: Stainless steel
 Finishes: US32D
 Fasteners: Four (4) 1/4-20 x 3/4" Undercut FPHMS (Security Torx)
 Notes:

- ADA Compliant
- Not available for back to back mounting