



KICK DOWN DOOR STOPS



270C

Kick Down Door Holder

Certification: Meets ANSI A156.16 for L71382
Base: 1-7/16" x 2-1/8" (37 mm x 54 mm)
Arm: 3-13/16" (97 mm)
Materials: Cast iron with rubber tip
Finishes: S1 - Sprayed Aluminum, S2 - Sprayed Brass, S3 - Sprayed Bronze
Fasteners: Four (4) #6 x 3/4" OPH tapping screws
Notes:

- Provides simple hold and release with a touch of the foot
- 2-1/4" (57 mm) max door to floor clearance



270D

Kick Down Door Holder

Certification: Meets ANSI A156.16 for L01381
Base: 1-19/32" x 1-25/32" (41 mm x 45 mm)
Arm: 3-1/2" (89 mm)
Materials: Cast brass with rubber tip
Finishes: US3, US10, US10B, US15, US15A, US19, US26, US26D
Fasteners: Three (3) #6 x 3/4" OPHWS
Notes:

- Provides simple hold and release with a touch of the foot
- 2-1/4" (57 mm) max door to floor clearance



270R

Replacement Rubber Tip

Materials: Rubber
Notes:

- For use with 270D and 271D
- Sold in packs of 10



270CR

Replacement Rubber Tip

Materials: Rubber
Notes:

- For use with 270C
- Sold in packs of 6



271D

Kick Down Door Holder

Certification: Meets ANSI A156.16 for L01381
Base: 1-19/32" x 1-25/32" (41 mm x 45 mm)
Arm: 4-7/16" (87 mm)
Materials: Cast brass with rubber tip
Finishes: US3, US10, US10B, US26, US26D
Fasteners: Three (3) #6 x 3/4" OPHWS
Notes:

- Provides simple hold and release with a touch of the foot
- 3-1/4" (83 mm) max door to floor clearance

