



## PUSH BARS



### 125S

#### Bent Push Bar

Certification: Meets ANSI A156.6 for J501 Push Bar  
Bar Size: 3/8" x 1-1/4" (10 mm x 32 mm)  
Projection: 2-1/8" (54 mm)  
Base Plate: 1" x 3" (25 mm x 76 mm)  
Materials: Aluminum, brass, bronze, stainless steel  
Finishes: US3, US4, US10, US10B, US28, US32, US32D  
Fasteners: Two (2) #8 x 3/4" FPH tapping screws and one (1) 1/4 - 20 OPHMS  
Options: May be ordered with thru bolts in place of surface screws



### 126S

#### Push Bar

Certification: Meets ANSI A156.6 for J501 Push Bar  
Bar Size: 3/8" x 1-1/4" (10 mm x 32 mm)  
Projection: 2-1/8" (54 mm)  
Base Plate: 1" x 3" (25 mm x 76 mm)  
Materials: Aluminum, brass, bronze, stainless steel  
Finishes: US3, US4, US10, US10B, US28, US32, US32D  
Fasteners: Four (4) #8 x 3/4" FPH tapping screws  
Options: May be ordered with thru bolts in place of surface screws



### 127S

#### Push Bar

Certification: Meets ANSI A156.6 for J501 Push Bar  
Bar Size: 3/8" x 1-1/4" (10 mm x 32 mm)  
Projection: 3/4" (19 mm)  
Base Plate: 1-1/4" x 1-1/4" (32 mm x 32 mm)  
Materials: Aluminum, brass, bronze, stainless steel  
Finishes: US3, US4, US10, US10B, US28, US32, US32D  
Fasteners: Two (2) 1/4-20 FPHMS  
Options: May be ordered with thru bolts in place of surface screws



### 128P

#### Wide Push Bar

Certification: Meets ANSI A156.6 for J501 Push Bar  
Bar Size: 3/8" x 3" (10 mm x 76 mm)  
Projection: 2-1/8" (54 mm)  
Base Plate: 1-1/2" x 4-1/2" (38 mm x 114 mm)  
Materials: Aluminum, brass, bronze, stainless steel  
Finishes: US3, US4, US10, US10B, US26, US26D, US28, US32, US32D  
Fasteners: Eight (8) #8 x 3/4" FPH tapping screws





## PUSH BARS



### 128S

#### Wide Push Bar

Certification: Meets ANSI A156.6 for J501 Push Bar  
 Bar Size: 3/8" x 3" (10 mm x 76 mm)  
 Projection: 2" (51 mm)  
 Base Plate: 1-1/2" x 4-1/2" (38 mm x 114 mm)  
 Door Thickness: 1-3/4" (45 mm) - Standard  
 Materials: Aluminum, brass, bronze, stainless steel  
 Finishes: US3, US4, US10, US10B, US26, US26D, US28, US32, US32D  
 Fasteners: Two (2) 1/4 - 20 x 2-1/4" FPHMS with finish washers  
 Notes: 128S is same as 128P, but without base plates



### 129P

#### Wide Push Bar

Certification: Meets ANSI A156.6 for J501 Push Bar  
 Bar Size: 3/8" x 3" (10 mm x 76 mm)  
 Projection: 3/4" (19 mm)  
 Base Plate: 1" x 3" (25 mm x 76 mm)  
 Materials: Aluminum, brass, bronze, stainless steel  
 Finishes: US3, US4, US10, US10B, US28, US32, US32D  
 Fasteners: Two (2) 1/4-20 x 1-1/4" FPHMS  
 Options:
 

- May be ordered with thru bolts in place of surface screws
- #14 Flat head wood screws available on special order



### 130S

#### Round Push Bar

Certification: Meets ANSI A156.6 for J501 Push Bar  
 Bar Stock: 1" (25 mm)  
 Projection: 2-1/2" (64 mm)  
 Door Thickness: 1-3/4" (45 mm) - Standard  
 Materials: Aluminum, brass, bronze, stainless steel  
 Finishes: US3, US4, US10, US10B, US28, US32, US32D  
 Fasteners: Two (2) 1/4-20 x 20 x 2-1/4" FPHMS with finish washers  
 Options: May be ordered with Type 5 concealed mountings at extra charge



### 131S

#### Round Push Bar

Certification: Meets ANSI A156.6 for J501 Push Bar  
 Bar Stock: 1" (25 mm)  
 Projection: 2-5/8" (67 mm)  
 Base Diameter: 2" (51 mm)  
 Door Thickness: 1-3/4" (45 mm) - Standard  
 Materials: Aluminum, brass, bronze, stainless steel  
 Finishes: US3, US4, US10, US10B, US28, US32, US32D  
 Fasteners: Two (2) 1/4-20 x 2-1/4" FPHMS with finish washers  
 Options: May be ordered with Type 5 concealed mountings at extra charge



## PUSH BARS



### 133S

#### Round Push Bar

Certification: Meets ANSI A156.6 for J501 Push Bar  
Bar Stock: 3/4" (19 mm)  
Projection: 2-1/4" (57 mm)  
Door Thickness: 1-3/4" (45 mm) - Standard  
Materials: Aluminum, brass, bronze, stainless steel  
Finishes: US3, US4, US10, US10B, US28, US32, US32D  
Fasteners: Two (2) 1/4 - 20 x 2-1/4" FPHMS with finish washers



### 134S

#### Round Push Bar

Certification: Meets ANSI A156.6 for J501 Push Bar  
Bar Stock: 3/4" (19 mm)  
Projection: 2-3/8" (60 mm)  
Base Diameter: 1-1/4" (32 mm)  
Door Thickness: 1-3/4" (45 mm) - Standard  
Materials: Aluminum, brass, bronze, stainless steel  
Finishes: US3, US4, US10, US10B, US28, US32, US32D  
Fasteners: Two (2) 1/4 - 20 x 2-1/4" FPHMS with finish washers  
Options: May be ordered with Type 5 concealed mountings at extra charge



### 136S

#### Round Push Bar

Certification: Meets ANSI A156.6 for J501 Push Bar  
Bar Stock: 1-1/4" (32 mm)  
Projection: 3" (76 mm)  
Door Thickness: 1-3/4" (45 mm) - Standard  
Materials: Aluminum, brass, bronze, stainless steel  
Finishes: US3, US4, US10, US10B, US28, US32, US32D  
Fasteners: Two (2) 5/16 - 18 x 2-1/4" FPHMS with finish washers  
Options: May be ordered with Type 5 concealed mountings at extra charge



### 137S

#### Round Push Bar

Certification: Meets ANSI A156.6 for J501 Push Bar  
Bar Stock: 1-1/4" (32 mm)  
Projection: 3-1/8" (79 mm)  
Base Diameter: 2" (51 mm)  
Door Thickness: 1-3/4" (45 mm) - Standard  
Materials: Aluminum, brass, bronze, stainless steel  
Finishes: US3, US4, US10, US10B, US28, US32, US32D  
Fasteners: Two (2) 5/16 - 18 x 2-1/4" FPHMS with finish washers  
Options: May be ordered with Type 5 concealed mountings at extra charge

