


## NOTES:

1. 294D CONSISTS OF ONE 291S AND ONE 294S FOR TWO POINT LATCHING.
2. 294D HAS A 1-1/2 HR FIRE RATING FOR WOOD DOORS UP TO 4 FT. WIDE X 9 FT. TALL.
3. DIMENSIONS SHOWN ON THIS TEMPLATE ARE FOR TOP FLUSH BOLTS. FOR BOTTOM FLUSH BOLTS INVERT & MEASURE FROM BOTTOM EDGE OF DOOR
4. WHEN TWO POINT LATCHING IS REQUIRED, IT IS RECOMMENDED THAT ONE 294S CONSTANT LATCHING FLUSH BOLT BE USED WITH ONE 291S AUTOMATIC FLUSH BOLT, WITH THE 294S INSTALLED AT THE TOP OF THE DOOR.

# 294S/294D\* CONSTANT LATCHING FLUSHBOLT WOOD DOOR & FRAME PREP TEMPLATE

\* SEE NOTE 1



TEMPLATE NO: T294S DRAWING NO: T-TA00173 REV: 03 SHEET 1 OF 1

HAGER COMPANIES 139 Victor Street, St. Louis, MO 63104 - (800) 325-9995 - Fax (800) 782-0149

