



RESIDENTIAL



208

Kick Down Door Stop

Base: 1-5/8" x 1-7/8" (41 mm x 48 mm)
 Arm: 3-7/8" (98 mm)
 Materials: Aluminum alloy
 Finishes: US3, US4, US5, US10A, US15A, US15, US26, US26D, ABA
 Fasteners: Three (3) #6 x 3/4" FPHWS
 Notes:

- Poly bag (1 each) with screws
- Provides simple hold and release with a touch of the foot
- 3" (76 mm) max door to floor clearance



209

Floor Door Stop

Height: 1-1/4" (32 mm)
 Base Diameter: 1-3/32" (28 mm)
 Tip Diameter: 19/32" (15 mm)
 Materials: Zinc alloy
 Finishes: US3, US4, US5, US10A, US15A, US15, US26, US26D, ABA
 Fasteners: One (1) #8 x 2" FPHWS
 Notes:

- Non-marking white tip
- 3/8" (9.5 mm) max door to floor clearance



BL6209

Floor Door Stop

Height: 1-3/8" (35 mm)
 Base Diameter: 13/16" (21 mm)
 Tip Diameter: 1/2" (13 mm)
 Materials: Zinc alloy
 Finishes: US26D, ABA
 Fasteners: #8 x 11/32" thread
 Notes:

- Non-marking white tip
- 150 per case
- 1/2" (13 mm) max door to floor clearance
- Hex shape near the base allows usage of a wrench for easier installation



210

Rigid Door Stop

Projection: 3" (76 mm)
 Tip Diameter: 11/16" (17.5 mm)
 Base Diameter: 1" (25 mm)
 Materials: Zinc alloy
 Finishes: US3, US26, AN
 Fasteners: #8 x 5/8" thread
 Notes: Bumper made of rubber



HAGER
COMPANIES

RESIDENTIAL



211

Flexible Door Stop

Projection: 3-1/8" (79 mm)
Tip Diameter: 9/16" (14 mm)
Base Diameter: 1" (25 mm)
Materials: Steel
Finishes: US3, US4, US5, US10A, US10R, US15A, US15, US26, US26D, ABA
Fasteners: One (1) #8 x 3/4" PPHWS
Notes:

- Bumper made of rubber
- Flexible spring



BL6211

Flexible Door Stop

Projection: 3" (76 mm)
Tip Diameter: 7/16" (11 mm)
Base Diameter: 3/4" (19 mm)
Materials: Zinc alloy base
Finishes: US3, US4, US5, US10A, US10R, US15A, US15, US26, US26D, ABA
Fastener: #8 x 11/32" thread
Notes:

- Bumper made of rubber
- Flexible spring



212

Hinge Pin Door Bumper

Materials: Zinc alloy base
Finishes: US3, US4, US5, US10A, US10R, US15A, US15, US26, US26D, ABA
Notes:

- Non-marking white plastic tip
- For use where standard door stops are not desirable
- For use with narrow trim
- Adjustable from 80 degrees to 120 degrees
- For use with residential hinges
- Works with 1/4" (6 mm) hinge pins



BL6212

Hinge Pin Door Bumper

Materials: Zinc alloy base
Finishes: US3, US4, US5, US10A, US10R, US15A, US15, US26, US26D, ABA
Notes:

- Non-marking white plastic tip
- Works with 1/4" (6 mm) hinge pins
- For use where standard door stops are not desirable
- For use with narrow trim
- Adjustable from 80 degrees to 120 degrees
- For use with residential hinges



1412

Door Guard

Arm Length: 4 (102 mm)
Materials: Zinc alloy base
Finishes: U3, US4, US5, US10A, US15A, US15, US26, US26D, ABA
Fasteners: Seven (7) #6 x 3/4" FPHWS
Notes:

- Provides extra security from inside door
- Limits door opening when latch is thrown
- Poly bag (1 each) with screws





RESIDENTIAL



1413

Flush Bolt

Faceplate: 3/4" x 6" (19 mm x 181 mm)
 Strike: 7/8" x 1-3/4" (22 mm x 45 mm)
 Bolt Diameter: 1/2" (13 mm)
 Bolt Throw: 15/16" (24 mm)
 Bolt Backset: 7/16" (11 mm)
 Materials: Brass faceplate with steel components
 Finishes: US3, US4, 10A, 10R, US15, US26, US26D
 Fasteners: Four (4) #6 x 3/4" FPHWS
 Notes:

- Poly bag (1 each) with strikeplate and screws
- Square corners



1414

Flush Bolt

Faceplate: 3/4" x 6" (19 mm x 181 mm)
 Strike: 7/8" x 1-3/4" (22 mm x 45 mm)
 Bolt Diameter: 1/2" (12.7 mm)
 Bolt Throw: 15/16" (24 mm)
 Bolt Backset: 7/16" (11 mm)
 Materials: Brass faceplate with steel components
 Finishes: US3, US4, 10R, US15, US26D
 Fasteners: Four (4) #6 x 3/4" FPHWS
 Notes:

- Poly bag (1 each) with strikeplate and screws
- Rounded corners



1415

Strike Plate

Size: 7/8" x 1-3/4" (22 mm x 45 mm)
 Finishes: US3, US10A, US15A, US15, US26D
 Fasteners: Two (2) #6 x 3/4" FPHWS
 Notes:

- For use with 1413 and 1414 Flush Bolts
- Packed (1 each) with Poly bag and screws



1416

Single Route Flush Bolt

Faceplate: 3/4" x 7-1/8" (19 mm x 181 mm)
 Strike: 21/32" x 1-1/2" (17 mm x 38 mm)
 Bolt Diameter: 5/16" (8 mm)
 Bolt Throw: 7/8" (22 mm)
 Bolt Backset: 3/8" (9.5 mm)
 Materials: Brass faceplate with steel components
 Finishes: US3, US4, US5, US10A, US10R, US15A, US15, US26, US26D, ABA
 Fasteners: Two (2) #8 x 1-1/2" FPHWS and two (2) #6 x 3/4" FPHWS
 Notes:

- Poly bag (1 each) with strikeplate and screws
- Rounded corners
- Single route for quick and simple door prep



RESIDENTIAL



1418

Flush Bolt with Extension Rod

- Faceplate: 23/32" x 7-3/8" (18 mm x 187 mm)
Strike: 5/8" x 1-1/2" (16 mm x 38 mm)
Bolt Diameter: 5/16" (8 mm)
Bolt Throw: 3/4" (19 mm)
Bolt Backset: 3/8" (9.5 mm)
Extension Rod Length: 16" (406 mm)
Materials: Brass faceplate with steel components
Finishes: US3, US4, US5, US10A, US10R, US15A, US15, US26, US26D, ABA
Fasteners: Two (2) #8 x 1-1/2" FPHWS and two (2) #6 x 3/4" FPHWS
Notes:
 - Poly bag (1 each) with strikeplate and screws
 - Rounded corners
 - Single route for quick and simple door prep



1419

Flush Bolt with Extension Rod

- Faceplate: 3/4" x 7-1/8" (19 mm x 181 mm)
Strike: 5/8" x 1-1/2" (16 mm x 38 mm)
Bolt Diameter: 5/16" (8 mm)
Bolt throw: 3/4" (19 mm)
Bolt Backset: 5/16" (8 mm)
Materials: Brass faceplate with steel components
Fasteners: Two (2) #8 x 1-1/2" FPHWS and two (2) #6 x 3/4" FPHWS
Finishes: US3, US4, US10A, US10R, US15, US26, US26D, ABA, AN
Notes: Single route for quick and simple door prep



1439 | BL6439

Magnetic Catch - Light Weight

- Catch: 1-1/16" x 2" (27 mm x 51 mm)
Strike: 7/8" x 1" (22 mm x 25 mm)
Materials: Tan plastic case
Fasteners: Two (2) #6 x 1/2" TPHWS and one (1) #4 x 1/2" FPHWS
Notes:
 - Poly bag (1 each) with screws
 - Double-sided magnet, self-aligning, 6 lb. pull
 - Self aligning magnet insures maximum pull
 - BL6439 is Builder's Pack Poly bag (1 each) with screws



1445

Roller Latch

- Hole Diameter: 13/16" (21 mm)
Hole Depth: 1-1/8" (29 mm)
Materials: Zinc alloy base
Finishes: US3, US4, US5, US10A, US10R, US15A, US15, US26, US26D, ABA
Fasteners: Two (2) #4 x 3/4" FPHWS
Notes:
 - Poly bag (1 each) with screws
 - Designed for use on cabinets and lightweight doors
 - Not intended for heavy weight applications





RESIDENTIAL



1446

Light Weight Ball Catch

- Faceplate: 1" x 2-1/4" (25 mm x 57 mm)
 Strike: 1-3/8" x 2-1/4" (35 mm x 57 mm)
 Hole Diameter: 1" (25 mm)
 Hole Depth: 1-1/4" (32 mm)
 Materials: Steel housing, brass strike, plated steel ball
 Finishes: US3, US4, US5, US10A, US10R, US15A, US15, US26, US26D
 Fasteners: Four (4) #6 FPHWS
 Notes:
- Designed for use on cabinets and light weight doors
 - Not intended for heavy weight applications
 - Ball adjusts in and out for various door and frame clearances
 - Poly bag (1 each) with steel screws



1447

Light Weight Ball Catch

- Strike: 1-3/8" x 2-1/4" (35 mm x 57 mm)
 Faceplate: 1" (25 mm) diameter
 Hole Diameter: 15/16" (24 mm)
 Hole Depth: 1-1/4" (32 mm)
 Materials: Zinc housing, brass strike, plated steel ball
 Finishes: US3, US4, US5, US10A, US10R, US15A, US15, US26, US26D
 Fasteners: Two (2) #6 FPHWS
 Notes:
- Designed for use on cabinets and light weight doors
 - Not intended for heavy weight applications
 - Ball adjusts in and out for various door and frame clearances
 - Poly bag (1 each) with steel screws



1448

Strike Plate

- Size: 1-3/8" x 2-1/4" (35 mm x 57 mm)
 Material: Brass
 Finishes: US3, US4, US5, US10A, US10R, US15A, US15, US26, US26D, ABA
 Fasteners: Two (2) #6 FPHWS
 Notes: For use with 1446 and 1447 ball catches



1449

Drive In Ball Catch

- Faceplate: 1" (25 mm) diameter
 Hole Diameter: 15/16" (24 mm)
 Hole Depth: 1-1/4" (32 mm)
 Materials: Zinc housing, plated steel ball
 Finishes: US4
 Packaging: 100 per box
 Notes:
- Ball catch designed for use on cabinets and light weight doors
 - Not intended for heavyweight applications
 - Ball adjusts in and out for various door and frame clearances



RESIDENTIAL



BL6793

Pole Sockets

Outside Diameter:

2-7/16" (62 mm)

Materials:

Steel

Notes:

- For poles up to 1-3/8" (35 mm) diameter
- Flange design prevents accidental knock out of pole
- Poly bag (2 each) with screws



BL6794

Pole Sockets

Outside Diameter:

2-3/16" (56 mm)

Materials:

Plastic

Notes:

- For poles up to 1-3/8" (35 mm) diameter
- Poly bag (2 each) with screws



1795

Closet Rod

Pole Diameter:

1" (25 mm)

Available Lengths:

18" - 30"

30" - 48"

48" - 72"

72" - 96"

96" - 150"

Materials:

Steel with bright zinc finish

Finishes:

White enamel

Fasteners:

Six (6) #8 x 1" TPH tapping screws

Notes:

- Quick mount end
- High strength lock seam tubing
- Poly bag (1 each) with screws



1797

Shelf Bracket with 2-1/2" Drop

Materials:

Steel ANSI B04051

Finishes:

White Enamel

Fasteners:

Two (2) #8 x 5/8" PPH tapping screws and two (2) #10 x 1-1/2" PPH tapping screws

Notes:

- For shelf and rod support
- Heavy gauge steel construction embossed for added strength
- Holds 1-3/8" (35 mm) diameter rod
- Supports 12" (305 mm) shelf
- Bulk with screws
- 150 lbs. load rating






RESIDENTIAL



1798

Shelf Bracket with 3" Drop

- Materials: Steel ANSI B04051
 Finishes: White Enamel
 Fasteners: Two (2) #8 x 5/8" PPH tapping screws and two (2) #10 x 1-1/2" PPH tapping screws
- Notes:
- For shelf and rod support
 - Heavy gauge steel construction embossed for added strength
 - Holds 1-3/8" (35 mm) diameter rod
 - Supports 12" (305 mm) shelf
 - Bulk with screws
 - 150 lbs. load rating



1799

Shelf Bracket - Adjustable

- Materials: Steel ANSI B04051
 Finishes: White Enamel
 Fasteners: Two (2) #8 x 3/4" PPH tapping screws and two (2) #10 x 1-1/2" PPH tapping screws
- Notes:
- Adjustable shelf and rod support
 - Heavy gauge steel construction embossed for added strength
 - Holds 1-3/8" (35 mm) diameter rod
 - Supports 12" (305 mm) shelf
 - 3/4" (19 mm) adjustability
 - Bulk with screws



1801

Shelf Bracket

- Materials: Steel ANSI B04051
 Finishes: White enamel
 Fasteners: Two (2) #8 x 5/8" PPH tapping screws and two (2) #10 x 1-1/2" PPH tapping screws
- Notes:
- Less rod support
 - Heavy gauge steel construction embossed for added strength
 - Supports 12" (305 mm) shelf
 - Bulk with screws



6601

Handrail Bracket

- Projection: 3-1/4" (82.5 mm)
 Base to Center of Rail: 2-3/4" (70 mm)
 Materials: Cast aluminum
 Finishes: US3, US4, US5, US10A, US10R, US15, US15A, US26, US26D, ABA
 Fasteners: Three (3) #8 x 1-1/2" OPHWS and two (2) #8 x 3/4" OPHWS
 Notes: Poly bag (1 each) with wood screws and rail bracket



BL6610

Coat and Hat Hook

- Upper Projection: 2-13/16" (71 mm)
 Lower Projection: 1-5/16" (33 mm)
 Material: Cast steel
 Finishes: US3, US4, US5, US10A, US15A, US15, US26, US26D, ABA
 Fasteners: Two (2) #6 x 3/4" FPHWS
 Notes:
- Poly bag (1 each) with screws
 - Builder's pack