



WALL STOPS & HOLDERS



230W

Convex Wall Stop

Certification: Meets ANSI A156.16 for L02101
Diameter: 2-15/32" (63 mm)
Projection: 1-3/32" (28 mm)
Materials: Cast brass, bronze with grey rubber bumper
Finishes: US3, US4, US10, US10B, US15, US15A, US19, US26, US26D
Fasteners: One (1) #10 x 1-1/2" PPHWS with plastic and toggle anchor.
Notes:

- Concealed tamper proof mounting
- Easy installation by inserting screwdriver through small hole in bumper
- Specify 230T for machine screw and toggle nut screwpack (10 pk)



232W | BL232W

Convex Wall Stop

Certification: Meets ANSI A156.16 for L02101
Diameter: 2-7/16" (62 mm)
Projection: 1" (25 mm)
Materials: Wrought brass, bronze, stainless steel with grey rubber bumper
Finishes: US3, US4, US5, US9, US10, US10B, US15, US15A, US19, US26, US26D, US32, US32D
Fasteners: One (1) #10 x 1-1/2" PPHWS with plastic and toggle anchor
Notes:

- Concealed tamper proof mounting
- Easy installation by inserting screwdriver through small hole in bumper
- Specify 230T for machine screw and toggle nut screwpack (10 pk)
- BL232W is 232W case quantity 50



234W

Concave Wall Stop

Certification: Meets ANSI A156.16 for L02251
Diameter: 2-15/32" (63 mm)
Projection: 1-3/32" (28 mm)
Materials: Cast brass, bronze with grey rubber bumper
Finishes: US3, US4, US10, US10B, US15, US15A, US19, US26, US26D
Fasteners: One (1) #10 x 1-1/2" PPHWS w/ plastic and toggle anchor
Notes:

- Easy installation by inserting screwdriver through small hole in rubber bumper
- Concealed tamper proof mounting
- Concave rubber bumper prevents damage to locksets with projecting buttons
- Specify 230T for machine screw and toggle nut screwpack (10 pk)



236W | BL236W

Concave Wall Stop

Certification: Meets ANSI A156.16 for L02251
Diameter: 2-7/16" (75 mm)
Projection: 1" (25 mm)
Materials: Wrought brass, bronze, stainless steel with grey rubber bumper
Finishes: US3, US4, US5, US9, US10, US10B, US15, US15A, US19, US26, US26D, US32, US32D
Fasteners: One (1) #10 x 1-1/2" PPHWS w/ plastic and toggle anchor
Notes:

- Easy installation by inserting screwdriver through small hole in rubber bumper
- Concealed tamper proof mounting
- Concave rubber bumper prevents damage to locksets with projecting buttons
- Specify 230T for machine screw and toggle nut screwpack (10 Pk)
- BL236W is 236W case quantity 50



WALL STOPS & HOLDERS



250W

Convex Wall Stop

Diameter: 1" (25 mm)
Projection: 9/16" (14 mm)
Materials: Cast brass
Finishes: US3, US4, US10, US10B, US15, US15A, US19, US26, US26D
Fasteners: One (1) #6 x 3/4" screw with plastic anchor and one (1) 0.052 diameter nail
Notes:

- Concealed mounting screw prevents vandalism
- For use on drywall
- Compact design



251W

Concave Wall Stop

Diameter: 1-7/8" (48 mm)
Projection: 25/32" (20 mm)
Materials: Adhesive backed rubber bumper
Finish: Grey only
Notes:

- Concave bumper prevents damage to locksets with projecting buttons
- For areas where concealed mounting is not required
- Adhesive backing for use on clean smooth flat surfaces only



254S

Wall Stop & Holder

Certification: Meets ANSI A156.16 for L01341
Base Diameter: 2-11/32" (60 mm)
Base Projection: 3-1/2" (89 mm)
Engaged Projection: 5-19/32" (142 mm)
Keeper: 1" x 2" (25 mm x 51 mm)
Materials: Cast brass with black rubber bumper
Finishes: US3, US4, US10, US10B, US15, US26, US26D
Fasteners: Five (5) #10 x 1" FPHWS, and three (3) plastic anchors
Notes:

- For use on drywall
- Manual holder ideal for interior and exterior applications
- Unit functions as a stop, but can serve as a "Hold Open" when hook is manually engaged
- Ideal for use with locksets with a projection of 3-5/16" (84 mm) or less



254W

Wall Stop & Holder

Certification: Meets ANSI A156.16 for L01351
Base Diameter: 2-11/32" (60 mm)
Base Projection: 3-1/2" (89 mm)
Engaged Projection: 5-19/32" (142 mm)
Keeper: 1" x 2" (25 mm x 51 mm)
Materials: Cast brass with black rubber bumper
Finishes: US3, US4, US10, US10B, US15, US26, US26D
Fasteners: Three (3) #10 x 1" FPH tapping screw, one (1) plastic anchor, one (1) 5/16-18 x 2-1/2" threaded stud, and one (1) 5/16-18 lead anchor
Notes:

- For use on concrete walls
- Manual holder ideal for interior and exterior applications
- Unit functions as a stop, but can serve as a "Hold Open" when hook is manually engaged
- Ideal for use with locksets with a projection of 3-5/16" (84 mm) or less





WALL STOPS & HOLDERS



255S

Wall Stop

Certification: Meets ANSI A156.16 for L02011
Base Diameter: 2-11/32" (60 mm)
Projection: 3-11/16" (94 mm)
Materials: Cast brass with black rubber bumper
Finishes: US3, US4, US10, US10B, US15, US26, US26D
Fasteners: Three (3) #10 x 1" OPHWS and three (3) plastic anchors
Notes:

- For use on drywall
- Ideal for interior and exterior applications
- Heavy duty - for use in high traffic areas
- Ideal for use with locksets with a projection of 3" (76 mm) or less



255W

Wall Stop

Certification: Meets ANSI A156.16 for L02021
Base Diameter: 2-11/32" (60 mm)
Projection: 3-11/16" (94 mm)
Materials: Cast brass with black rubber bumper
Finishes: US3, US4, US10, US10B, US15, US26, US26D
Fasteners: One (1) #10 x 1" OPHWS, one (1) plastic anchor, one (1) 5/16-18 lead anchor, one (1) 5/16-18 x 2-1/2" threaded stud, one (1) 5/16-18 x 2-1/2" combo threaded stud
Notes:

- For use on concrete walls
- Ideal for interior and exterior applications
- Heavy duty - for use in high traffic areas
- Ideal for use with locksets with a projection of 3" (76 mm) or less



256S

Manual Wall Stop & Holder

Certification: Meets ANSI A156.16 for L01341
Base Diameter: 2-1/4" (57 mm)
Base Projection: 3-3/4" (95 mm)
Engaged Projection: 5-11/16" (145 mm)
Keeper: 25/32" x 1-1/2" (20 mm x 38 mm)
Materials: Cast brass with black rubber bumper
Finishes: US3, US10, US10B, US15, US26, US26D
Fasteners: Three (3) #10 x 1" OPHWS and three (3) plastic anchors
Notes:

- For use on drywall
- Ideal for interior and exterior applications
- Heavy duty - for use in high traffic areas
- Unit functions as a stop, but can serve as a "Hold Open" when hook is manually engaged
- Ideal for use with locksets with a projection of 3" (76 mm) or less



WALL STOPS & HOLDERS



256W

Manual Wall Stop & Holder

Certification: Meets ANSI A156.16 for L01351
Base Diameter: 2-1/4" (57 mm)
Base Projection: 3-3/4" (95 mm)
Engaged Projection: 5-11/16" (145 mm)
Keeper: 25/32" x 1-1/2" (20 mm x 38 mm)
Materials: Cast brass with black rubber bumper
Finishes: US3, US10, US10B, US15, US26, US26D
Fasteners: One (1) #10 x 1" OPHWS, one (1) plastic anchor, one (1) 5/16-18 lead anchor, one (1) 5/16-18 x 2-1/2" threaded stud, and one (1) 5/16-18 x 2-1/2" combo threaded stud

- Notes:
- For use on concrete walls
 - Ideal for interior and exterior applications
 - Heavy duty - for use in high traffic areas
 - Unit functions as a stop, but can serve as a "Hold Open" when hook is manually engaged
 - Ideal for use with locksets with a projection of 3" (76 mm) or less



260W

Angled Wall Stop

Certification: Meets ANSI A156.16 for L02201
Base: 2-3/16" x 2-15/16" (56 mm x 75 mm)
Projection: 3-21/32" (93 mm)
Materials: Cast brass with black rubber bumper
Finishes: US26D
Fasteners: Three (3) #14 x 1-1/2" FPHWS, three (3) 1/4-20 x 3/4" FPHMS, three (3) plastic anchors, and three (3) 1/4-20 lead anchors

- Notes:
- For use with drywall or concrete walls
 - Sloping design resists vandalism
 - Ideal for use with locksets with a projection of 3" (76 mm) or less



324W

Light Duty Wall Bumper

Certification: Meets ANSI A156.16 for L02031
Base Diameter: 1-1/4" (32 mm)
Projection: 3-1/4" (83 mm)
Tip Diameter: 5/8" (16 mm)
Materials: Cast brass, bronze with white rubber tip
Finishes: US3, US4, US5, US10, US10B, US15, US15A, US19, US26, US26D
Fastener: #10 x 7/8" wood thread
Notes:

- Replaceable rubber tip available
- Hex shape near the tip allows usage of a wrench for easier installation





WALL STOPS & HOLDERS



326W

Automatic Wall Stop & Holder

Certification: Meets ANSI A156.16 for L01293
 Holder Base: 2-13/32" x 2-25/32" (61 mm x 71 mm)
 Holder Projection: 2-5/16" (59 mm)
 Engaged Projection: 3-5/8" (92 mm)
 Strike Base: 1" x 2-1/16" (25 mm x 52 mm)
 Strike Projection: 2" (51 mm)
 Keeper: 1" x 2" (25 mm x 51 mm)
 Materials: Cast brass
 Finishes: US3, US10, US10B, US26, US26D
 Fasteners: Five (5) #10 x 1" OPHWS, three (3) 10-24 x 1-1/4" FPHMS, and three (3) plastic anchors

- Notes:
- For use with wood or metal doors
 - Holder is mounted on the door
 - Roller is spring loaded to seat on strike - heavy duty rubber pad dampens sound and shock
 - Ideal for use with locksets with a projection of 3" (76 mm) or less



327W

Automatic Wall Stop & Holder

Certification: Meets ANSI A156.16 for L11291
 Holder Base: 3-1/16" x 3-1/2" (78 mm x 89 mm)
 Holder Projection: 1-15/16" (49 mm)
 Engaged Projection: 3-1/2" (89 mm)
 Strike Diameter: 2-3/8" (60 mm)
 Strike Projection: 3-1/16" (78 mm)
 Materials: Cast brass
 Finishes: US3, US4, US10, US10B, US26, US26D
 Fasteners: Three (3) #14 x 1-1/2" FPHWS, three (3) 1/4-20 x 3/4" FPHMS, four (4) 12-24 x 1" TPHMS, four (4) #12 x 1" TPHWS, and three (3) 1/4-20 lead anchors

- Notes:
- For use with wood or metal doors
 - For use with drywall or concrete walls
 - Roller is spring loaded to seat on strike - heavy duty rubber pad dampens sound and shock
 - Strike is adjustable 45° left or right
 - Holder has vertical adjustment once mounted on the door
 - Ideal for use with locksets with a projection of 3" (76 mm) or less
 - For doors up to 500 lbs