

Henkel Corporation
 1345 Gasket Drive
 Elgin, IL 60120
 Contact Information:
 Telephone: 847-468-9200
 Emergency Telephone: 860-571-5100

H.M.I.S.
 HEALTH 2*
 FLAMMABILITY 3
 REACTIVITY 0
 These ratings should be used only
 as part of full implemented
 H.M.I.S. program.

M A T E R I A L S A F E T Y D A T A S H E E T

SECTION 1 - PRODUCT INFORMATION

DATE OF PREPARATION 5/29/07

TRADE NAME..... SIA-689 SOLVENT PAIL/5GAL PHYSICAL FORM: SOLVENT
 MANUFACTURER CODE I.D. F689-05T (Formerly a Sovereign Specialty Chemical Inc Product)
 SOVEREIGN MANUFACTURER CODE I.D. F689 05T

SECTION 2 - HAZARDOUS INGREDIENTS/COMPOSITION INFORMATION

INGREDIENT	% BY WGT	CAS NO.	ALLOWABLE EXPOSURE LEVEL		SARA 313	VP mm Hg @ 20 DEG.C	
			PPM	MG/CU.M.			
METHYL ETHYL KETONE	< 5	78-93-3	TLV-TWA	200	590	X	78
			TLV-STEL	300	885		
			OSHA-PEL	200	590		
			OSHA-STEL	300	885		
			LFL	1.4	UFL 11.4		
SOLVENT REFINED NAPHTHA		64741-84-0	NONE ESTABLISHED				
			LFL	1.0			UFL
HEXANE	15	110-54-3	TLV-TWA	50	180	SKIN X	120
			OSHA-PEL	500	1800		
			LFL	1.0	UFL		
CYCLOHEXANE	< 5	110-82-7	TLV-TWA	100	344	X	
			OSHA-PEL	300	1050		
			LFL	1.3	UFL		
ACETONE		67-64-1	TLV-TWA	500	1188		180
			TLV-STEL	750	1800		
			OSHA-PEL	750	1800		
			OSHA-STEL	1000	2400		
			LFL	2.6	UFL		
TOLUENE	50	108-88-3	TLV-TWA	20	75	SKIN X	22
			OSHA-PEL	200	752		
			OSHA-STEL	300	1128		
			OSHA-CEIL	500	1880		
			LFL	1.7	UFL		

LFL = LOWER FLAMMABILITY LIMIT PERCENT
 UFL = UPPER FLAMMABILITY LIMIT PERCENT
 SKIN = SKIN ABSORPTION MUST BE CONSIDERED AS A ROUTE OF EXPOSURE
 C-CEILING= ALLOW. EXPOSURE LEVEL SHOULD NOT BE EXCEEDED FOR ANY TIME PERIOD
 MFR = MANUFACTURER RECOMMENDED EXPOSURE LIMIT
 STEL = SHORT TERM EXPOSURE LIMIT
 X-SARA 313 = CHEMICAL IS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313
 OF TITLE III OF S.A.R.A. 40 CFR PART 372

SECTION 2 - HAZARDOUS INGREDIENTS/COMPOSITION INFORMATION (Continu

SECTION 3 - HAZARDS IDENTIFICATION

EFFECTS OF SHORT TERM OVEREXPOSURE

SWALLOWING

Can cause gastrointestinal irritation, nausea, and vomiting. Aspiration of material into lung may cause chemical pneumonitis which can be fatal.

INHALATION

May cause nose or throat irritation. High concentrations may cause acute central nervous system depression characterized by headaches, dizziness, nausea and confusion.

EYE

May cause eye irritation.

SKIN

Liquid material may be absorbed through the skin in harmful amounts. May cause defatting and irritation of the skin.

EFFECTS OF REPEATED OVEREXPOSURE

Repeated overexposure to toluene may cause liver damage.

Repeated overexposure to n-hexane may cause damage to the peripheral nervous system.

Methyl ethyl ketone increases the potential for n-hexane to cause neurotoxic effects. Additional precautions must be taken to keep exposure to both substances well below their allowable exposure levels.

Exposure to Methyl Ethyl Ketone may enhance the neurotoxicity of n-Hexane and Methyl-n-Butyl Ketone. This synergistic effect has resulted in peripheral neuropathy in humans.

Reports have associated prolonged and repeated occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH.

Toluene has been found to cause kidney, lung and spleen damage in laboratory animals.

Laboratory studies involving rats indicate some evidence that Methyl Ethyl Ketone may be embryotoxic, fetotoxic and teratogenic.

SECTION 4 - FIRST-AID MEASURES

SWALLOWING

If swallowed do not induce vomiting. (Never give anything by mouth to an unconscious person). Call Poison Control Center, Hospital Emergency Room, or Physician immediately.

INHALATION

Remove to fresh air immediately. If breathing has stopped, give artificial respiration. Keep warm and quiet. Get medical attention immediately.

EYE

Flush with large amounts of water, lifting upper and lower lids occasionally. Continue for at least 15 minutes. Get medical attention immediately.

SKIN

Remove contaminated clothing. Wash affected area with soap and water. Obtain medical attention if irritation persists.

NOTES TO PHYSICIAN

Any treatment that might be required for overexposure should be directed at the control of symptoms and the clinical conditions.

SECTION 5 - FIRE-FIGHTING MEASURES

NFPA FLAMMABILITY CLASSIFICATION FLAMMABLE LIQUID - CLASS IB

FLASHPOINT -1 DEG.F,SFCC (-18 DEG.C,)

EXTINGUISHING MEDIA

Use NFPA Class B Fire extinguishers (carbon dioxide, all purpose dry chemical or alcohol foam) designed to extinguish flammable liquid fires. Polymer foam is preferred for large fires.

SECTION 5 - FIRE-FIGHTING MEASURES (Continued)

UNUSUAL FIRE AND EXPLOSION HAZARDS

During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

DANGER! EXTREMELY FLAMMABLE. VAPORS MAY CAUSE FLASH FIRE.

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters should wear self-contained breathing apparatus.

Water may be ineffective, but may be used to cool exposed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Refer to Section 8 and don respirators, eye, hand, and body protection appropriate for the size of the spill and the exposures encountered.

Keep spectators away. Eliminate all ignition sources (flames, hot surfaces, and sources of electrical, static or frictional sparks).

Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered metal containers for recovery or disposal, or remove with inert absorbent. Use only non-sparking tools. Place absorbent diking materials in covered metal containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.

WASTE DISPOSAL

Dispose in accordance with federal, state and local regulations.

RCRA CLASSIFICATION

This product, if discarded directly, would be classified a hazardous waste based on its ignitability characteristic, i.e. has a flash point of 140 deg. F.(60 deg.C) or less. The proper RCRA classification would be D001.

ENVIRONMENTAL HAZARDS

None known

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Do not store above 115 deg.F (46 deg.C) store large quantities in compliance with OSHA 29CFR1910.106.

OTHER PRECAUTIONS

Do not take internally. Close container after each use. Avoid skin contact.

Empty containers must not be washed and re-used for any purpose.

Containers should be grounded and bonded to the receiving container.

Do not weld, braze or cut on empty container.

Never use pressure to empty. Drum is not a pressure vessel.

SECTION 8 - EXPOSURE CONTROLS

RESPIRATORY PROTECTION

Proper selection of respiratory protection depends upon many factors including duration and level of exposure and conditions of use. In general exposure to organic chemicals such as those contained in this product may not require the use of respiratory protection if used in well ventilated areas. In areas of restricted ventilation a NIOSH approved organic vapor respirator may be required. Under certain conditions, such as spraying, a mechanical prefilter may also be required. In confined areas or in high exposure situations a NIOSH/MSHA approved air supplied respirator may be required. If the TLV's or PEL's listed in Section II are exceeded use a properly fitted NIOSH/MSHA approved respirator with an appropriate protection factor. Refer to OSHA 29 CFR 1910.134 "Respiratory Protection", and "Respiratory Protection a Manual and Guideline, American Industrial Hygiene Association".

VENTILATION

Provide local exhaust ventilation in sufficient volume and pattern so as to maintain exposures below nuisance dust limits and permissible exposure

SECTION 8 - EXPOSURE CONTROLS (Continued)

VENTILATION

limits which may be listed in Section II. Refer to Industrial Ventilation - A Manual for Recommended Practice - American Conference Of Governmental Industrial Hygienists.

HAND PROTECTION

Solvent impermeable gloves are required for immediate or prolonged contact. Refer to glove manufacturer's recommendations and specifications.

EYE PROTECTION

Wear safety glasses meeting the specifications of ANSI Z87.1 where no contact with the eye is anticipated. Chemical safety goggles meeting the specifications of ANSI Z87.1 should be worn whenever there is a possibility of splashing or other contact with the eyes.

OTHER PROTECTIVE EQUIPMENT

Eyewash facility, safety shower.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE 130 DEG.F. (54 DEG.C.) TO 233 DEG.F.(112 DEG.C.)

VAPOR DENSITY Heavier than air. % **VOLATILE BY VOLUME** 100

EVAPORATION RATE VOC 6.50 lb/gal less water& NPRS* 780 g/l less water CALCULATED
Slower than diethyl ether.

WEIGHT LB./GAL. 6.4 VOC .00 lb/gal solids 0 g/l solids CALCULATED
SPECIFIC GRAVITY 0.8

All Physical data determined at 68 DEG. F. (20 DEG. C.) 760 mm Hg

* Negligibly Photochemically Reactive Materials

SECTION 10 - STABILITY AND REACTIVITY

STABILITY

Normally stable.

CONDITIONS TO AVOID

Avoid excessive heat (>115 F (46 C) and sources of ignition.

INCOMPATIBILITY (MATERIALS TO AVOID)

Strong acids or alkaline materials.

HAZARDOUS DECOMPOSITION PRODUCTS

Burning, including when heated by welding or cutting, will produce smoke, carbon monoxide and carbon dioxide.

HAZARDOUS POLYMERIZATION

Will not occur

CONDITIONS TO AVOID

Keep away from heat sparks and flame.

SECTION 11 - TOXICOLOGICAL INFORMATION

No information available.

SECTION 12 - ECOLOGICAL INFORMATION

No information available.

SECTION 13 - DISPOSAL CONSIDERATIONS

See Section 6.

SECTION 14 - TRANSPORT INFORMATION

ITEM: F689-05T

DESC/SIZE: SIA-689 SOLVENT PAIL/5GAL

MODE PROPER SHIPPING NAME CLASS I.D.# PKG GRP
NAERG: 3-05

SECTION 14 - TRANSPORT INFORMATION (Continued)

MODE	PROPER SHIPPING NAME	CLASS	I.D.#	PKG	GRP
IATA (AIR)	PAINT RELATED MATERIAL CARGO AIR ONLY NAERG: 3L	3	UN1263	II	
DOT (HM-181) (DOMESTIC SURFACE)	PAINT RELATED MATERIAL NAERG: 128	3	UN1263	II	
IMDG CODE (OCEAN)	PAINT RELATED MATERIAL	3	UN1263	II	

NOTE! The assignment of Proper Shipping Names is in part a function of the size of the product container and the transport mode. For example, the Proper Shipping Name for a bulk container can differ significantly from the Proper Shipping Name for the same product packaged in a non-bulk container. This can also be true for products shipped via different modes of transportation (i.e. ground, air, ocean). The descriptions provided above are intended to provide some guidance. However, these descriptions may not apply to your package size or mode of shipment. The U.S. Code of Federal Regulations, 49 CFR - Transportation, regulations, and the policies established by some transporters, require that the shipper properly classify and assign a Proper Shipping Name, and label, mark and package the material properly. Therefore, the user of this information is cautioned to consult with applicable regulations, and with qualified advisors prior to the repackaging and or reshipment of this or other any product which contain this product.

SECTION 15 - REGULATORY INFORMATION

All ingredients in this product are listed on the US TSCA Inventory.

WARNING: This product contains
TOLUENE;
a chemical known to the State of California to cause birth defects or other reproductive harm.

INGREDIENT	CAS NO.	DETAIL INVENTORY LIST INFORMATION
METHYL ETHYL KETONE	78-93-3	TSCA(8a PAIR) TSCA(8d) DSL
SOLVENT REFINED NAPHTHA	64741-84-0	DSL
HEXANE	110-54-3	TSCA(12b) TSCA(4) DSL
CYCLOHEXANE	110-82-7	TSCA(12b) TSCA(4) TSCA(8a PAIR) TSCA(8d) TSCA(8d term) DSL
ACETONE	67-64-1	TSCA(4) DSL
TOLUENE	108-88-3	TSCA(8a CAIR) TSCA(8a PAIR) TSCA(8d) DSL

DETAIL INVENTORY LIST DESCRIPTION

SECTION 15 - REGULATORY INFORMATION (Continued)

DETAIL INVENTORY LIST DESCRIPTION

TSCA/Toxic Substances Control Act
(12b)Notices of Export
(4)Test Rules
(8a CAIR)Comprehensive Assessment Information Rules
(8a PAIR)Preliminary Assessment Information Rules
(8d)Health and Safety Reporting Rules
(8d term)Health and Safety Reporting Rules termination
DSL/Canadian Domestic Substance List

SECTION 16 - OTHER INFORMATION

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

For Safety and Regulatory Information contact:
Product Safety and Regulatory Affairs,
Rocky Hill, CT
860-571-5204