



SELF LATCHING FLUSH BOLTS

SELF LATCHING FLUSH BOLTS

Self Latching Flush Bolts by Hiawatha are UL-Listed and are installed in the inactive door. Top bolt automatically engages curved

lip frame strike when inactive door is closed. Bolt remains engaged until retracted by depressing the plunger on the face of the bolt. If provided, the bottom bolt will engage

sill strike only when active door is closed. When active and inactive doors are closed, top and bottom bolts are engaged.



Self Latching Flush Bolts (UL Listed)			
FIRE-RATED METAL DOORS			
		WT.	ANSI/BHMA
3845	Set of Top & Bottom Bolts - 3 Hour Fire Rating Non-handed Flush Bolts for up to 8' x 10' metal doors. Solid Brass or Bronze material. Bolts can be vertically adjusted up to 1-1/2". Face Plate 1" x 6-3/4", overall length 12".	3 lbs	156.16, L14251
3805	Single Top Bolt - 3 Hour Fire Rating Non-handed top bolt for up to 8' x 10' metal doors. Solid Brass or Bronze material. Bolts can be vertically adjusted up to 1-1/2". Face Plate 1" x 6-3/4", overall length 12". Standard finishes US 3,4,10,10B, 26, 26D, 32, 32D. When ordered with bottom fire bolt BFBM, (3805 -BFBM), eliminates the need for bottom automatic flush bolt and dust-proof strike.	1.5 lbs	156.16, L14251
3840	Single Bottom Bolt - 3 Hour Fire Rating Non-handed bottom bolt for up to 8' x 10' metal doors. Solid Brass or Bronze material. Bolts can be vertically adjusted up to 1-1/2". Face Plate 1" x 6-3/4", overall length 12". Standard finishes US 3,4,10,10B, 26, 26D, 32, 32D.	1.5 lbs	
Standard Finishes for Trim Pack(bolt cover plate, screws & strikes: US3,4,10,10B, 26, 26D, 32, 32D)			
FIRE-RATED WOOD DOORS			
		WT.	ANSI/BHMA
3945	Set of Top & Bottom Bolts - 1-1/2 Hour Fire Rating For up to 8' x 9' wood doors. Solid Brass or Bronze material. Bolts can be vertically adjusted up to 1/2". Face Plate 1" x 8-1/2", Depth 2", Door bottom or top plate length 7-1/4". Standard finishes US 3,4,10,10B, 26, 26D, 32, 32D.	3 lbs	156.16, L14251
3905	Single Top Bolt - 1-1/2 Hour Fire Rating For up to 8' x 9' wood doors. Solid Brass or Bronze material. Bolts can be vertically adjusted up to 1/2". Face Plate 1" x 8-1/2", Depth 2", Door top plate length 7-1/4". Standard finishes US 3,4,10,10B, 26, 26D, 32, 32D. When ordered with bottom fire bolt BFBW, (3905-BFBW), eliminates the need for bottom automatic flush bolt and dust-proof strike.	1.5 lbs	156.16, L14251
3940	Single Bottom Bolt - 1-1/2 Hour Fire Rating Non-handed bottom bolt for up to 8' x 9' wood doors. Solid Brass or Bronze material. Bolts can be vertically adjusted up to 1/2". Face Plate 1" x 8-1/2", Depth 2", Door bottom plate length 7-1/4". Standard finishes US 3,4,10,10B, 26, 26D, 32, 32D	1.5 lbs	156.3, Type 25
Standard Finishes for Trim Pack(bolt cover plate, screws & strikes: US3,4,10,10B, 26, 26D, 32, 32D)			