

MANUAL FLUSH BOLTS



Manual Flush Bolts are installed in the inactive door. The lever mechanism extends the bolt head 3/4" into the frame and sill strike, locking inactive door. All rods have 2" adjustment for door and strike clearance.



3790 Flush Bolt for Wood Door



3780 Flush Bolt for Metal Door

Manual Flush Bolts (UL Listed)			
QTY	#	FIRE-RATED METAL DOORS	ANSI/ BHMA
	3780	Manual Bolt - 3 Hour Fire Rating: For up to 8' x 10' metal doors. Solid Brass or Bronze material. Bolts can be vertically adjusted up to 1/2". Face Plate 1" x 6-3/4", overall length 12", top strikes 1-5/16" x 1-5/8" and 1" x 2". Standard finishes US 3,4,10,10B, 26 or 26D. BHMA standard: 605,606,612,613,625,626. Wt: 1 lb	156.16, L14251 Top Strike: A115.4
QTY	#	FIRE-RATED WOOD DOORS	ANSI/ BHMA
	3790	Manual Bolt - 1-1/2 Hour Fire Rating: For up to 8' x 10' wood doors. Solid Brass or Bronze material. Bolts can be vertically adjusted up to 1/2". Face Plate 1" x 6-3/4", overall length 6-3/4", top strikes 15/16" x 2-1/4" and 1" x 2-1/12". Standard finishes US 3,4,10,10B, 26 or 26D. BHMA standard: 605,606,612,613,625,626. Wt: 1 lb	156.16, L14251 Top Strike: A115.4

FIRE BOLTS, STRIKES & TRIM		
	BFBM	Bottom Fire Bolt, UL Listed to pairs of fire doors when specified with an automatic and self latching top flush bolt models 3140 or 3805. US32D. Bolt projects at 230°F, locking leaves. Wt: .1 lb
	BFBW	Bottom Fire Bolt, UL Listed to pairs of fire doors when specified with an automatic and self latching top flush bolt models 3240, 3905 or 3660. US32D. Bolt projects at 230°F, locking leaves. Wt: .1 lb
	380	Dust Proof Strike: 2" deep for floor installation. Face plate 1-1/2" x 3" in US32D or US32 finish. 2 fasteners #8 x 3/4" APA with Rawl plug. 1" x 2-1/8" prep hole for 3/4" bolt. Wt: .4 lb
	381	Dust Proof Strike: 2" deep for threshold installation. Std Finish US32D or US32. 1 Tru Arc ring fastener. 1" x 2-1/8" prep hole for 3/4" bolt. Wt: .4 lb
	382	Dust Proof Universal Strike: 2" deep for threshold or floor installation. US 3, 4,10, 10B, 26, 26D finishes available. Adjustable plate for carpet, threshold or concrete includes lock nut and screw package for all installations. 1" x 2" prep hole for 3/4" bolt. Wt: .1 lb
	-T	Flush Bolt Trim Package: US 3,4,10,10B, 26,26D, 32, 32D. Add "T" to Model Number.

 	Distributor:		Quantity:
	Contractor:		Approved By:
	Model #:	Finish:	Architect:
	Project:		Date:
HEADQUARTERS: 4450 WEST 78TH ST CIRCLE, BLOOMINGTON, MN 55435-5416 PH: 800-554-6077 FAX: 952-835-2218 EMAIL: JL@JLINDUSTRIES.COM WWW.ACTIVARCPG.COM 10/12/10			