

SELF LATCHING FLUSH BOLTS



Self Latching Flush Bolts are installed in the inactive door. Top bolt automatically engages curved lip frame strike when inactive door is closed. Bolt remains engaged until retracted by depressing the plunger on the face of the bolt. If provided, the bottom bolt will engage sill strike only when active door is closed. When active and inactive doors are closed, top and bottom bolts are engaged.

Self Latching Flush Bolts (UL Listed)

QTY	#	FIRE-RATED METAL DOORS	ANSI/ BHMA
		Set of Top & Bottom Bolts - 3 Hour Fire Rating Non-handed Flush Bolts for up to 8' x 10' metal doors. Solid Brass or Bronze material. Bolts can be vertically adjusted up to 1-1/2". Face Plate 1" x 6-3/4", overall length 12". Standard finishes US 3,4,10,10B, 26, 26D, 32, 32D. Wt: 3.0 lb	156.16, L14251
		Single Top Bolt - 3 Hour Fire Rating Non-handed top bolt for up to 8' x 10' metal doors. Solid Brass or Bronze material. Bolts can be vertically adjusted up to 1-1/2". Face Plate 1" x 6-3/4", overall length 12". Standard finishes US 3,4,10,10B, 26, 26D, 32, 32D. When ordered with bottom fire bolt BFBM, (3805-BFBM) , eliminates the need for bottom automatic flush bolt and dust-proof strike. Wt: 1.5 lb	156.16, L14251
		Single Bottom Bolt - 3 Hour Fire Rating Non-handed bottom bolt for up to 8' x 10' metal doors. Solid Brass or Bronze material. Bolts can be vertically adjusted up to 1-1/2". Face Plate 1" x 6-3/4", overall length 12". Standard finishes US 3,4,10,10B, 26, 26D, 32, 32D. Wt: 1.5 lb	
QTY	#	FIRE-RATED WOOD DOORS	ANSI/ BHMA
		Set of Top & Bottom Bolts - 1-1/2 Hour Fire Rating For up to 8' x 9' wood doors. Solid Brass or Bronze material. Bolts can be vertically adjusted up to 1/2". Face Plate 1" x 8-1/2", Depth 2", Door bottom or top plate length 7-1/4". Standard finishes US 3,4,10,10B, 26, 26D, 32, 32D. Wt: 3 lbs	156.16, L14251
		Single Top Bolt - 1-1/2 Hour Fire Rating For up to 8' x 9' wood doors. Solid Brass or Bronze material. Bolts can be vertically adjusted up to 1/2". Face Plate 1" x 8-1/2", Depth 2", Door top plate length 7-1/4". Standard finishes US 3,4,10,10B, 26, 26D, 32, 32D. When ordered with bottom fire bolt BFBW, (3905-BFBW) , eliminates the need for bottom automatic flush bolt and dust-proof strike. Wt: 1.5 lb	156.16, L14251
		Single Bottom Bolt - 1-1/2 Hour Fire Rating Non-handed bottom bolt for up to 8' x 9' wood doors. Solid Brass or Bronze material. Bolts can be vertically adjusted up to 1/2". Face Plate 1" x 8-1/2", Depth 2", Door bottom plate length 7-1/4". Standard finishes US 3,4,10,10B, 26, 26D, 32, 32D. Wt: 1.5 lb	



3845: Set of 3805 Top & 3840 Bottom Flush Bolts



3945: Set of 3905 Top & 3940 Bottom Flush Bolts

		FIRE BOLTS, STRIKES & TRIM
	BFBM	Bottom Fire Bolt, UL Listed to pairs of fire doors when specified with an automatic and self latching top flush bolt models 3140 or 3805. US32D. Bolt projects at 230°F, locking leaves. Wt: .1 lb
	BFBW	Bottom Fire Bolt, UL Listed to pairs of fire doors when specified with an automatic and self latching top flush bolt models 3240, 3905 or 3660. US32D. Bolt projects at 230°F, locking leaves. Wt: .1 lb
	380	Dust Proof Strike: 2" deep for floor installation. Face plate 1-1/2" x 3" in US32D or US32 finish. 2 fasteners #8 x 3/4" APA with Rawl plug. 1" x 2-1/8" prep hole for 3/4" bolt. Wt: .4 lb
	381	Dust Proof Strike: 2" deep for threshold installation. Std Finish US32D or US32. 1 Tru Arc ring fastener. 1" x 2-1/8" prep hole for 3/4" bolt. Wt: .4 lb
	382	Dust Proof Universal Strike: 2" deep for threshold or floor installation. US 3, 4,10, 10B, 26, 26D finishes available. Adjustable plate for carpet, threshold or concrete includes lock nut and screw package for all installations. 1" x 2" prep hole for 3/4" bolt. Wt: .1 lb
	-T	Flush Bolt Trim Package: US 3,4,10,10B, 26,26D, 32, 32D. Add "T" to Model Number.



Distributor:	Quantity:
Contractor:	Approved By:
Model #:	Finish:
Project:	Architect:
	Date:

HEADQUARTERS: 4450 WEST 78TH ST CIRCLE, BLOOMINGTON, MN 55435-5416
 PH: 800-554-6077 FAX: 952-835-2218 EMAIL: JL@JLINDUSTRIES.COM WWW.ACTIVARCPG.COM 10/12/10