

A

Hinges & Pivots

B

Pulls & Plates

C

Flush Bolts & Coordinators

D

Latches, Catches & Bolts

E16

Stops

F

Exterior Hardware

G

Miscellaneous Hardware



Meets ANSI/BHMA 156.16, L11383 for brass and L31383 for aluminum.

FS452 Kick Down Holder

- Units provide simple hold and release, activated with a touch of the foot.
- Cast brass or aluminum construction.
- Stainless steel spring.
- Replaceable non-marring rubber shoes have corrugated bottoms to provide secure grip.
- Shoes are easily replaced when worn. Shoe held on with screw.
- Packed with sheet metal screws.

FS452-4 has a door-to-floor clearance of 2" or less.

FS452-5 has a door-to-floor clearance up to 3".

Dimensions

FS452-4 Door-to-Floor Clearance: 2" or less

FS452-5 Door-to-Floor Clearance: Up to 3"

FS452-4 Plate Height: 2-1/8"

FS452-5 Plate Height: 2-1/8"

FS452-4 Plate Width: 1"

FS452-5 Plate Width: 1"

Finishes *brass*

Ives Number	US3	US4	US10	US10B	US15	US26	US26D
BHMA	605	606	612	613	619	625	626

Finishes *aluminum*

Ives Number US28*

BHMA 628

* available in 4" only



Meets ANSI/BHMA 156.16, L11382 for brass and L31382 for aluminum.

FS455 Kick Down Holder

- Units provide simple hold and release, activated with a touch of the foot.
- Cast brass or aluminum construction.
- Replaceable non-marring rubber shoes have corrugated bottoms to provide secure grip. When worn, shoes are easily replaced. Shoe held on with screws.
- Door-to-floor clearances of 2" or less.

Dimensions

Door-to-Floor Clearance: 2" or less

Plate Height: 1-3/4"

Plate Width: 1-3/4"

Finishes *brass*

Ives Number	US3	US4	US5	US10	US10B	US15	US26	US26D
BHMA	605	606	609	612	613	619	625	626

Finishes *aluminum*

Ives Number	US3AL	US5AL	US10AL	US27
BHMA	666	609	668	673



FS544
Meets ANSI/BHMA 156.16, L11381

FS555
Meets ANSI/BHMA 156.16, L11391

**FS544
FS555 Kick Down Holder**

- Units provide an economical method to hold open doors.
- Cast of durable iron.
- Non-marring rubber shoes have corrugated bottoms to provide secure grip. Rubber shoe is securely fastened with screw. When worn, shoes are easily replaced.

FS544 for door-to-floor clearances of 2" or less
FS555 for door-to-floor clearances up to 3".

Dimensions

FS544	FS555
Door-to-Floor Clearance: 2" or less	Door-to-Floor Clearance: Up to 3"
Plate Height: 2-1/4"	Plate Height: 2-1/4"
Plate Width: 1-7/16"	Plate Width: 1-7/16"

Finishes

Ives Number	SP4	SP10	SP28	SP313	SPBLK
BHMA	706	691	689	695	622

Hinges & Pivots	A
Pulls & Plates	B
Flush Bolts & Coordinators	C
Latches, Catches & Bolts	D
E17 Stops	E17
Exterior Hardware	F
Miscellaneous Hardware	G