

8400 Series Protection Plates

- Door protection plates are available in .050" thick brass, stainless steel or aluminum; and 1/8" thick high impact polyethylene in clear or black.
- Bevel edge options; specify B4E for all four edges.
- Mounting screw pack furnished standard, 16 screws per pack. Optional screw packs are available for TEK or TORK screw heads. Refer to the following chart for ordering.
- Specify NMH for no mounting holes.
- Specify NMH-A for no mounting holes with adhesive.
- Specify CS for counter sunk mounting holes.
- Specify ERS prepped with extra row of screws.

Kickplate Gasket Tape Tape is recommended when using a brass plate on a metal door to reduce tarnishing from electrolytic oxidation. One tape pack will cover an the perimeters of a 8" x 34" kickplate. Order 8401 Gasket Tape.


8400 Protection Plate
8402 (UL)* Protection Plate

*UL mark appears in upper right corner.

Number of screw packs required by plate size (specify TEK Screws or TORK screws).

	22"-25"	26"-33"	34"-41"	42"-48"
4"-8"	1	1	1	1
9"-16"	1	1	1	1
17"-24"	1	1	1	2
25"-32"	1	1	2	2
33"-40"	1	2	2	2
41"-48"	2	2	2	2

Finishes brass

US Number	US3	US4	US10	US10B	US15	US26	US26D
BHMA	605	606	612	613	619	625	626

Finishes stainless steel

US Number	US32	US32D
BHMA	629	630


Finishes aluminum

US Number	US28
BHMA	628

Finishes plastic

Clear and Black

A
Hinges & PivotsB13
Pulls & PlatesC
Flush Bolts & CoordinatorsD
Latches, Catches & BoltsE
StopsF
Exterior HardwareG
Miscellaneous Hardware

A Hinges & Pivots		Mop Plates • Protect the bottom of the pull side of door subject to cleaning and mopping procedures. • Size Ranges: 4" to 6" high, 22" to 48" wide
B14 Pulls & Plates		Kick Plates • Protect the bottom of the push side of doors subject to scuffing from foot traffic. • Recommended for all doors subject to normal use (especially doors using a closer). • Size Ranges: 8" to 24" high, 22" to 48" wide
C Flush Bolts & Coordinators		Stretcher Plates • Protect doors at specific areas where consistent contact is made by stretchers, service carts or other equipment. • Usually applied to push side of doors. • Specify "B4E" Option for beveled edges. • Size Ranges: 6" to 8" high, 22" to 48" wide
D Latches, Catches & Bolts		Armor Plates • Protect lower half of doors from abuse by hard carts, trucks and rough usage. • Usually applied to push side of single doors and both sides of double acting doors. • Size Ranges: 26" to 48" high, 22" to 48" wide
E Stops		
F Exterior Hardware		
G Miscellaneous Hardware		