

KLEIN EST STOOLS



Klein Tools Telecom

Table of Contents

Pliers	Cutting & Hole Making	5
Wire Strippers/Cutters & Crimpers	Lineman Tools	. 6
Crimping Tools	Hammers, Chisels & Punches	6
Cutting Tools	Jobsite Accessories	6
Levels & Measuring	Belts, Pouches, Storage & Tool Bags	7
Screwdrivers & Nut Drivers	Voice, Data, Video Tools	8
Gloves	Fish Tapes & Rods	10
Test & Measurement	Wrenches	10

Warnings and Warranty

Warning Symbols



Warning



Always wear approved eye protection.



NOT insulated. Plastic-dipped or slip-on plastic handles are NOT intended for protection against electrical shock.

Never use on or near live electrical circuits.



Use a safe work position to avoid loss of balance.



Do NOT use to pry.



Do NOT extend handle length.



Do NOT use to chisel.

Test and Measurement

AWARNING:

- To ensure safe operation and service of the tester, follow these instructions.
 Failure to observe these warnings can result in severe injury or death.
- · Before each use, verify meter operation by measuring a known voltage or current.
- Never use a meter on a circuit with voltages that exceed the category based rating of the meter.
- \bullet Do not use the meter during electrical storms, or in wet weather.
- $\bullet\,$ Do not use the meter or test leads if they appear to be damaged.
- · Ensure meter leads are fully seated, and keep fingers away from the metal probe contacts when making measurements.
- Never assume neutral or ground wires are de-energized. Neutrals in multi-wire branch circuits may be energized when disconnected and must be retested before handling.
- · Do not open the meter to replace batteries while the probes are connected.
- Use caution when working with voltages above 60V DC, or 25V AC RMS.
 Such voltages pose a shock hazard.
- To avoid false readings that can lead to electrical shock, replace batteries
 if a low battery indicator appears.
- Unless measuring voltage or current, shut off and lock out power before measuring resistance or capacitance.
- Always adhere to local and national safety codes. Use individual protective equipment to prevent shock and arc blast injury where hazardous live conductors are exposed.

Fish Tapes

AWARNING: Never remove screws while fish tape is coiled inside reel.

Personal Protective Equipment (Hard Hats, Eyewear, Accessories)

AWARNING: It is important that users of these products read, understand, and follow all instructions, cautions, and warnings that are attached to and/or packed with the product.

See www.kleintools.com/warranty for more information.

Warranty Returns

All warranty returns must include a Warranty Return Authorization (WRA) number. The WRA for the U.S. can be obtained by calling Customer Service at 1-800-553-4676. (International call 1-847-821-5500) or email serviceonline@kleintools.com.

Specifications of all products in this catalog are subject to change without notice.

Dimensions shown for all forged products in this catalog are as precisely accurate as possible, but subject to very slight variations that are unavoidable in forging and grinding operations. Dimensions of Klein forged tools and all other tools and equipment are always within commercial tolerances recognized for such products.

Side-Cutting Pliers

New England Nose with plastic-dipped handles.

Cat. No.	Description	Overall Length	Jaw Length	Jaw Width	Handle Color
D2000-9NE	Heavy-Duty Cutting	9-3/8" (238 mm)	1-19/32" (41 mm)	1-1/4" (32 mm)	Royal Blue
D2000-9NETH	Lineman Bolt Holding	9-3/8" (238 mm)	1-19/32" (41 mm)	1-1/4" (32 mm)	Royal Blue
D213-8NE	Standard Cutting	8-11/16" (221 mm)	1-7/16" (37 mm)	5/8" (16 mm)	Dark Blue
D213-9NE	Standard Cutting	9-3/8" (238 mm)	1-19/32" (41 mm)	5/8" (16 mm)	Dark Blue
HD213-9NE	Heavy-Duty Oversized	9-1/2" (241 mm)	1-19/32" (41 mm)	1-1/4" (32 mm)	Light Red
D213-9NETH	Lineman Bolt Holding	9-3/8" (238 mm)	1-19/32" (41 mm)	1-1/4" (32 mm)	Dark Blue
HD213-9NETH	Heavy-Duty Oversized Lineman Bolt Holding	9-1/2" (241 mm)	1-19/32" (41 mm)	1-1/4" (32 mm)	Light Red





Diagonal-Cutting

Plastic-dipped handles

Cat. No.	Description	Nose Type	Overall Length	Jaw Length	Jaw Width	Jaw Thickness	Cutting Knives	Handle Color
72192	Telephone Work, Bell D-6	N/A	6-1/8" (156 mm)	13/16" (21 mm)	3/4" (19 mm)	13/16" (21 mm)	Standard	Red
D252-6SW	Bell System Type "W" Notches	Tapered	6-1/8" (156 mm)	13/16" (21 mm)	3/4" (19 mm)	7/16" (11 mm)	Standard	Red
D228-7	High-Leverage	Standard	7-1/8" (181 mm)	13/16" (21 mm)	1-3/16" (30 mm)	7/16" (11 mm)	Standard	Red
D228-8	High-Leverage	Standard	8-1/16" (205 mm)	13/16" (21 mm)	1-3/16" (30 mm)	7/16" (11 mm)	Standard	Red
D238-8	High-Leverage	Angled	8-1/16" (205 mm)	13/16" (21 mm)	1-3/16" (31 mm)	7/16" (11 mm)	Semi-Flush*	Red
D248-8	Angled Head	Standard	8-1/16" (205 mm)	13/16" (21 mm)	1-3/16" (31 mm)	7/16" (11 mm)	Standard	Red
D202-6	Standard	Tapered	6-1/8" (156 mm)	13/16" (21 mm)	11/16" (18 mm)	7/16" (11 mm)	Standard	Red
D202-6C	Standard	Tapered	6-1/8" (156 mm)	13/16" (21 mm)	11/16" (18 mm)	7/16" (11 mm)	Standard	Red
D220-7	Heavy-Duty	Tapered	7-11/16" (195 mm)	1" (25 mm)	31/32" (25 mm)	1/2" (13 mm)	Standard	Red
D252-6	Heavy-Duty	Tapered	6-1/8" (156 mm)	13/16" (21 mm)	3/4" (19 mm)	7/16" (11 mm)	Standard	Red
D240-6	Stripping Hole	Standard	6-1/8" (156 mm)	13/16" (21 mm)	11/16" (18 mm)	7/16" (11 mm)	Standard	Red
D230-4C	Electronics	Pointed	4-1/4" (108 mm)	1/2" (13 mm)	7/16" (11 mm)	1/4" (6 mm)	Semi-Flush*	Royal Blue
D257-4	Electronics, Midget	Pointed	4-1/4" (108 mm)	1/2" (13 mm)	7/16" (11 mm)	1/4" (6 mm)	Semi-Flush*	Royal Blue
D244-5C	Electronics, Midget	Pointed	5-1/16" (129 mm)	11/16" (18 mm)	1/2" (13 mm)	5/16" (8 mm)	Flush	Royal Blue
D275-5	Electronics, Flush Cutter	Pointed	5" (127 mm)	N/A	N/A	N/A	Flush	Red

^{*}Semi-flush cutting knives cut Cherry Burrel rivets. For use on non-ferrous wire only.

Long-Nose Pliers

Plastic-dipped handles

Cat. No.	Description	Overall Length	Jaw Length	Jaw Width	Knife Length	Point Thinkness	Handle Color
D203-6	Standard Side-Cutting	6-5/8" (168 mm)	1-7/8" (48 mm)	11/16" (18 mm)	1/2" (13 mm)	3/32" (2 mm)	Yellow
D203-6C	Standard Side-Cutting, Spring-Loaded	6-5/8" (168 mm)	1-7/8" (48 mm)	11/16" (18 mm)	1/2" (13 mm)	3/32" (2 mm)	Yellow
D203-6H2	Switchboard Work Side Cutting Strips 19 & 22 AWG	6-5/8" (168 mm)	1-7/8" (48 mm)	11/16" (18 mm)	1/2" (13 mm)	3/32" (2 mm)	Yellow
D203-7	Standard Side-Cutting	7-3/16" (183 mm)	2-7/16" (62 mm)	11/16" (18 mm)	1/2" (13 mm)	3/32" (2 mm)	Yellow
D301-6	Standard	6-5/8" (168 mm)	1-7/8" (48 mm)	11/16" (18 mm)	N/A	3/32" (2 mm)	Yellow
D301-6C	Standard Spring-Loaded	6-5/8" (168 mm)	1-7/8" (48 mm)	11/16" (18 mm)	N/A	1/16" (2 mm)	Yellow
D302-6	Curved Electronics	6-3/8" (162 mm)	1-1/2" (38 mm)	11/16" (18 mm)	N/A	3/32" (2 mm)	Yellow
D320-41/2C	Midget Curved Electronics	4-3/4" (121 mm)	1" (25 mm)	13/32" (10 mm)	N/A	1/16" (2 mm)	Royal Blue

Slip-Joint Pliers



Pump Pliers

Cat. No.	Overall Length	Max. Jaw Capacity	Handle Finish	Handle Color
D502-6	6-1/2" (165 mm)	1-3/16" (30 mm)	Plastic-Dipped	Yellow
D502-10	10" (254 mm)	1-3/4" (45 mm)	Plastic-Dipped	Yellow
D502-12	12-1/4" (311 mm)	2-3/8" (60 mm)	Plastic-Dipped	Yellow








Strippers

Cat. No.	Strips & Cuts	Crimps	Spring-Loaded	Screw Shearing	Overall Length	Handle Color				
Klein Kurv	Klein Kurve® Multi-Purpose Wire Strippers/Cutters									
11055	10 – 18 AWG solid (4.0 mm² – .75 mm²) & 12 – 20 AWG stranded (2.5 mm² – .50 mm²)	No	Yes	6-32 & 8-32	7-1/8" (181 mm)	Blue/Yellow				
Solid and	Stranded Wire Strippers/Cutters									
11045	10 – 18 AWG solid (4.0 mm² – .75 mm²)	No	Yes	No	6-1/4" (159 mm)	Yellow				
11046	16 - 26 AWG stranded (1.0 mm ² 14 mm ²)	No	Yes	No	6-1/4" (159 mm)	Red				
11047	22 - 30 AWG solid (.34 mm ² 05 mm ²)	No	Yes	No	6-1/4" (159 mm)	Yellow				
Combinati	Combination Wire-Stripping and Cutting Tools									
1000	8 – 22 AWG solid (6.0 mm² – .34 mm²), 10-16 AWG stranded (4.0 mm² – 1.0 mm²)	Insulated terminals	No	4-40, 6-32, 8-32, 10-24, 10-32	7-3/4" (197 mm)	Red				

Crimping Tools



Cutting Tools

Cat. No.	Description	Cutting Capacity			Overall Length	
Bolt Cutte	ers					
63324	Steel-Handle Bolt Cutter	7/16" Soft & Medium; 5/16" Hard Materi	al		24" (610 mm)	
63336	Steel-Handle Bolt Cutter	9/16" Soft & Medium; 7/16" Hard Materi	al		36" (914 mm)	
Cable Cut	ters					
63030	Coaxial Cable Cutter	Up to 1" Copper and Aluminum Coaxial	Cable		8-1/4" (210 mm)	
63035	Utility Cable Cutter	MCM Cable 350 Copper, 350 Aluminum			16-1/4" (413 mm)	
63041	Standard Cable Cutter	1-3/8" diameter, MCM Cable 500 Coppe	r, 750 Aluminum		25-1/2" (648 mm)	
63050	High Leverage Cable Cutter		•			
J63050	High Leverage Cable Cutter, Journeyman™ Handles	4/0 Aluminum, 2/0 Soft Copper, 100-Pa	9-9/16" (243 mm)			
63055	Compact Cable Cutter	24 AWG Copper, Aluminum Multi-Strand	d Cable and Wire, and 10	00-Pair Telephone Cable	8" (203 mm)	
63060	Ratcheting Cable Cutter	MCM Cable up to 600 Copper, 750 Alur	ninum, 1-1/8" Communi	cation Cable	- 10-1/4" (260 mm)	
63607	Ratcheting ACSR Cable Cutter	MCM Cable up to 336 ACSR, 400 Coppe	er, and 600 Aluminum		- 10-1/4 (200 111111)	
PVC Cutte	r					
50034	Large Capacity Ratcheting PVC Cutter	O.D. 5/8" to 2-1/2" (15.9 to 63.5 mm) I.I	O. 1/2" to 2" (12.7 to 50.	8 mm)	11" (279 mm)	
50035	Blade for Large Capacity PVC Cutter	N/A			N/A	
Cat. No.	Description	Strips	Features	Cutting Length	Overall Length	
Scissors a	and Snips					
2100-7	Electrician's Scissors	- 19 and 23 AWG Wire	Scraper, File	1 7/0" /40 mm)	5-1/4" (133 mm)	
2100-8	Free-Fall Snip, Stainless Steel	- 19 and 23 AWG Wife	Extended handle 1-7/8" (48 mm)		6-5/16" (160 mm)	

⚠WARNING: Do NOT cut cold PVC.

MARNING: Do NOT Cable.

⚠WARNING: Do NOT cut steel

or ACSR.

AWARNING: Do NOT use to cut metallic pipes, cable or wire.





Levels & Measuring

Cat. No.	Description
935	Torpedo Level
862-16	16' Double Hook Magnetic Tape Measure
862-25	25' Double Hook Magnetic Tape Measure



- Protect hands when cleaning magnetic tip end. Use gloves or cloth. Avoid magnetic contact with sensitive electronic or computer equipment.
- To avoid personal injury and damage to this tool, do not allow the tape blade to retract into case.
- Do NOT open case. Spring motor is under tension, and opening case may
- cause injury.







Screwdrivers & Nut Drivers

Cat. No.	Tip Type	Tip Size	Shank Length	Overall Length
Cushion-(Grip Screwdrivers			
600-4	Keystone, Heavy-Duty	1/4" (6 mm)	4" (102 mm)	8-11/32" (212 mm)
600-8	Square Shank	3/8" (10 mm)	8" (203 mm)	13-7/16" (341 mm)
601-4	Oakinst Dawed Obasil	3/16" (5 mm)	4" (102 mm)	7-3/4" (197 mm)
601-6	— Cabinet, Round Shank	3/16" (5 mm)	6" (152 mm)	9-3/4" (248 mm)
602-4	Keystone, Heavy-Duty	1/4" (6 mm)	4" (102 mm)	8-11/32" (212 mm)
602-6	Round Shank	5/16" (8 mm)	6" (152 mm)	10-15/16" (278 mm)
603-3		#1	3" (76 mm)	6-3/4" (171 mm)
603-4	Phillips, Round Shank	#2	4" (102 mm)	8-5/16" (211 mm)
603-6	_	#3	6" (152 mm)	11" (279 mm)
Plastic Ha	andle Screwdrivers			
A216-4	Cabinet, Round Shank	1/8" (3 mm)	4" (102 mm)	7" (178 mm)
Cat. No.	Size	Shank Length	Color Code	Overall Length
Cushion-	Grip Nut Drivers			
630-1/4	1/4"	3" (76 mm)	Red	6-3/4" (172 mm)
630-3/16	3/16"	3" (76 mm)	Black	6-3/4" (172 mm)
630-3/8	3/8"	3" (76 mm)	Blue	6-3/4" (172 mm)
630-5/16	5/16"	3" (76 mm)	Yellow	6-3/4" (172 mm)
630-7/16	7/16"	3" (76 mm)	Brown	7-5/16 (186 mm)
630-1/2	1/2"	3" (76 mm)	Red	7-5/16 (186 mm)
Cat. No.	Size	Shank Length	Handle Color	Overall Length
Plastic Ha	andle Nut Drivers			
S10-6M	5/16"	6" (152 mm)	Amber	9-5/8" (245 mm)
S12-6M	3/8"	6" (152 mm)	Blue	9-5/8" (245 mm)
S86M	1/4"	6" (152 mm)	Yellow	9-5/8" (245 mm)
Cat. No.	Shank Length		Overall Length	
Cushion-	Grip Scratch Awl			
650	3-1/2" (89 mm)		7-7/8" (200 mm)	



Multi-Bits Screwdrivers/Nut Drivers & Sets

Cat. No.	Description	Contains				
Cushion-Grip Handles						
85076	7-Piece Screwdriver Set	4" square-shank, keystone-tip, 6" round-shank, keystone-tip, 3" round-shank, cabinet-tip, 6" round-shank, cabinet-tip, 4" round-shank, #1 Phillips-tip, 3" round-shank, #1 Phillips-tip, 4" round-shank, #2 Phillips-tip				
631	7-Piece Nut Driver Set	3/16", 1/4", 5/16, 11/32, 3/8", 7/16", 1/2" in 3" (76 mm) lengths				
647	7-Piece Nut Driver Set	3/16", 1/4", 5/16, 11/32, 3/8", 7/16", 1/2" in 6" (152 mm) lengths				
32581	4-in-1 Electronics Screwdriver	T7, T8, T10, T15 TORX®. 6-1/2" (165 mm) overall length				
32476	5-in-1 Screwdriver/Nut Driver	5/16" (8 mm) nut driver, #1 & #2 Phillips, 1/4" & 3/16" (7 mm & 5 mm) slotted. 7-3/4" (197 mm) overall length				
32807MAG	7-in-1 Multi-Nut Driver	1/4", 5/16", 11/32", 3/8", 1/2", 7/16" & 9/16" sizes. 9.5" (241 mm) overall length				
32477	10-in-1 Screwdriver/Nut Driver	5/16" and 1/4" nut drivers, #1 & #2 Phillips, 1/4" & 3/16" slotted, T10 and T15 TORX®, #1 & #2 square-recess. 7-3/4" (197 mm) overall length				
32500	11-in-1 Screwdriver/Nut Driver	3/8", 5/16" & 1/4" nut drivers, #1 & #2 Phillips, 1/4" & 3/16" slotted, T10 & T15 TORX®, #1 & #2 square-recess. 7-1/4" (184 mm) overall length				
Plastic-Ha	ndles					
32460	4-in-1 Screwdriver	Phillips #1, #2; Cabinet; Slotted - 7-5/8" (194 mm) overall length				
70035	Magnetic Screwdriver Set	#1, #2 Phillips, 3/16" & 9/32" (4.8 & 7.1 mm) Slotted - 3-7/16" overall length				



Gloves

Description	Medium	Large	X-Large	XX-Large
Long-Cuff Gloves		40010	40012	
Cowhide Gloves with Thinsulate™	40016	40017	40018	
Cowhide Work Gloves	40021	40022		
Lineman Work Gloves	40080	40082	40084	40086
Journeyman™ Utility Gloves		40206	40207	
Journeyman™ Leather Gloves	40220	40221	40222	



 $\triangle \textbf{WARNING:}$ Not flameproof or fire retardant. DO NOT expose to open flame or sparks.





Test & Measurement

Cat. No.	Description	Functions	Included Accessories	Batteries	Safety Rating	Drop Protection
CL110	Digital Clamp Meter AC Auto-Ranging 400A	AC current via the clamp & AC/DC voltage, resistance and continuity via test-leads	Carrying Case, Test Leads, Batteries	3 x AAA	CAT III 600V	3.3 ft (1 m)
CL210	Digital Clamp Meter AC Auto- Ranging 400 with Temperature	AC current, AC/DC voltage, resistance, continuity and temperature	Carrying Case, Test Leads, Thermocouple with Adapter, Batteries	3 x AAA	CAT III 600V	3.3 ft. (1 m)
IR2000A	12:1 Infrared Thermometer	Auto Scan -76° to 1022°F (-60° to 550°C) Max/ Min/Average/ Differential	Case, K-type Thermocouple and Batteries	2 x AAA	N/A	6.6 ft (2 m)
IR5	Dual Laser Infrared Thermometer	Temperature: -22° to 752°F (-30° to 400°C), Auto-scan; max/min/avg/diff	Pouch, Batteries	9V	N/A	6.6 ft. (2 m)
MM300	600V Manual-Ranging Multimeter	Manual-ranging, AC/DC voltage, DC current, resistance, test diode, continuity, battery test	Test Leads, Batteries	2 x AAA	CAT III 600V	3.3 ft (1 m)
MM400	600V Auto-Ranging Multimeter	Auto-ranging, AC/DC voltage, AC/DC current, resistance, temperature, capacitance, frequency, duty-cycle, diode test, continuity	Test Leads, Batteries, Thermocouple	2 x AAA	CAT III 600V	3.3 ft (1 m)
MM700	1000V AC/DC TRMS/Low Impedance Multimeter	Auto-ranging True Root-Mean-Squared (TRMS), AC/DC voltage, AC/DC current, and resistance, temperature, capacitance, frequency, duty-cycle, diode test, continuity	Case, Test Leads, Thermocouple, Batteries, Alligator Clips	2 x AAA	CAT IV 600V	6.6 ft (2 m)
RT210	GCFI Receptacle Tester	Diagnoses common wiring faults in standard grounded outlets	N/A	N/A	UL, SA, CE	6.6 ft (2 m)

Holemaking

Cat. No.	Description	Features
53001	15-Piece Regular-Point Drill-Bit Set	• 1/16" through 1/2" by 32nds drill bits • Hinged metal box with two stand-up bit holders
53716	Flex Bit Auger, 3/8" x 54" length	Screw point tip pulls the bit through wood
53751	Flex Bit Auger, 3/4" x 54" length	Hole in tip allows for use with wire or cable pulling grip

NOTE: Read and follow safety instructions in power tool owner's manual.



Saws & Blades

Cat. No.	Description	Blade Length	Overall Length
703	Magic-Slot Compass Saw	8" (203 mm)	13" (330 mm)
725	Jab Saw	6" (152 mm)	12" (305 mm)
31737	Folding Jab Saw	5.2" (132 mm)	11.9" (302 mm)
31734	Saw Blades for 18 Gauge Metal, 5-pack	6" (152 mm)	6" (152 mm)
702-12	High-Tension Hacksaw	12" (305 mm)	16-1/4" (413 mm)
1224BIP	Bi-Metal Blades, 10-pack for use with 702-12	12" (305 mm)	12" (305 mm)



Knives

Cat. No.	Description	Features	Blade Length	Overall Length		
Cable/Lin	eman's Skinning Knives					
44218	Cable Skinning Utility Knife	440A Stainless Steel Sheepsfoot blade	2-1/2" (64 mm)	7-51/64" (198 mm)		
44138	Replacement Blades for Cable Skinning U	tility Knife (3-Pack)				
1570-3LR	Cable Skinning Knife	Hook Blade and Notch	3" (76 mm)	8" (203 mm)		
1570-3	Cable Skinning Knife	Hook Blade, Notch, and Ring	3" (76 mm)	8" (203 mm)		
Cable Spl	itting/Splicing Knives & Accessor	es				
1515-S	Cable-Sheath Splitting Knife	2-3/4" (70 mm)	7-3/8" (187 mm)			
5574S	Knife Guard, Small fits Cat. No. 1515-S knife					
15151	Cable-Sheath Splitting Knife, Bell System		4-1/2" (114 mm)	8-3/4" (222 mm)		
5574L	Knife Guard, Large fits Cat. No. 1515-1 ki	nife				
44200	Cable Splicer's Knife	1095 steel	1-3/4" (45 mm)	6-1/4" (159 mm)		
46037	Cable Splicer's Kit	Cable splicer's knife, electricians scissors and 2-pocket leather pouch				
46039	Cable Splicer's Kit	Cable splicer's knife, free-fall snip and lea	ther holder			
Pocket Kr	ives					
44033	Drop-Point	Stainless steel blade with Rosewood Handle Insert	2-1/4" (57 mm)	5-1/4" (133 mm)		
1550-4	Sheepsfoot Slitting Blade	Carbon steel	2-5/8" (67 mm)	6-1/8" (156 mm)		
44100	Utility Knife with Retractable Blade	3 standard blades stored in handle	N/A	6-5/8" (168 mm)		











⚠WARNING: Blades are intended for cutting only, and should be handled and disposed of with care. Bending the blade can cause it to break, possibly resulting in bodily injury. Check local laws on legality of selling or possesing these knives.

Lineman Buckets & Accessories

Cat. No.	Description	Body Material /Color		Handles	Extra Features
Oval Bucket	ts				
5144	15-Pocket Aerial	Canvas (natural)		N/A	Hooks (2)
5144H	Hook for Aerial Buckets	Nylon 66 polymer		N/A	N/A
5144S	15-Pocket Aerial	Canvas (natural)		Sisal Rope	Swivel snap
5144BHB140S	29-Pocket Hard-Body Aerial	Denier Polyester (black)		Polyester	N/A
5152S	41-Pocket Aerial	Canvas (natural)		Sisal Rope	Swivel snap
Tapered Wa	III Buckets				
5103\$	Heavy-Duty	Canvas (natural)		Rope	Swivel snap, leather glove strap
5172PS	Heavy-Duty with 15-Pockets	Canvas (natural)		Rope	Swivel snap
Cat. No.	Description	Load Rating	Body Material/Color	Handles	Extra Features
Straight Wa	II Buckets				
5104S	Leather-Bottom Bucket	100 lbs (45 kg)	Canvas (natural)	Rope	Swivel snap
5104FR	Flame-Resistant Canvas Bucket	100 lbs (45 kg)	Flame-Resistant Canvas (black)	Web	Interior Pocket
5104VT	Leather Bottom Bucket with Top	N/A	Canvas (natural)	Rope	VELCRO® Closure
5104CLR17	Heavy Duty Top Closing Bucket, 17"	150 lbs (68 kg)	Canvas (natural)	Web	Swivel snap Holds a 5-gallon bucket
51T0P	Vinyl Bucket Top	N/A	Orange	Strap	Works with 5104 series



AWARNINGS:

• Inspect for damage before each use. • Remove from service if bucket shows signs of wear. • Never exceed the working load limit.

Tool Tethers

Cat. No.	Load Rating	Relaxed Length	Stretched Length	Weight
TT1	10 lbs (4.5 kg)	32" (81.3 cm)	60" (152.4 cm)	0.22 lbs (0.10 kg)
TT2	15 lbs (6.8 kg)	32" (81.3 cm)	51" (130 cm)	0.10 lbs (0.05 kg)

Block & Tackle

Cat. No.	267 Block	268 Block	258 Anchor Hook	259 Swivel Anchor Hook	Rope spliced to component number						
Block & Tackle Packages											
1802-30	Χ	Χ	Χ								
1802-30SR	Χ	χ	Χ		268 Block						
1802-30S	Х	Х		Χ							
Cat. No.	Length	Max. Safe Load	Includes								
Polypropyl	lene Hand-Lines										
1803-60	75' (00 m)	0E0 lbo (110 kg)	Snap Hook (Cat. No. 44	I3A)							
1804-60	- 75' (23 m)	250 lbs. (113 kg)	Swivel Hook (Cat. No. 4	170)							
Light, galvaniz	ed-steel shell blocks are	fitted with snubbing ho	ooks to hold the load. Sh	eaves are strong yet	lightweight aluminum						

Light, galvanized-steel shell blocks are fitted with snubbing hooks to hold the load. Sheaves are strong yet lightweight aluminur alloy with all-bronze bushings.

⚠WARNING: This is NOT an occupational protective device. NOT for human support.

Rope spliced to component number 268 Block lightweight aluminum

Hammers, Chisels & Punches

Cat. No.	Description	Head Weight	Overall Length
807-18	Electrician's Straight-Claw Hammer	18 oz (510 g)	15" (381 mm)
808-16	Straight-Claw Hammer - Heavy-Duty	16 oz (454 g)	13" (330 mm)
832-32	Lineman's Straight-Claw Hammer	32 oz (907 g)	15" (381 mm)
809-36	Lineman's Double-Face Hammer	36 oz (1021 g)	14" (356 mm)
809-36MF	Lineman's Milled-Face Hammer	36 oz (1021 g)	14" (356 mm)
818-16	Curved-Claw Hammer – Heavy-Duty	16 oz (454 g)	13" (330 mm)
818-20	Curved-Claw Hammer - Heavy-Duty	20 oz (567 g)	14" (356 mm)



Jobsite Accessories

Cat. No.	Description	Towel Size	Towel Size			
51425	Klein Kleaners™ Hand Cleaning Towels	9" x 12" (229 mm x 3	305 mm) Package of 72			
Cat. No.	Description	Lumens	Run Time	Drop Height	Batteries	
56220	LED Headlamp Flashlight with Strap for Hard Hat	Spotlight - 150, Floodlight - 50	6 hrs. 10 hrs.	6' (1.8 m)	3 x AAA	
Cat. No.	Description	Overall Length	Overall Height	Overall Height Overall Width		
Tradesma	n Pro™ Coolers					
55600	Tough Box, 17-Quart	12" (305 mm)	12" (305 mm)	16-13/64" (412 mm)	2	
55601	Soft Lunch	9-1/2" (241 mm)	13" (330 mm)	12" (305 mm)	4	
55625	Tough Box, 9-Quart	14.7" (373 mm)	12" (305 mm)	8.8" (224 mm)	2	









Tool Bags & Storage

55421	RF	0_1	4

Cat. No.	Description	Material/Color	Shoulder Strap	Closure Type	Total Pockets	Length	Width	Height/Depth
Tool Bags	& Storage							
5151	Ten-Compartment Drawstring Bag	Canvas, Olive	No	Drawstring	10	11" (279 mm)	N/A	6" (152 mm)
58888	Tool Tote™	Denier polyester (Black)	Included	Open top	12	15-1/2" (394 mm)	7-1/2" (191 mm)	10" (254 mm)
58890	Tool Tote™, Tape Thong	Denier polyester (Black)	Included	Open top	17	15-1/2" (394 mm)	7-1/2" (191 mm)	10" (254 mm)
5140	4-Pack Zipper Bags	Canvas (Olive, Orange, Blue, Yellow)	No	Zipper	1	12-1/2" (318 mm)	1/2" (13 mm)	7" (178 mm)
55470	2-Pack Stand-Up Zipper Bags	1680d/2520d ballistic nylon bottom (Orange/Black; Gray/Black)	No	Zipper	1	8 1/2" (216 mm) 9" (229 mm)	1-1/8" (29 mm)	6-1/2" (165 mm) 7-1/2" (191 mm)
5102-16	Canvas Tool Bag - 16"		5102S	Straps	1	16" (406 mm)	6" (152 mm)	14" (356 mm)
5102-22	Canvas Tool Bag - 22"		5102S	Straps	1	22" (559 mm)	6" (152 mm)	15" (381 mm)
5102-24	Canvas Tool Bag - 24"	Canvas - (natural) & vinyl (Brown)	5102S	Straps	1	24" (610 mm)	6" (152 mm)	15" (381 mm)
5105-20	High-Bottom Canvas Tool Bag- 20"		5102S	Straps	1	20" (508 mm)	6" (152 mm)	15" (381 mm)
5105-24	High-Bottom Canvas Tool Bag- 24"	-	5102S	Straps	1	24" (610 mm)	6" (152 mm)	15" (381 mm)
5102S	Adjustable Shoulder Strap Kit	Leather	Yes	N/A	N/A	N/A	N/A	N/A
5108-18	Deluxe Leather Bag	Leather	Included	Straps	N/A	18" (457 mm)	7" (178 mm)	8" (203 mm)
Tradesmai	n Pro™ Organizers							
5541610-14	10" Tote		Included	Open Top	30	12" (305 mm)	10" (254 mm)	10" (254 mm)
55419SP-14	Shoulder Pouch	-	Included	Zipper	16	10" (254 mm)	8" (203 mm)	5" (127 mm)
55421BP-14	Backpack	1680d ballistic nylon (Black ext./Orange int.)	Included	Zipper	39	18" (457 mm)	14" (356 mm)	7" (178 mm)
55452RTB	Rolling Tool Bag	- (Didok OAL/Ordingo IIIL)	No	Zipper	24	19" (483 mm)	12.5" (318 mm)	14" (356 mm)
55456BPL	Tech Backpack	-	Included	Zipper	25	14" (356 mm)	7" (178 mm)	18-1/2" (470 mm)









Tool Pouches

Cat. No.	Description	Material/Color	Belt Connection	Belt Width	Dimensions	Specialty Add-Ons
42241	6-Pocket Nail/Screw	Leather (natural)	Tunnel loop	3" (76 mm)	11" x 11-3/4" (279 x 298 mm)	Hammer loops (2)
5166	7-Pocket	Leather (white)	Tunnel loop	2-1/4" (57 mm)	7" x 9-1/2" (178 x 241 mm)	Chain tape thong
5164	8-Pocket	Leather (natural)	Slots	2" (51 mm)	6-3/4" x 9-3/4" (171 x 248 mm)	Knife snap
5701	8-Pocket	Cordura® (Black)	Tunnel loop	2-1/2" (64 mm)	11" x 12" (279 x 305 mm)	
5164T	8-Pocket	Leather (natural)	Tunnel loop	2-1/2" (64 mm)	6-3/4" x 9-3/4" (171 x 248 mm)	Knife snap
5162T	8-Pocket Extra-Capacity	Leather (natural)	Tunnel loop	3" (76 mm)	8-1/2" x 10-3/4" (216 x 273 mm)	Knife snap, leather tape thong
5165	10-Pocket	Leather (natural)	Slots	2" (51 mm)	10" x 10" (254 x 254 mm)	Knife snap
5190	10-Pocket	Leather (natural)	Slots	1-3/4" (44 mm)	6" x 8-3/4" (152 x 222 mm)	Leather tape thong
5719	18-Pocket	Cordura® (Black)	Tunnel loop	2-1/2" (64 mm)	11" x 12" (279 x 305 mm)	Chain tape thong
5142	Utility Bag	Canvas (natural)	Loops	3" (76 mm)	9" x 10" x 8" x 3" (229 x 254 x 203 x 76 mm)	
5142P	Utility Bag with Interior Pocket	Canvas (natural)	Loops	3" (76 mm)	9" x 10" x 8" x 3" (229 x 254 x 203 x 76 mm)	
5141P	Utility Bag – Extra-Large	Canvas (natural)	Loops	3" (76 mm)	10" x 12" x 5" (254 x 305 x 127 mm)	
5416T	Bull-Pin/Bolt Bag	Canvas (natural)	Loops	3" (76 mm)	5" x 9" x 10" (127 x 229 x 254 mm)	Bull pin loops
5416TCP	Extra Tall Top Closing Bolt Bag	Canvas (natural)	Tunnel loop	3" (76 mm)	5" x 12" x 9" (127 x 305 x 229 mm)	
5416TC	Top Closing Bolt Bag	Canvas (natural)	Tunnel loop	3" (76 mm)	5" x 10" x 9" (127 x 254 x 229 mm)	



Tool Pouch & Belt Sets

Cat. No.	Description	Material /Color	Pockets	Components	Belt Width	Waist Size	Specialty Add-Ons
5710M	Electrician's Combo Set 4 Piece – Medium			F704 F700		32" - 36" (813 - 914 mm)	
5710L	Electrician's Combo Set 4 Piece – Large	Cordura® (Black)	27	5704, 5706, 5718, 5719	2" (51 mm)	36" - 40" (914 - 1016 mm)	Hammer Holder
5710XL	Electrician's Combo Set 4 Piece – Extra-Large			0710, 0713		40" - 44" (1016 - 1118 mm)	

 $\triangle \textbf{WARNING:}$ This is NOT an occupational protective belt.

 $\triangle \textbf{WARNING:}$ NOT for fall arrest or back support.

Tool Belts

Cat. No.	Description	Material /Color	Buckle Type	Belt Width	Waist Size
5201	Lightweight Tool Belt	Leather (natural)	Single-tongue	1" (25 mm)	33" to 45" (838 to 1143 mm)
5225	Adjustable Web Tool Belt	Polypropylene web (Black)	Slide-action	2" (51 mm)	48" (1219 mm)
5202XL	General-Purpose Belt – Extra-Large	Leather (natural)	Single-tongue	1-1/2" (38 mm)	46" to 54" (1168 to 1372 mm)
5207L	Electrician's Tool Belt – Large	Leather (natural)	Single-tongue	1-1/2" (38 mm)	38" to 46" (97 to 117 cm)
5415L	Heavy-Duty Embossed Tool Belt – Large	Leather (natural)	Double-tongue	2" (51 mm)	40" to 48" (1016 to 1219 mm)



AWARNING: This is NOT an occupational protective belt.

AWARNING: NOT for fall arrest or back support.

Tool Holder

Cat. No.	Description	Material / Color	Belt Connection	Belt Width	Dimensions	For Use With
5101	Scissors Holder	Leather (black)	Tunnel	Up to 1-1/2" (38 mm)	2" to 7" (51 to 178 mm)	Klein Electrician's Scissors (Cat. Nos. 2100-5 and 2100-7)



Voice, Data, Video Installation Kit

Cat. No.	Description	Includes
VDV011-832	VDV ProTech™ Coaxial Kit	Case with 12 organizational compartments Coax Cable Stripper - 2-Level (VDV110-061) Compression Crimper (VDV211-048) Multi-Cable Cutter Klein-Kurve [®] (63020) 10-pack - Universal F Connectors - R659 (VDV812-615) 10-pack (2x) - Universal F Connectors - R66/60 (VDV812-606) 10-pack (2x) - F Connectors - R66 (VDV812-628) 10-pack - Universal BNC Connectors - R66/60 (VDV813-616) 10-pack - Universal BNC Connectors - R66/60 (VDV813-607)



Radial Strippers

Cat. No.	Description	Cable Type	Color	Level(s)	Strip/Slit Dimensions	Overall Length
VDV110-061	Coax Cable, 2-Level	RG59, RG6, RG6-QS	Yellow/Black	2	0.313" & 0.250" (7.94 & 6.35 mm)	4.4" (112 mm)
VDV110-095	Coax Cable, 2-Level	RG59, RG6, RG6-QS, RG7, RG11	Yellow/Gray	2	0.313" & 0.250" (7.94 & 6.35 mm)	5-1/4" (133 mm)
VDV110-261	Twisted Pair	CAT3, CAT5/5e, CAT 6/6A	Yellow/Blue	1	2" (51 mm) - Strip length varies by application	4-3/4" (121 mm)
VDV110-295	Coax Twisted Pair	RG59, RG6/RG6Q; CAT3, CAT5/5e, CAT6/6A	Yellow/Blue	2	0.313" & 0.250" (7.9 & 6.4 mm) Strip length varies by application	5-1/4" (133 mm)



Compression Crimpers, Connectors & Cutters

Cat. No.	Description	Cable Type	Strips and Cuts	Color	Connectors	Overall Length
VDV211-048	Compact, Multi-Connector	Coaxial	N/A	Yellow/Black	Coax F	5.6" (142 mm)
VDV211-063	Lateral, Multi Connector	Coaxial	N/A	Yellow/Chrome	BNC, F, RCA	6.3" (158 mm)
VDV211-100	Extended Reach Coaxial	Coaxial	N/A	Yellow/Black	BNC, F, RCA	9" (229 mm)
VDV226-005	Compact Pass-Thru Crimper	Twisted Pair (STP/UTP)	N/A	Yellow/Black	RJ45, Klein Pass-Thru™ Connectors	5-1/2" (142 mm)
VDV226-110	Pass-Thru™ Modular	Twisted Pair (STP/UTP)	STP/UTP & Flat Satin Phone Cable	Yellow/Black	RJ11/RJ12 Standard; Klein Pass-Thru™ Connectors	6-3/32" (155 mm)
Cat. No.	Description	Cable Type	Position/Contacts	Color	Connectors	Package Qty
Connectors	;					
VDV826-763	Pass-Thru™ Data Plugs	CAT5e	8P 8C	Clear	RJ45	200
Cat. No.	Description	Cuts	Cutting Knives		Handle Type/Color	Overall Length
Cable Cutte	er					
VDV600-096	Coaxial Cable Cutter - CCS	RG59, RG6, RG6Q, RG7, RG11 Twisted Pair	Custom Notch for CO Standard Shears for		Plastic-Dipped/Yellow	8.4 oz. (238 g)











Punchdown Tools

Cat. No.	Description					
VDV427-822	Cushion-Grip Impact Punchdown Tool Kit – includes the following (items also sold separately)					
Cat. No.	Description	Configuration End 1	Configuration End 2	Color	Overall Length	
VDV427-821	Impact Punchdown Tool	110 Terminate and Cut	66 Terminate and Cut	Black/Yellow	8-1/4" (206 mm)	
VDV427-104	Dura-Blade™ Punchdown Blade	110 Terminate and Cut	66 Terminate and Cut	Chrome	2-13/64" (56 mm)	
VDV327-103	Wire Pick	Metal Hook	Non-Conductive Spudger	Yellow	7-1/4" (184 mm)	



















Voice, Data, Video Test Equipment

,	,,			VDV5U1-828			
Cat. No.	Description	Supported Remotes	Connection & Adapter Types	Tone Generator	Cable ID	Test & Measure Types	Includes
VDV500-051	TONEcube – Tone Generator		RJ11, Coax RJ45	5		Yes	9V Battery
VDV500-060	PROBEplus – Tone Tracing Probe		RJ11, Coax RJ45	No		No	9V Battery
VDV500-808	TONEcube & PROBEplus		RJ11, Coax RJ45	5		No	9V Battery
VDV512-007	Pocket Continuity Tester		RG59, RG6, RG6Q	1		• OpenFault • Short Fault • Good	Red remote AAA Battery
VDV512-101	Coax Explorer® 2 with Remote Kit		RG59, RG6, RG6Q	1		• Open Fault • Short Fault • Good	Removable snap-on remote holder 4 color-coded push-on remotes F-adapter AAA Batteries (2)
VDV526-052	LAN Scout Jr. Continuity Tester		Cat5e, Cat6, Cat6A	4		MiswireOpen FaultShort FaultSplit Pair	• Self-storing remote • 6V to 4 x LR44 Alkaline Battery
VDV501-823	VDV Scout® Pro 2 Tester Kit	CoaxMap™ ID LanMap™ ID	Coax F, RJ45	4	Supports up to 19	Continuity Miswire Open & Short Fault Split Pairs Shield	Tester (VDV501-098) LanMap™ Remotes (5) CoaxMap™ Remotes (5) Coax Barrel F Adapter 9V Battery Case
VDV501-825	VDV Scout® Pro 2 LT Tester Remote Kit	CoaxMap™ ID Test-n-Map™ LanMap™ ID	Coax F, RJ45	4	Supports up to 19	Continuity Miswire Open & Short Fault Split Pairs Cable Length Shield	Tester (VDV501-108) Test-n-Map™ Remote (1) LanMap™ Remotes (19) CoaxMap™ Remotes (19) Coax Barrel F Adapter Sy Battery Case
VDV501-826	VDV Scout® Pro 2 LT Tester & Test-n-Map Remote Kit	CoaxMap™ ID Test-n-Map™ LanMap™ ID	Coax F, RJ45	4	Supports up to 19	Continuity Miswire Open & Short Fault Split Pairs Cable Length Shield	Tester (VDV501-108) Test-n Map™ Remotes (8) Goax Barrel F Adapter Coax Push-on F Adapter (8) RJ45 Jumper Test Cables (8) 9V Battery Case
VDV501-828	VDV Commander™ Test Kit	CoaxMap™ ID Test-n-Map™ LanMap™ ID	Coax F, RJ45	4	Supports up to 20	Continuity Miswire Open & Short Fault POE Split Pairs Cable Length Shield	Test-n-Map Remote (1) LandMap™ Remotes (5) CoaxMap™ Remotes (5) Test cables Coax adapter AA Batteries (6) Case
VDV501-829	VDV Commander™ Test & Map	CoaxMap™ ID Test-n-Map™ LanMap™ ID	Coax F, RJ45	4	Supports up to 20	• Continuity • Miswire • Open & Short Fault • PoE • Cable Length • Split-Pairs • Shield	Test-n-Map Remote (1) PROBEplus (ToneTracing Probe VDV500-060) LanMap™ Remotes (20) CoaxMap™ Remotes (20) Coax adapter Batteries: AA (6), 9V Case

Description

Accessories

VDV770-834 VDV Commander™ Test-n-Map™ Remote Kit

(7) Test-n-Map™ Remotes, (8) Coax Push-on F Adapter, (8) 9° RJ45 Jumper Test Cables, (2) 9° RJ11/RJ12 Jumper Cables, 18' Verification Cable









Fish Tapes

Cat. No.	Tape Length	Tape Width	Tip Type	Case Diameter	Laser Etched	
Steel Fish						
56001	50' (15 m)	1/8" (3 mm)	Offset-bent	7" (178 mm)	Yes	
56002	65' (19 m)	1/8" (3 mm)	Offset-bent	9" (229 mm)	Yes	
56003	125' (38 m)	1/8" (3 mm)	Offset-bent	13" (330 mm)	Yes	
56004	240' (73 m)	1/8" (3 mm)	Offset-bent	13" (330 mm)	Yes	
Fiberglass Fish Tape						
56010	100' (30 m)	3/16" (5 mm)	Eyelet with 7" spiral leader	13" (330 mm)	Yes	
56014	200' (60 m)	3/16" (5 mm)	Eyelet with 7" spiral leader	17" (432 mm)	Yes	
56059	200' (60 mm) Multi-Groove	3/16" (5 mm)	Eyelet with 7" non- conductive leader	17" (432 mm)	No	
Cat. No.	Description		Container		Weight	
Wire Pull	ing Accessories					
56110	Poly Pull Line with Orange Tra	icer 6500'	Five-Gallon Bucket		11 lbs. (5 kg)	









⚠WARNING: Never remove screws while fish tape is coiled inside reel.

Fish Rods

Cat. No.	Description	Set Contains		Material		
56418	18' (5.5 m) Hi-Flex Glow Rod Set	(3) 5/32" (4 mm) diameter 6' (1.83 m) glow rods hook attachments	(3) $5/32^{\circ}$ (4 mm) diameter 6° (1.83 m) glow rods with bullet nose and hook attachments			
56430	30' (9.1 m) Glow Rod Set	(6) 5' (1.5 m) Glow Rods with Bullet Nose, Hook, LED-Illuminated Tip Attachments	and	Fiberglass Rods Coated with Splinter Guard		
56400	Splinter Guard™ Fish/Glow Rod Kit	2) low-flex 48" rods, (2) mid-flex 18" glow rods, (7) rods, (2) high-flex 72" glow rods; (7) Attachments including Double S-hook, Bullet Nose, Chain, Mag Twin Hook, Whisk; Carrying Case (Cat. No. 56401	Fiberglass Rods Coated with Splinter Guard			
56401	Fish Rod Bag with Shoulder Bag	Adjustable bag fits rods 48" to 72"	PVC-coated polyester			
56511	Fish Rod Attachment Set	(7) Attachments compatible with all Klein Tools' fi S-hook, Bullet Nose, Chain, Magnet, Single Hook,	Plastic Case			
Cat. No.	Description	Set Contains	Compact Length	Extended Length		
SRS56036	WIRESPANNER Plus™ Telescopic Pole	Large Hook Attachment, Padded Shoulder Strap	32" (813 mm)	18' (5.5 m)		
SRS56037	Magnetic Wire Pulling System	Swivel leader eyelet, Non-marring nylon leader-pull with heavy-duty nylon rope eyelet N/A for wire tie-on		20' (6.1 m)		
SRS56980	Deluxe Fish Rod Set, 19 Pieces	10 Rods, 8 Attachments, 1 Carrying Tube	N/A	33' (10 m)		
SRS56981	Mega Fish Rod Kit, 34 Pieces	13 Rods, 3 Swivel Rods, 12 Attachments, 5 Glow Attachments, 1 Carrying Tube	N/A	52' (16 m)		



Wrenches

MIGII	61162			
Cat. No.	Description	Range	Overall Length	
57005	3/8" Torque Wrench Square Drive	30 to 250 in. lb. (40.7 to 338.9 Nm)	10-5/8" (270 mm)	
Cat. No.	Description	Includes		
65504	3/8" 6-Point and 12-Point Socket Set, 12-Piece	(4) 6-point sockets: 3/8", 7/16", 1/2", and 9/16" (Spark plug socket (2) Extensions: 1-3/4" (44 mm		
Cat. No.	Description	Size/Capacity	Overall Length	
68005	Can Wrench	3/8" (9.5 mm) and 7/16" (11.1 mm) Hex Nut, 1" Handle Diameter	7" (178 mm)	
68461	Open-End Wrench	3/8" (9.5 mm) and 7/16" (11.1 mm)	6" (152 mm)	
3146B	Bell System Type	3/8" (9.5 mm) and 7/16" (11.1 mm)	13" (330 mm)	
Cat. No.	Description	Features	Overall Length	
Lineman	Wrenches			
KT151T	Lineman's Ratcheting	3/4", 1" & 1-1/8" combination square bolt-through socket design	13" (330 mm)	
KT152T	Lineman's Slim Ratcheting	3/4", 13/16", 1" and 1-1/8" combination square socket for most common utility hardware	13-1/4" (337 mm)	
Cat. No.	Length	Capacity	Handle Finish	Handle Color
Adjustabl	e Wrenches			
506-15	15-7/8" (403 mm)	1-11/16" (43 mm)	High-Polish Chrome	Chrome
D507-6	6-1/2" (165 mm)	15/16" (24 mm)		
D507-8	8-1/4" (209 mm)	1-1/8' (28 mm)	- Diactic Diagod	Transparent Dad
D507-10	10-1/4" (260 mm)	1-5/16" (33 mm)	- Plastic-Dipped	Transparent Red
D507-12	12-3/8" (314 mm)	1-1/2" (38 mm)	=	













See our complete line of **Telecom Products www.kleintools.com**





