



# LUBRIPLATE®

## MATERIAL SAFETY DATA SHEET

### Section 1

**PRODUCT NAME OR NUMBER**

LUBRIPLATE Chain &amp; Cable Fluid (AEROSOL)

**FORMULA**

Mineral Oil, Additives and Propellant

**GENERIC/CHEMICAL NAME:**

Petroleum Lubricating Oil

**USDA AUTHORIZATION:**

H-2

**Manufacturer's Name**

Fiske Brothers Refining Co.

**Address**

1500 Oakdale Ave., Toledo, Ohio 43605 - 129 Lockwood St., Newark, NJ 07105

**Emergency Telephone Number**

1-800-255-3924 - CHEM-TEL (24 hour)

**Telephone Number for Information**

419-691-2491 - Toledo Office

### Section 2 - Hazardous Ingredients/Identity Information

Hazardous Components	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Oil Mist in Air	5mg/m <sup>3</sup>	5mg/m <sup>3</sup>		
O-Dichlorobenzene (95-50-1)	C-300 mg/m <sup>3</sup>	150 mg/m <sup>3</sup>		<4
Propane (74-98-6)	1000 ppm	1000 ppm		20

\* ACGIH - LISTED AS SIMPLE ASPHYXIANT (See Section III)

**Hazardous Material Identification System (HMIS):** Health - 1, Flammability - 4, Reactivity - 0  
**Not a Controlled Product under (WHMIS) - Canada** Consumer Commodity  
**Special Protection:** See Section 9

### Section 3 - Health Hazard Data

**Threshold Limit Value** PEL for Ortho-dichlorobenzene: C-300mg/m<sup>3</sup> TLV for oil mist = 5mg/m<sup>3</sup>**Effects of Overexposure** Inhalation is the most likely method of exposure. Minimal effects are expected at levels below the TLV of components. Dizziness, drowsiness, coughing, nasal or throat irritations at higher levels. Propane may act as a simple asphyxiant without other significant physiologic effects if the oxygen content is low. It is reported that O-Dichlorobenzene can cause liver and kidney damage in test animals.**Carcinogenicity:** NTP? No IARC Monographs? No OSHA Regulated? No

### Section 4 - Emergency and First Aid Procedures

**EYE CONTACT:** Flush with clear water for 15 minutes or until irritation subsides. If irritation persists, consult a physician.**SKIN CONTACT:** Remove any contaminated clothing and wash with soap and warm water.**INHALATION:** Remove to fresh air. If breathing has stopped, administer artificial respiration. Get medical help immediately.**INGESTION:** If ingested, call a physician immediately. Do not induce vomiting.

### Section 5 - Fire and Explosion Hazard Data

**Flash Point (Method Used)** Propellant <0°F**Flammable Limits****LEL** 0.9%**UEL** 9.5%**Extinguishing Media**

Foam, Dry Chemical, Carbon Dioxide.

**Special Fire Fighting Procedures**

Keep containers cool. Use air-supplied breathing equipment for enclosed or confined spaces. Use shielding to protect personnel against bursting containers.

**Unusual Fire and Explosion Hazards**

Do not spray near open flame. At elevated temperatures (over 130°F.), aerosol containers may vent, burst, or rupture.

**PRODUCT NAME OR NUMBER - LUBRIPLATE Chain & Cable Fluid (AEROSOL)****Section 6 - Physical/Chemical Characteristics**

<b>Boiling Point</b>	(Aerosol) N/A	<b>Specific Gravity (H<sub>2</sub>O = 1)</b>	0.93
<b>Vapor Pressure (mm Hg.)</b>	Aerosol @ 130°F. - 80 psig	<b>Melting Point</b>	Spray
<b>Vapor Density (AIR = 1)</b>	>1	<b>Evaporation Rate (Butyl Acetate = 1)</b>	Faster
<b>Solubility in Water</b>	Insoluble		
<b>Appearance and Odor</b>	Off white mist with additive odor from aerosol can.		

**Section 7 - Reactivity Data**

<b>Stability</b>	Unstable	<b>Conditions to Avoid</b>	Avoid spraying into open flame or onto red hot surfaces.
<b>Incompatibility (Materials to Avoid)</b>	Stable X Strong oxidizers.		
<b>Hazardous Decomposition or Byproducts</b>		May form Carbon Monoxide, Hydrogen Chloride.	
<b>Hazardous Polymerization</b>	May Occur	<b>Conditions to Avoid</b>	N/A
	Will Not Occur X		

**Section 8 - Spill or Leak Procedures****Steps to be taken in case material is released or spilled**

Remove sources of ignition, ventilate area. Use appropriate safety equipment to enter area. Allow time for vapors to be below their TLV. Add oil absorbent and clean area. Keep petroleum products out of sewers and water courses.

**Waste disposal method**

Do not puncture or incinerate containers. Give empty, leaking or full containers to a disposal service equipped to safely handle and dispose of pressurized containers.

**SARA/TITLE III, Section 313 Status - 1,2 - Dichlorobenzene - <4%****Section 9 - Special Protection Information**

**Respiratory Protection (Specify type)** Need approved organic vapor mask if TLV is exceeded.

**Ventilation**      **Local Exhaust**      Use for fumes & to maintain below TLV value.      **Special** N/A  
                    **Mechanical (General)**                     **Other** N/A

**Protective Gloves** Use oil-impervious gloves.      **Eye Protection** Use goggles or face shield.

**Other Protective Equipment** Use oil-resistant apron, if needed.

**Section 10 - Special Precautions****Precautions to be taken in handling and storing**

Store in cool, dry area out of direct sunlight. Do not puncture or incinerate, or heat full or empty containers above 130°F.

**Other Precautions**

Please read and follow the directions on the product label. Keep away from children.

**The above information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Fiske Brothers Refining Company. The data on these sheets relates only to the specific material designated herein. Fiske Brothers Refining Company assumes no legal responsibility for use or reliance upon this data.**