

GENERAL DESCRIPTION: Larsen's heavy gauge extinguisher, fire hose, and fire department valve cabinets provide an effective method of securing fire protection equipment for all types of detention facilities. Available as fully recessed, semi-recessed or surface-mounted cabinets, these units feature one piece solid doors with matching trim and heavy gauge continuous piano hinges. These features, combined with security locks, fire extinguishers, valves, and hose rack units, offer a high level of fire protection for any detention facility.



When specifying Larsen's "Flame-Shield" fire-rated cabinet option for the DEC, DVC or DHC Series, refer to the dimension chart at right and select from the models with an "FS" prefix. As is the case with non-rated detention valve and hose cabinets, no knock-outs are provided with the fire-rated detention valve and hose cabinets. Pipe holes must be drilled by the installer and complete instructions are supplied with each fire-rated valve and hose cabinet. For complete details of the "Flame-Shield" option, see page 4.

BOX SPECIFICATION: All recessed, semi-recessed and surface-mounted cabinets feature 12 gauge cold-rolled steel boxes. Cabinets with stainless steel trim and door have a box constructed entirely of 12 gauge, 304 stainless steel. Surface-mounted stainless boxes have industrial matte finish.

TRIM AND DOOR SPECIFICATION: Steel trims and doors are manufactured entirely from 12 gauge cold-rolled steel. The doors are one piece construction. Stainless steel trims and doors feature the same construction using 12 gauge 304 stainless steel with industrial matte finish.

TO SPECIFY:

1. Insert, after "DEC", "DVC" or "DHC", the appropriate prefix for the trim and door material. Use "S" for 12 gauge steel and specify white or red finish. Use "SS" for 12 gauge stainless steel.
2. Select the required model number from the dimensional chart based on wall depth and interior capacity.
3. Select **"DETENTION LOCK"** (page 12).
4. OTHER OPTIONS: Die-cut lettering (page 12), fire-rated option (page 4), recessed handle (page 12).

DIMENSIONS*

Model Number	Trim Style	Inside Box Dimensions H x W x D	Outside Trim Dimensions H x W	Rough Opening H x W x D	Interior Capacity
DEC2409-R	Rec. Flat	23¼ x 9¼ x 6¾	27¼ x 13	25 x 10½ x 7¼	MP2½, MP5, MP5-A, MP6, MP10, DC5, DC6, DC10, CD5, HT2½, HT5
FS DEC2409-R	Rec. Flat	23¼ x 9¼ x 6¾	27¼ x 13	25¼ x 11¼ x 8¼	
DEC2409-R4	Semi-Rec. ** 3½	23¼ x 9¼ x 6¾	27¼ x 13	25 x 10½ x 4½	
FS DEC2409-R4	Semi-Rec. ** 3½	23¼ x 9¼ x 6¾	27¼ x 13	25¼ x 11¼ x 5¼	
DEC2409-SM	Surface Mtd.	26¼ x 12¼ x 6¾	27¼ x 13	—	MP20, DC20, WC6-L, WC2½, PW2½, WM2½, CD10, HT11, HT15½
DEC2712-R	Rec. Flat	26¼ x 11¼ x 8¼	30¼ x 15½	28 x 13 x 8¼	
FS DEC2712-R	Rec. Flat	26¼ x 11¼ x 8¼	30¼ x 15½	28¼ x 13¼ x 9¼	
DEC2712-SM	Surface Mtd.	29¼ x 14¼ x 8¼	30¼ x 15½	—	
DVC1818-R	Rec. Flat	17¼ x 17¼ x 8¼	21¼ x 21¼	19 x 19 x 8¼	One 2½" Fire Dept. Valve w/ Cap & Chain
FS DVC1818-R	Rec. Flat	17¼ x 17¼ x 8¼	21¼ x 21¼	19¼ x 19¼ x 9¼	
DVC1818-SM	Surface Mtd.	20¼ x 20¼ x 8¼	21¼ x 21¼	—	One Hose Rack with 100' of Rack Hose
DHC2634-R	Rec. Flat	33¼ x 25¼ x 8¼	37¼ x 29¼	35 x 27 x 8¼	
FS DHC2634-R	Rec. Flat	33¼ x 25¼ x 8¼	37¼ x 29¼	36¼ x 28¼ x 9¼	One Hose Rack Unit with 100' of Rack Hose and a Fire Extinguisher
DHC2634-SM	Surface Mtd.	36¼ x 28¼ x 8¼	37¼ x 29¼	—	
DHC3234-R	Rec. Flat	33¼ x 31¼ x 8¼	37¼ x 35¼	35 x 33 x 8¼	
FS DHC3234-R	Rec. Flat	33¼ x 31¼ x 8¼	37¼ x 35¼	36¼ x 34¼ x 9¼	
DHC3234-SM	Surface Mtd.	36¼ x 34¼ x 8¼	37¼ x 35¼	—	

* Other sizes available, contact factory.

** Semi-recessed DEC 2409-R4 and FS DEC 2409-R4 cabinets have 3½" SQUARE trims.

FIRE BLANKET CABINETS

Larsen's fire blanket cabinets are all equipped with a 62" x 80" fire blanket fabricated of a rugged blend of reprocessed wool. These fire retardant blankets meet federal specification #CS-191-53. Larsen's fire blanket cabinets are available in the three following designs:

FB 68-6 SERIES: Fire blanket is attached to a roller and can be rapidly released by placing one's arm through the arm loop and turning into the blanket. This surface mounted unit is constructed of cold-rolled steel with a standard finish of red baked acrylic enamel, and as an option, the cabinet can be fabricated entirely of stainless steel (Model SS FB 68-6).

FB 1016 SERIES: Drop Type, surface mounted cabinet, constructed of cold-rolled steel with a red baked acrylic enamel finish. The folded blanket is always visible through the viewing knockout on the front and is quickly available by releasing the hinged bottom of the cabinet.

FB 3612 SERIES: Exclusive combination fire extinguisher and fire blanket cabinet, which is identical to the Architectural Series model 3612 (see pages 6 – 7) except

for the blanket shelf located 9" down from the top of the cabinet, leaving 27" for the extinguisher height. Please consult pages 6 and 7 for wall mounting, trim and door material, and appropriate door style options. The unit is also available with Gemini door styles (model G FB 3612 — see page 8), with "Fire Extinguisher" (vertical) and "Fire Blanket" (horizontal) lettering. If specified, "Fire Extinguisher" and "Fire Blanket" decals or die cut lettering are available with the appropriate door styles pictured on page 6. For steel door and trim units, white baked acrylic enamel is the standard color. Red is available if specified.

DIMENSIONS

Model Number	Trim Style & Projection	Inside Box Dimension H x W x D	Rough Opening H x W x D	Complies with ADA?
FB3612-R	Rec. — 5/16	36 x 12 x 8	37 x 13 x 8¼	YES
FS FB3612-R	Rec. — 5/16	36 x 12 x 8	38¼ x 14¼ x 9¼	YES
FB3612-RK	Semi-Rec. 1¼	36 x 12 x 8	37 x 13 x 7¼	YES
FS FB3612-RK	Semi-Rec. 1¼	36 x 12 x 8	38¼ x 14¼ x 8¼	YES
FB3612-RL	Semi-Rec. 2½	36 x 12 x 8	37 x 13 x 6	YES
FS FB3612-RL	Semi-Rec. 2½	36 x 12 x 8	38¼ x 14¼ x 7	YES
FB3612-RM	Semi-Rec. 4¼	36 x 12 x 8	37 x 13 x 4	♦
FS FB3612-RM	Semi-Rec. 4¼	36 x 12 x 8	38¼ x 14¼ x 4¼	♦
FB3612-RT	Trimless	36 x 12 x 8	—	YES
FB3612-SM	Surface Mtd.	39¼ x 15¼ x 8	—	♦
FB3612-RA	Semi-Rec. 4	36 x 12 x 8	37 x 13 x 4¼	♦♦
FS FB3612-RA	Semi-Rec. 4	36 x 12 x 8	38¼ x 14¼ x 5¼	♦♦
FB68-6	Surface Mtd.	68 x 6¼ x 4	—	♦
FB1016	Surface Mtd.	10 x 16 x 8	—	♦



FB 68-6



FB 1016



AL G FB 3612
RED DOOR
WHITE LETTERS

FB 3612

NOTE: "FS" models denote Larsen's "Flame-Shield" fire-rated cabinets. When specifying Larsen's "Flame-Shield" fire-rated cabinet option for the Fire Blanket Cabinets, refer to the dimension chart at left and select from the models with an "FS" prefix. For complete details of the "Flame-Shield" option, see page 4.

- ♦ To comply with ADA wall projection guidelines, this cabinet must be mounted with its leading edge at or below 27" from the finished floor.
- ♦♦ To comply with ADA wall projection guidelines, this cabinet must specified with Larsen's recessed handle (see page 12).