

OVERHEAD CONCEALED CLOSERS

Single Acting, for Doors Hung on Center Pivots


202 CP Nos. 204 CP 206 CP

The basic overhead concealed closer adapted to center pivot hanging of door, which must have top members at least 134" thick. Door may be of wood, metal or tempered glass. Especially suitable for batteries of doors without mullions. Easy to regulate without removing any part. Closer may be removed without taking door down.

Top and bottom ball-bearing pivots of bronze, essential parts drop-forged, included with closer. Door may open 130°, jamb permitting. Hydraulic back-check protects walls, furniture, etc. A door stop is required if traffic tends to "ride" the door (see p. 3, sec. 9). Hold-open available; may be set to hold at any one of the following door positions: 85°, 90°, 100° or 110°.

Exposed parts in prime coat or in choice of LCN finishes, page 43. In ordering please note "How to Order," page 3, and give full information.

TYPES OF DOORS AND MAXIMUM WIDTHS for which these closers are designed (wood or metal or tempered glass)			CLOSER NO.		Shipping Weight
Entrance and Vestibule		Interior	With REGULAR	With HOLD-OPEN	Approxi- mate
INswinging	OUTswinging		Arm	Arm	
	_	3′0″	202 CP	202 CP-H	28 lbs.
2'6"	2′10″	3′6″	204 CP	204 CP-H	28 lbs.
3'2"	3'6"	4′0″	206 CP	206 CP-H	34 lbs.



Phantom drawing shows an LCN series 200 CP closer with center-pivot-hung door. Closer and upper pivot are concealed in head frame. Much used for tempered glass doors with metal top and bottom members 13/4" thick.

