

EPIC–Euro Profile Interchangeable Core

Medeco EPIC-Euro Profile cylinders are designed to accept a special, slab-sided, small format interchangeable core (SFIC) cylinder to retrofit into most standard European Profile applications.

Medeco Euro profiles can be furnished with Medeco's patented X4 technology, offering unmatched key control, the widest array of retrofit cylinders and four times the master keying capability.



Patented Key Control

Protects against unauthorized duplication of your keys.



Uses Existing Hardware

European profile cylinders retrofit into virtually any manufacturers' locksets requiring DIN Standard cylinders.



Superior Master Keying Capability

Furnished with Medeco X4 SFIC, EPIC offers superior master keying to accommodate very large systems.

Medeco X4 Technical Information

- 6 and 7 Pin cylinders available
- Solid nickel silver pins
- Many cylinder formats available
- Profile cylinders available in multiple sizes, finishes and functions
- Where interchangeable core is not required, Euro profile cylinders are also available in modular components and assembled standard lengths.
- Solid brass construction provides high quality and long cylinder life
- Solid nickel silver pins and keys
- European Profile Cylinders retrofit into virtually any manufacturers' locksets equivalent to DIN Standards
- For the highest grade of protection, Euro Profile cylinders and Ovals – should be installed with hardened escutcheons

Warranty

Warranted for (2) years against manufacturing defects. See Medeco Limited Warranty for full details.

EPIC–Euro Profile Interchangeable Core

Description	Part Number
6 Pin Part Numbers	
EPIC Euro Double 37.9 mm/37.9mm	2326D21
EPIC Euro Half 37.9mm	2326H01
EPIC Euro with Thumbturn 40mm int/39.2 mm ext	2326S12X*
Small Format Interchangeable Core (SFIC)	3360000R (P)
Small Format Interchangeable Core (SFIC)	3360000R (S)

7 Pin Part Numbers

EPIC Euro Double 41.73mm/41.73mm	2324D21
EPIC Euro Double 41.73mm/55mm	2324D25
EPIC Euro Half 41.73mm	2324H01
EPIC Euro Half 55mm	2324H05
EPIC with Thumbturn 40mm int/43mm ext	2324S12X
EPIC with Thumbturn 40mm int/55mm ext	2324S15X
EPIC with Thumbturn 55mm int/43mm ext	2324S52X
Small Format Interchangeable Core (SFIC)	3370000R (P)
Small Format Interchangeable Core (SFIC)	3370000R (S)

* X denotes thumb turn. Please see following page for thumb turn. EPIC sold less cylinder.

(P) = Pinned (combined)

(S) = Sub-assembled (uncombined)

Surcharges for Master Keying, Custom Coining and Custom Stamping apply, see page 196.
Refer to the XT and CLIQ Intelligent Key sections for format availability and pricing.

How To Order International Cylinders - Euro-Profile

<p>1</p> <p>23130 05500 base part # example</p> <p>Refer to pages 178-180 for descriptions and technical specifications to find the corresponding base part number.</p>	<p>2</p> <p>H technology</p> <p>H = M4 P = M4 BiLevel T = M³ J = M³ BiLevel S = M³ CLIQ W = Biaxial - = Original K = KM C = Classic CLIQ N = X4 M = X4 CLIQ</p>	<p>3</p> <p>05 finish</p> <p>Refer to the inside back cover of this catalog for finish options.</p>	<p>4</p> <p>M4 keyway</p> <p>Insert keyway if known or contact Customer Service for help.</p>	<p>5</p> <p>P pinning</p> <p>S = Sub-Assembled (Uncombined) N = Sub-assembled, - No side pins (M4 only) - No slider (M3 only) P = Pinned (Combinated) M = Master Keyed R = Master Keyed - blade and side pins (Medeco 4 only)</p>	<p>6</p> <p>624 side pin code (Medeco 4 only)</p> <p>Insert side pin code if known or contact Customer Service for help.</p>
---	---	--	--	--	--

BUILD A BASE PART #:

23130 X X X X X X

International Cylinder ———┐

Profile Design —————┐

Function —————┐

- *0 = Thumbturn Cylinder with "SR" Round Knob
- 1 = Half Cylinder
- 2 = Double Cylinder*
- *3 = Thumbturn Cylinder with Low Profile "LP" Knob
- *4 = Thumbturn Cylinder with Decorative "RD" Knob
- *5 = Thumbturn Cylinder with Lever "RL" Knob
- *6 = Thumbturn Cylinder with "CR" Crescent Knob
- *7 = Thumbturn Cylinder with "SP" Spade Knob
- *L = Thumbturn Cylinder with "L" Less Knob

Number of Pins —————┐

- 5 = 5 Pins
- 6 = 6 Pins
- 7 = 7 Pins

*Not available in M3 & M4 BiLevel

Interior/Exterior Length Extensions

0 = No Extension	5 = 25 mm (.984")
1 = 5 mm (.197")	6 = 30 mm (1.18")
2 = 10 mm (.394")	7 = 35 mm (1.38")
3 = 15 mm (.591")	8 = 40 mm (1.57")
4 = 20 mm (.787")	9 = 45 mm (1.77")

Cam Position
(from outside with bible down)

- 1 = 1 o'clock
- 2 = 10 point multi-gear
- 3 = EuroLine Module
- 5 = 5 o'clock
- 7 = 7 o'clock
- 8 = Multiposition (half cylinder only)
- 0 = 11 o'clock

*Thumbturn/Cam position available at 5 and 11 o'clock only

Assembly Variation for the BiLevel with Original Technology

- H = High Security
- B = Standard Security
- J = Standard Security all except Double Euro Profile