




ENGINEERED FOR MOTION

Contact Information

MS Sedco
8701 Castle Park Drive
Indianapolis, IN 46256
Phone: (317) 842-2545
Fax: (317) 849-3387
Email: custsvc@mssedco.com
www.mssedco.com

ACCESSORY #1



Product Name

MS-BDB Optional Mounting Bracket

Product Description

The MS-BDB is an optional mounting device that allows the installer to elevate and rotate the microstar-M for special configurations.

ACCESSORY #2



Product Name

MSRC (Optional Rain Cover)

Product Description

The MSRC is a rain cover designed

for use with the microStar-M sensors on installations that require protection from direct rainfall. The MSRC is made of black polycarbonate plastic..

ACCESSORY #3



Product Name

DH-BDB Bracket/Backplate

Product Description

BASIC USE

The DH-BDB is an optional bracket used to swivel mount the DH400 sensor for unique or industrial door applications.

ACCESSORY #4



Product Name

DHRC Rain Cover


Product Description

BASIC USE

The DHRC is a rain cover designed for use with the DH-series sensors on installations that require protection from direct rainfall. The DHRC is made of tinted plastic.

Sensor Accessories

ACCESSORY #5



Product Name

GDB Bracket
(Pictured With GD11S)

Product Description

BASIC USE

The GDB is an optional stand-off type bracket designed to allow our GD11S surface mount beams to clear garage door track hardware (shown with GD11S).

ACCESSORY #6



Product Name

12024 Open Frame 24V AC Transformer

Product Description

BASIC USE

The 12024 transformer is a screw mount type transformer used to convert a 120V AC power supply to 24V AC low voltage.

Technical Data

- Screw Mount
- Open Frame
- 2 Wire Type
- Listing: UL recognized component

Specifications

Primary Rated Voltage/Frequency:
120V AC/60Hz

072015

No Load Secondary Voltage:

24V AC

Power:

24VA

Tolerance:


±0.5V

Thermal Cutoff: 125°C, 2A, 250V

Weight: 1.46 lbs. (663g)

Size: 2 1/4"W x 2 1/4"D x 2"H

ACCESSORY #7



Product Name

BRM Bridge Rectifier Module

Product Description

BASIC USE

The BRM is a bridge rectifier module that can be used to convert AC voltage to DC voltage for a variety of applications.

Specifications

Primary Rated Voltage/Frequency:
100V AC/60 Hz

Temperature:
-85°F to 30°F (-65°C to 150°C)

Weight:
Less than 0.5 lb.

Product Description

BASIC USE

The RIM is a relay isolation module that can be used in applications that could damage input or output connections on sensors, timing modules, or other low voltage devices. The relay on the RIM is rated to handle higher current that might be used for locks, alarms, or other electronic devices that exceed the ratings of standard relays.

- Terminal Block Simplifies Wiring
- Listing: UL Recognized Component

Specifications

Primary Rated Voltage:

24V DC/110V AC

Contact Current Rating:

15A @ 24V DC/110V AC

Minimum Load:

110mA @ 5V DC

Temperature:

-13°F to 158°F (-25°C to 70°C)

Weight:

Approx. 0.5 lb.

Availability & Cost

AVAILABILITY

Available internationally from manufacturer's authorized distributors; contact MS Sedco for the location of nearest distributor.

COST

Cost information on MS Sedco products is available from the manufacturer's authorized distributors.

Warranty

MS Sedco, Inc. guarantees this product to be free from manufacturing defects for one year from date of installation. Unless MS Sedco is notified of the date of installation, the warranty will be in

effect for one year from the date of shipment from our factory. If, during the first year, this product fails to operate and has not been tampered with or abused, the unit can be returned prepaid to the factory and be repaired free of charge. After one year, the unit will be repaired for a nominal service charge. **Limited warranty is in lieu of all other warranties, expressed or implied, including any implied warrantability of merchantability, no representative or person is authorized to assume for MS Sedco any other liability in connection with the sale of our products. All warranties are limited to the duration of this written limited warranty. In no event shall MS Sedco be liable for any special, incidental, consequential or other damage arising from any unclaimed breach of warranty as to its products or services.**

Maintenance

MS Sedco recommends that all maintenance and adjustments be performed by an AAADM Certified Technician.


Technical Services

MS Sedco's staff of factory trained sales and service personnel offer design assistance and technical support. Local distributors are also available to assist in selecting appropriate devices for specific uses and to provide onsite installation.

Filing Systems

- Sweet's
- Additional product information is available from the manufacturer upon request.

ACCESSORY #8



Product Name

RIM Relay Isolation Module