


National Guard Products Inc.

1-800-
647-7874



320 Automatic Door Bottom



This product is designed to fit in a 3/4" deep channel in the bottom of a Hollow Metal Door.

Installation Instructions

1. Cut door bottom 1/8" less than inside length of door channel. DO NOT EXTEND DROP BAR WHILE CUTTING. Do not cut from end with adjusting rod. MAXIMUM CUT door bottoms 36" and longer = 4", shorter than 36" should not be field cut - order net length.
2. Drill 1/4" hole for adjusting rod in center of hinge edge of door 1/2" on center from bottom of door.
3. Set adjusting rod for proper seal. To reduce drop, turn adjusting rod right; to increase drop turn left. Maximum drop = 1/2". CAUTION: When adjustment reaches maximum drop, rod will stop turning easily. Do not force beyond maximum 1/2" drop or damage will occur and void warranty.



UL 10C Positive
Pressure Tested
Gasketing Material
for Fire Doors. Also
Classified in accordance with
UBC 7-2 (1997).



UL10B
Gasketing
Materials for
Fire Doors.

Intended for Application to
Classified Steel type fire doors
rated up to and including 3
hours.

Smoke and Draft Control door
bottom (Category H) meets
requirements of UBC 7-
2(1997) part 2, NFPA 105,
IBC, and UL 1784 intended
for application to classified
"S" label doors. 1/09