



Self-Adhesive Silicone Gasketing



5050B Brown
5050C Charcoal
5050W White
5050T Tan
5050CL Clear



Silicone Bulb Fire and Smoke Seal



Edge Sealing System - Category "G" for 20 minute rated category B wood doors perimeter application up to:

single swing 4'0 x 8'0
pairs 8'0 x 8'0
use 9550 at the meeting edge of pairs




Smoke and Draft Control - Category "H"

Up to 3 hours steel fire doors
Up to 90 minutes wood fire doors



Meets requirements of ROHS Directive 2002/95/EC



Available in 17', 20', 21', 25' and 300' rolls.



2525B Brown
2525C Charcoal
2525W White
2525T Tan

Silicone Bulb Smoke Seal



Available in 17', 20', 21', 25' and 300' rolls.



5040B Brown
5040W White

Silicone Fin Smoke Seal

Available in 17', 20', 25', 300' rolls



5060B Brown
5060CL Clear

Silicone Fin Smoke Seal

Available in 17' and 21' rolls.



Adhesive specifications: Modified acrylic pressure sensitive adhesive protected by release liner. Provides high initial adhesion and long term holding power for permanent mounting in exterior or interior locations. Resistant to aging, weathering, UV radiation, water, detergent, alcohol and the influence of chemicals. End use temperature range, long term exposure 0°F up to 190°F; short term exposure 0° F up to 400° F. Shelf life of adhesive prior to installation is one year when stored at 75°F and 50% relative humidity or less.