





UL CERTIFIED FOR USE IN THE US AND CANADA

UL Certified Solution for Fire Doors When Either Removing Existing Hardware and/or Using a New Hardware Type Over Existing Hardware Prep's.

- Application Certified on both Hollow Metal and Wood Fire-Rated Doors, up to 90 Minutes
- Certified for Use in Combination With Gap Guard™ Fire Caulk to Fill Thru-Holes Between ½" Diameter and 2⅓" Diameter



PART NO.	DESCRIPTION
HP90 - 0.5	½" Diameter Hardware Prep Filler (10 Pack)
HP90 - 1.0	1" Diameter Hardware Prep Filler (10 Pack)
HP90 - 1.5	1½" Diameter Hardware Prep Filler (10 Pack)
HP90 - 2.0	2" Diameter Hardware Prep Filler (10 Pack)



POSITIVE PRESSURE TESTED MISCELLANEOUS FIRE DOOR ACCESSORY

## GAPGUARD™ FIRE CAULK







UL Certified Solution for Fire Doors and Frames to Seal Thru-Holes as well as in Combination With Other Hardware Prep Filler Solutions.

UL CERTIFIED FOR USE IN THE US AND CANADA

## PRODUCT INFORMATION

- Application Certified on both Hollow Metal and Wood Fire-Rated Doors, up to 90-Minutes
- Ocan be Used to Fill up to a ½" Diameter Thru-Hole
- Fully Cured in 24 Hours
- On be Sanded and Painted after Full Cure
- Indoor Use Only
- Shelf Life is 12 Months
- o 10.3 fl. oz. Cartridge
- 10 Tubes per Box
  Color: Tan



POSITIVE PRESSURE TESTED MISCELLANEOUS FIRE DOOR ACCESSORY

