

**ACCESSORIES**



663\*

**Motion Sensor**

- » 4-3/4" x 3-3/16" x 2" projection
- » Unidirectional
- » Black cover
- » SPDT relay
- » Adjustable angle pattern
- » 24 VDC input
- » Must not be placed where motion of door can be sensed



500 & 530

**Switch Post**

- » 4" x 6" x 40" x 3/16" wall thickness
- » 9 volt battery
- » RF temperature range: -4° F to 122° F
- » 689 (aluminum) or 690 (dark bronze) finishes; specify when ordering
- » Standard formed plastic cap
- » Surface mounted (above ground)
- » 530 - radio frequency transmitter
- » 500 - hard wired switch
- » 530POST - post only; switch not included



6000SEC

**Security Plate Package**

- » Conceals the ON/OFF/HOLD OPEN (ON/OFF) switch to deter tampering. Packed standard with the operator.



585

**Presence Detector**

- » Diffused active infrared technology
- » 11.8" l x 1.9" h x 1.9" w
- » Black anodized aluminum
- » 9'x0" maximum mounting height
- » Supply voltage: 24VAC/DC

\*Use of motion sensor must be approved by local authority having jurisdiction.

**Transmitters**



536

- » 2-3/8"w x 4-3/16"h x 15/16"d
- » Single channel



538

- » 2-3/8"w x 4-3/16"h x 15-16"d
- » Two channel



548

- » Converts existing hard wired push plates to work with RF receivers offered after June 2013
- » Single channel
- » 9 volt

**Radio Frequency Receiver**

- » 433 MHz



539

**Low Profile Push Plate**

- » 36" x 6" activation zone
- » 1" low profile depth
- » Stainless steel face plate
- » Adapts to either wireless or hardwired installations
- » 638 - Wireless
- » 639 - Hardwired

