

PARAMOUNT

12 SERIES

COMMERCIAL LOCKSETS

- Non-handed
 - For 1 3/8" (35mm) to 1 7/8" (48mm) door thickness
 - Standard backset 2 3/4" (70mm); optional 2 3/8" (60mm)
 - Latch with square corners faceplate
 - Standard ASA strike
 - Solid brass 6-pin tumbler cylinder
 - Standard Schlage "C" keyway
 - Rose cover conceals mounting screws
 - Easy installation, fits ANSI 115.2, 161 door prep
 - Wide variety of functions available
 - Conforms to ANSI A156.2 series 4000, Grade 2
 - 3 hour UL fire rating
 - 1 year mechanical limited warranty
-



CONFORMS TO ANSI
GRADE 2



12 series standard duty locksets are recommended by door hardware specialists for use in multi-unit housing or standard commercial applications.

12 SERIES LOCKSETS

SPECIFICATION

All bored lever locksets shall be 12 Series. Locksets shall meet ANSI A156.2 Series 4000, Grade 2 specification and ANSI A117.1 Accessibility Code requirements. The locksets shall have 3 hour fire UL rating. The lock chassis shall be made of steel and zinc construction materials with corrosion resistance protection. The latch bolt shall be made of brass chrome plated material with 1/2" (12.7mm) throw and deadlocking feature on keyed functions. The standard latch bolt backset shall be 2 3/4" (70mm) and optional 2 3/8" (60mm). The latch face plate shall be made of corrosion protected steel, 1 1/8" x 2 1/4" (28.5mm x 57.1mm) with square corners. The trim shall be made of wrought brass and bronze, with levers made of pressure die cast zinc, plated to the required finish. The cylinder shall be solid brass with 6-pin tumbler and a standard Schlage "C" keyway. **OPTIONAL:** finishes, latches, keyways, keying, backsets and strikes.

SIZE CHART & SELECTION GUIDE

SERIES	A	B	C	D	E
12-L	3 11/32 (85.0)	2 7/8 (72.8)	5/8 (15.5)	5 5/32 (130.8)	1 3/8 to 1 7/8 (35 to 48)

MODEL NUMBER	FUNCTION	FINISH	QTY PER CASE	WEIGHT LBS / KG
12-L00	Dummy	3, 26D	20	33.2 / 15.1
12-L10	Passage		10	43.4 / 19.7
12-L40	Privacy		10	44.8 / 20.3
12-L53	Entrance		10	46.2 / 21.0
12-L53C	Entrance, with clutch		10	44.2 / 20.1
12-L70	Classroom		10	45.8 / 20.8
12-L70C	Classroom, with clutch		10	44.0 / 20.0
12-L72*	Communication		10	45.0 / 20.5
12-L72C*	Communication, with clutch		10	41.0 / 18.6
12-L80	Storeroom		10	40.8 / 18.5
12-L80C	Storeroom, with clutch		10	38.8 / 17.6
12-L82*	Institution or utility		10	42.8 / 19.5
12-L89	Exit		10	42.8 / 19.5

ORDERING EXAMPLE: **12-L** SERIES **53** FUNCTION **C** OPTION **-26D** FINISH

PARTS & ACCESSORIES

STRIKE-T	T-type strike, 1 1/8" (29mm) x 2 3/4" (70mm)	SL234	2 3/4" (70mm) passage latch
ASA-T	ASA strike with adjustable tab	EXT5	Latch extension for 5" (127mm) backset
DL238	2 3/8" (60mm) deadlatch		
DL234	2 3/4" (70mm) deadlatch		
SL238	2 3/8" (60mm) passage latch		

STRIKE-T	ASA-T	DEADLATCH	SPRING LATCH	EXT5
				