



3-KNUCKLE FULL MORTISE CONCEALED BEARING

STANDARD WEIGHT.
4 1/2" x 4", 4 1/2" x 4 1/2"

Templates:

BB45



CB81 (ANSI A8112)
Steel-Polished and Plated or Bonderized and Prime Coated for Painting.

CB21 (ANSI A2112)
Brass-Polished and Plated

CB51 (ANSI A5112)
Stainless Steel-Polished and Satin Finish

- For medium weight doors receiving medium frequency service.
- Attractive slim barrel with flush pins and plugs.
- Concealed bearing for trouble free long life application.
- May be used on fire rated openings.
- Non-rising removable pin.
- For hospital type, add HT to suffix of part number.
- Hole in bottom tip for easy pin removal.
- All hinges are ANSI template.

GENERAL PRODUCT INFORMATION: PBB, Inc. template hinges are manufactured to close tolerances and meet all specifications and requirements set by the American National Standards Institute (ANSI).

HINGE SWAGING: A standard swaging of our standard weight full mortise hinge when closed to parallel position provides a 1/16" clearance between leaves.

MATERIAL GAUGE:

.134 ± .005 for 4-1/2" x 4"
.134 ± .005 for 4-1/2" x 4-1/2"

OTHER SPECIFICATIONS:

Height of hinge:
4.50 (+.000/-.015) for 4-1/2" x 4"
4.50 (+.000/-.015) for 4-1/2" x 4-1/2"

Width:
4.00 ± .015 for 4-1/2" x 4"
4.50 ± .015 for 4-1/2" x 4-1/2"

4-1/2" STANDARD SCREW SIZE

FHMS - 12-24 x 1/2"
FHWS - 12 x 1-1/4"

PACKAGING INFORMATION:

One hinge per plastic bag, 3 hinges and 1 screw pack per unit carton.
16 unit carton or 48 hinges per master shipping carton.
1 screw pack includes all machine screws (24), and 1/2 wood screws (12). ATMS & AWS also available.