

TECH-SPEC:

Product Reference Sheet

332_S_

Example: 332 | C | S | 36
 Profile# Finish Sponge Silicone Length

CATEGORY: Perimeter Gasketing

TYPE: Standard Perimeter Gasketing

FINISHES: C (Clear Anodized), D (Dark Anodized), G (Gold Anodized)


LENGTHS: Up to 120"

WIDTH: 1-1/16" (26.99 mm)

HEIGHT: 1/4" (6.35 mm)

WEIGHT: Estimated per foot: 0.2 lbs

RATINGS:



PRODUCT APPROVALS:

- 332_N has been tested and approved under UL10C for Fire
- BHMA A156.22-2011 Standard for Door Gasketing Systems
- ASTM E-283 for Air Infiltration
- ASTM E 90-2009 for Sound
- UL 1784 for Smoke and also meets the requirements for NFPA 105-2010
- Category J gaskets for use with listed steel frames and/or classified steel covered composite, hollow metal doors rated up to and including 3 hours; wood and plastic covered composite doors rated up to and including 1-1/2 hours; and wood core doors rated for 20 minutes.

ANSI NUMBER: R3E165

LEAD TIME: 4 working days (or less)

AVAILABLE: 332_S_ is shipped from PEMKO's Memphis, Ventura, Vancouver and Toronto locations

CROSS REFERENCE: Reese: 669

INSTRUCTIONS: Available upon request and on website

CAD DRAWINGS: Available upon request and on website

PROFILE DRAWINGS: Available upon request and on website

CUT SHEET: Available upon request and on website

www.pemko.com

Memphis, TN USA
P.O. Box 18966
Memphis, TN 3818
P: 800.824.3018
F: 800.243.3656

Ventura, CA USA
P.O. Box 3780
Ventura, CA 93006
P: 800.283.9988
F: 800.283.4050

Vancouver, BC Canada
103-2480 Mt. Lehman Rd.
Abbotsford, BC V2T 6W3
P: 877.535.7888
F: 877.535.7444

Toronto, ON Canada
160 Four Valley Dr.
Vaughan, ON L4K 4T9
P: 877.535.7888
F: 877.535.7444